

COLORADO OIL AND GAS CONSERVATION COMMISSION  
SUNDRY NOTICES AND REPORTS OF WELLS

JUL 15 1964

OIL & GAS  
CONSERVATION COMMISSION

(Indicate nature of data by checking below)

## Locate Well Correctly

Notice of intention to drill (attach plat) \_\_\_\_\_  
 Notice of intention to change plans \_\_\_\_\_  
 Notice of date for test of water shut-off \_\_\_\_\_  
 Report on result of test of water shut-off \_\_\_\_\_  
 Notice of intention to re-drill or repair well \_\_\_\_\_  
 Notice of intention to clean out well \_\_\_\_\_  
 Statement of shooting \_\_\_\_\_  
 Statement of perforating \_\_\_\_\_  
 Notice to pull or otherwise alter casing \_\_\_\_\_  
 Notice of intention to abandon well xxx \_\_\_\_\_  
 Report of work done on well since previous report \_\_\_\_\_


Notice to do work	<input checked="" type="checkbox"/>
Report of work done	<input type="checkbox"/>

Land: Fee and Patented ☒ State ☐

Lease No.

Colorado  
State

Logan  
County

Atwood  
Field

J-9	Pomeroy	C SE SW SE	20	7N	53W	6th
(Well No.)	(Lease)	(1/4 Sec.)	(Sec.)	(Twp.)	(Range)	(Meridian)

The Well is located 330 Ft. <sup>SOUTH</sup> (N) of Section Line and 1650 Ft. <sup>(E)</sup> of ~~(S)~~ <sup>EAST</sup> (W) Section Line.

The elevation above sea level is 4100 Ft. K.B.

Details of Plan of Work: (State names of and expected depths to objective sands. Show sizes, weights, and length of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work.)

The above-described well being depleted of economic primary reserve with current production less than 3 barrels of oil per day at a 92 percent water-cut and having no application for remedial work or secondary recovery, we propose to abandon the well employing the following procedure:

T.D. 4734' - The 5-1/2" casing will be shot off at approximately 3700' and attempts made to recover that amount. Cement plugs will be placed as follows:

Plug No. 1	-	4734'	-	4600'	-	20 sacks cement
		4600'	-	190'	-	Heavy mud
Plug No. 2	-	190'	-	140'	-	10 sacks cement
		140'	-	20'	-	Heavy mud

Plug No. 3 - 20' - Surface - 5 sacks cement with regulation  
marker secured in cement.

The location will be cleared of all debris and appurtenances.

Approved: JUL 17 1964

Date July 8, 1964

Company **AMAX PETROLEUM CORPORATION**

Address Box 2250 - Casper, Wyo.

By Allen Thomas  
Allen Thomas

Title	Dist.	Production	Superintendent

DVR	
WRS	
HMM	
JAM	
FJP	✓
JJD	✓
FILE	

Submit reports of proposed work, for approval, on this form in Duplicate for patented lands and in Triplicate for school and state lands.