

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY



00065700

LEASE
C-10485

RECEIVED
SEP 19 1985

COLO. OIL & GAS CONS. COMM.

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well gas well other

2. NAME OF OPERATOR
Coseka Resources (U.S.A.) Ltd.

3. ADDRESS OF OPERATOR
200 Writer Square, 1512 Larimer St., Denver, CO

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1494' FWL, 1967' FSL, Sec. 31-T1N-R102W
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: Same

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
Taiga Mountain

8. FARM OR LEASE NAME
Federal

9. WELL NO.
5-31-1N-102

10. FIELD OR WILDCAT NAME
Banta Ridge

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 31-T1N-R102W

12. COUNTY OR PARISH
Rio Blanco

13. STATE
Colorado

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
5690' GL

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input checked="" type="checkbox"/>	<input type="checkbox"/>
(other)		

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

WELL BORE DATA: See Attached

PROPOSED PROCEDURE:

- 1) Spot cement plug across Mesa Verde perms 1211'-1370' (159')
- 2) Load hole with 9 ppg mud laden fluid
- 3) Spot 100' cement plug 50' below to 50' above surface casing shoe 481'-581'
- 4) Set 50' cement plug at surface
- 5) Erect dry hole marker. Re-hab location.

NRS
FJP
MHM
<input checked="" type="checkbox"/>
PCC
LAR
CCM
ED

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Terry Cox TITLE District Superintendent DATE 9/17/85

(This space for Federal or State office use)

APPROVED BY William Smith TITLE DIRECTOR DATE SEP 25 1985
CONDITIONS OF APPROVAL, IF ANY: O & G Cons. Comm.

RECEIVED

SEP 19 1985

COLO. OIL & GAS CONS. COMM.

COSEKA RESOURCES (USA) LTD
TAIGA MTH UNIT No. 5(6)-31-114-102
1494' FWL, 1967' FSL SEC. 31 T11N R102W
RIO BLANCO COUNTY, COLORADO
LEASE No. C-10485

