



99999999

103-06370

STATES
THE INTERIOR
CAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐ MAR 22 1967

2. NAME OF OPERATOR
Rosen Oil Co. COLO. OIL & GAS CONS. COMM.

3. ADDRESS OF OPERATOR
139 N. Mead St., Wichita, Kansas 67202

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface NE-SW-SE of Sec. 10, T.1 N., R.102 W., 6th P.M.
1802' fr. E-line, & 1223' fr. S-line of Sec. 10

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
Grd. 5545'

6. INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
L. B. Baker

9. WELL NO.
Rosen #2894-1

10. FIELD AND POOL, OR WILDCAT W.
Castlegate-wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 10, T.1 N., R.102 W., 6th P.M.

12. COUNTY OR PARISH 13. STATE
Rio Blanco Colorado

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐ FULL OR ALTER CASING ☐
 FRACTURE TREAT ☐ MULTIPLE COMPLETE ☐
 SHOOT OR ACIDIZE ☐ ABANDON* ☒
 REPAIR WELL ☐ CHANGE PLANS ☐
 (Other) ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐ REPAIRING WELL ☐
 FRACTURE TREATMENT ☐ ALTERING CASING ☐
 SHOOTING OR ACIDIZING ☐ ABANDONMENT* ☒
 (Other) ☐ No Prior Approval

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Well was drilled to a total depth of 4300 feet on Jan. 4, 1967. Some oil was encountered in the hole but was not sufficient to make a commercial well; therefore, the well was plugged and abandoned on January 4, 1967. The surface casing was pulled 310 feet of 4-in. casing. A cement plug of 25 sacks was installed from 325 feet to 200 feet to seal off the Castlegate sandstone. Another plug of 5 sacks was installed at the bottom of the conductor casing from 25' to 15'. A well marker and cement plug will be placed at the surface as soon as roads permit access to the location.

DVR	
FJP	<input checked="" type="checkbox"/>
HHM	
JAM	
JJD	<input checked="" type="checkbox"/>

18. I hereby certify that the foregoing is true and correct

SIGNED H. Don Singley TITLE Cons. Geol.

DATE Mar. 20, 1967

(This space for Federal or State office use)

APPROVED BY H. Rogers TITLE Director

DATE MAR 24 1967

CONDITIONS OF APPROVAL, IF ANY:

COLO. OIL & GAS COMM.

*See Instructions on Reverse Side



00065505