

UNITED STATES
DEPARTMENT OF THE
GEOLOGICAL SURVEYPLICATED*
MS OR RE-Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

Fee Lease

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

12. COUNTY OR PARISH 13. STATE

14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)

1. OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

Theo Wood

3. ADDRESS OF OPERATOR

280 W. Haven Ave., Salt Lake City, Utah

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

SE-NW-SE Sec.12, T. 1 N., R. 103 W., 6th P.M.
1383.7 ft. from S-line and L846.0 ft. from
E-line of Sec. 12

6th P.M.

Rio Blanco Wyoming

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

☐
☐
☒
☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

☐
☐
☐☐
☐
☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Gas and oil were encountered in this well between 3800 feet and total depth at 6290 feet in various siltstone and limestone lenses. The amount was estimated to be about 30 to 50 barrels of oil per day. The operators decided that this was not enough to warrant completion so have made plans to abandon the hole. A cement plug will be placed at the bottom of the intermediate casing, from 2810 to 2860 feet. The plug will take about 20 sacks of cement in a dry hole. The intermediate casing will then be shot off at the free point and pulled from the hole. A cement plug plus well marker will be placed at the surface.

18. I hereby certify that the foregoing is true and correct

SIGNED

H. Don Gungley

TITLE Consulting Geologist

DATE Mar. 30, 1966

(This space for Federal or State office use)

APPROVED BY

W. Rogers

TITLE

Director

DATE

MAY 3 1966

CONDITIONS OF APPROVAL, IF ANY:

COLO. OIL & GAS COMM.

*See Instructions on Reverse Side