

OIL AND GAS CONSERVATION COMMISSION
OF THE STATE OF COLORADO

00053454

PLUGGING RECORD

INSTRUCTIONS

Within thirty (30) days after the plugging of any well, the owner or operator thereof shall file this form in duplicate for wells on Patented or Federal lands, and in triplicate for wells on State lands, give a detailed account of the manner in which the abandonment or plugging work was carried out, including the nature and quantities of materials used in plugging and the location and extent (by depths) of the plugs of different materials; records of the amount, size and location (by depths) of casings and junk left in the well; and a detailed statement of the volume and weight of mud fluid used.

Operator Equity Oil Company Field Shale Oil Wildcat X
 Lease Name Federal C-072924 Well No. 1 County Rio Blanco
 Location SE $\frac{1}{4}$ NE $\frac{1}{4}$ Section 2 Township 1N Range 103W Meridian 6thPM
 (Quarter Quarter)
 Corrected Location 2570 feet from N Section line and 1320 feet from E Section Line
 N or S E or W

TOTAL DEPTH 6100'DATE OF PLUGGING 12/22/63

Valid 12/23/63

DETAILS OF WORK

Due to Surface Topography moved location West & North approximately 100'. Set 10-3/4" 32.75# H-40 casing at 37.5' K.B. Cemented to surface with 22 sacks. Drilled with mud to 2481'. Set 7" - 23# new & used casing at 2471' and cemented with 125 sacks. Drilled with air to 6100'. No oil or moisture encountered. Per U.S.G.S, set Cast Iron Bridge Plug at 2350' w/10 sacks cement on top. Shoot off 7" at 1600' - recover, mud hole and put cement with marker in 10-3/4".

DVR	
WRS	
HHM	
JAM	
FJP	<input checked="" type="checkbox"/>
JJD	<input checked="" type="checkbox"/>
FILE	

I/we hereby swear (or affirm) that the statements herein made are a full and correct report:

Approved:

Date DEC 27 1963Director Al Rogers

Company Equity Oil Company Date 12/23/63
806 American Oil Bldg.
 Address Salt Lake City, Utah Phone No. DA 2-0429
 By C.E. Johnson Title Engineer
 (Signature)