THE WIRELINE GROUP

Radial Cement Bond
Gamma Ray
Casing Collar Log

Company	Caerus Oil and Gas LLC.
Well	BJU M33A FED 14B-32-496
Field	Grand Valley
County	Garfield
State	Colorado

Company Caerus Oil and Gas LLC.
Well BJU M33A FED 14B-32-496
Field Grand Valley
County Garfield State Colorado

Location: API #: 05-045-18721
SEC 33 TWP 4S RGE 96W

Other Services
CNL

Permanent Datum Ground Level Elevation 8403'
Log Measured From Kelly Bushing
Drilling Measured From Kelly Bushing

Elevation
K.B. 8433'
D.F. 8433'
G.L. 8403'

Date	19-NOV-2023
Run Number	One
Depth Driller	11697'
Depth Logger	11468'
Bottom Logged Interval	11455'
Top Log Interval	Surface
Open Hole Size	8.750"
Type Fluid	Fresh Water
Density / Viscosity	8.34 lb/gal
Max. Recorded Temp.	284°F
Estimated Cement Top	See Log
Time Well Ready	ROA
Time Logger on Bottom	14:30
Equipment Number	8102
Location	Grand Junction
Recorded By	P. Edwards
Witnessed By	B. Ellis

Borehole Record				Tubing Record		
Run Number	Bit	From	To	Size	Weight	From	To

Casing Record	Size (in)	Wgt (lbs/Ft)	Grade	Top	Bottom
Surface Casing	9.625	36.0	J-55	Surface	3001'
Intermediate #1	4.5	13.5	P-110	Surface	11678'
Intermediate #2					
Liner					

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

Log ran as per customer request.
Depth referenced to Kelly Bushing @ 30'
Marker Joint from 7530' - 7539'

Log ran with 0 PSI surface induced pressure.

Thank you for choosing The Wireline Group!!!

THE WIRELINE GROUP

Main Pass 5" = 100'

Database File	caerus_bju_m33_fed_14b-32-496_rcbl_cnl\caerus_bju_m33_fed_14b-32-496_rcbl_cnl.db
Dataset Pathname	main
Presentation Format	twgrcbl
Dataset Creation	Sat Nov 18 14:34:43 2023
Charted by	Depth in Feet scaled 1:240

Gamma Ray		3' Amplitude	5' Variable Density Log	Sector Map	Average Amplitude
0 (GAPI) 150		0 (mV) 100	200 (usec) 1200		0 120
Line Tension		3' Amplitude x 5			Mimimum Amplitude
0 (lb) 4000		0 (mV) 20			0 120
-9 CCL$1 1		3' Travel Time			Maximum Amplitude
0 Temp (degF) 300		650 (usec) 150			0 120

134.2
135.5
3800
137.0
138.3
3900
139.4
141.1
4000
142.1
143.3
4100
144.0
145.0
4200
169.5
5500
170.5
171.4
5600
172.1
173.1
5700
174.0
174.8
5800
175.5
176.4
5900
208.4
7400
209.2
210.1
7500
Marker Joint
210.7
210.7
7600
211.6
213.4
7700

THE WIRELINE GROUP

Repeat Pass 5" = 100'

Database File	caerus_bju_m33_fed_14b-32-496_rcbl_cnl\caerus_bju_m33_fed_14b-32-496_rcbl_cnl.db
Dataset Pathname	repeat1
Presentation Format	twgrcbl
Dataset Creation	Sat Nov 18 14:28:57 2023
Charted by	Depth in Feet scaled 1:240





Calibration Report

Database File c:\programdata\warrior\data\caerus_bju_m33_fed_14b-32-496_rcbl_cnl\caerus_bju_m33_fed_14b-32-
Dataset Pathname main
Dataset Creation Sat Nov 18 14:34:43 2023

Compensated Neutron Calibration Report

Serial Number: FW1409-35
Tool Model: 275Dig

TANK CALIBRATION Mon Jan 30 16:01:15 2023

	Tool Ratio	Tank Ratio	K-Factor
Tank Calibration	10.9772	11.6940	1.0653

Detector	Readings	
Short Space	765.97	cps
Long Space	69.78	cps

Gamma Ray Calibration Report

Serial Number:	110255	
Tool Model:	GCT275-0001	
Performed:	Thu Jul 6 13:26:01 2023	
Calibrator Value:	150.4	GAPI
Background Reading:	72.3	cps
Calibrator Reading:	300.9	cps
Sensitivity:	0.6579	GAPI/cps

Inclinometer Calibration Report

Performed: (Not Performed)

	Low Read.	High Read.	Low Ref.	High Ref.	
X Accelerometer	0.00	1.00	0.00	1.00	gee
Y Accelerometer	0.00	1.00	0.00	1.00	gee
Z Accelerometer	0.00	1.00	0.00	1.00	gee

Segmented Cement Bond Log Calibration Report

Serial Number:	FW1906-032	
Tool Model:	Probe275acc	
Calibration Casing Diameter:	4.500	in
Calibration Depth:	408.675	ft

Master Calibration, performed Thu Nov 16 10:37:44 2023:

	Raw (v)		Calibrated (mv)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
3'	0.006	0.745	0.150	81.196	109.612	-0.471
CAL	0.008	0.742				
5'	0.007	0.645	0.150	81.196	126.968	-0.747
SUM						
S1	0.008	0.737	0.000	100.000	137.054	-1.029
S2	0.007	0.712	0.000	100.000	141.811	-1.032
S3	0.007	0.717	0.000	100.000	140.727	-0.943
S4	0.006	0.730	0.000	100.000	138.238	-0.883
S5	0.006	0.755	0.000	100.000	133.649	-0.861
S6	0.008	0.767	0.000	100.000	131.730	-1.024
S7	0.007	0.780	0.000	100.000	129.383	-0.899
S8	0.006	0.777	0.000	100.000	129.680	-0.766

Internal Reference Calibration, performed (Not Performed):

	Raw (v)		Calibrated (v)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
CAL	0.000	0.000	0.008	0.742	1.000	0.000

Air Zero Calibration, performed Thu Nov 16 10:33:06 2023:

	Raw (v)	Calibrated (v)	Results
	Zero	Zero	Offset
3'	0.000	0.000	0.000
5'	0.000	0.000	0.000
SUM			
S1	0.000	0.000	0.000
S2	0.000	0.000	0.000
S3	0.000	0.000	0.000
S4	0.000	0.000	0.000
S5	0.000	0.000	0.000
S6	0.000	0.000	0.000
S7	0.000	0.000	0.000
S8	0.000	0.000	0.000

Inclinometer Calibration Report

Performed: (Not Performed)

	Low Read.	High Read.	Low Ref.	High Ref.	
X Accelerometer	0.00	1.00	0.00	1.00	gee
Y Accelerometer	0.00	1.00	0.00	1.00	gee
Z Accelerometer	0.00	1.00	0.00	1.00	gee

Sensor	Offset (ft)
GCT_FMWR	20.18
mSec_Count	20.18
RBT_Status	20.18
Error_Ct	20.18
WVFS8	14.63
WVFS7	14.63
WVFS6	14.63
WVFS5	14.63
WVFS4	14.63
WVFS3	14.63
WVFS2	14.63
WVFS1	14.63
WVF3FT	14.63
WVF5FT	13.63
RBT_ACCZ	10.38
RBT_ACCY	10.38
RBT_ACCX	10.38
GCT_HV	10.38
WVFSYNC	10.38
WVFCAL	10.38
CCL$2	9.53
CCL$1	9.53
GCT_Temp	8.78
GR	8.03
GCT_IntTemp	7.04
GCT_ACCZ	5.37
GCT_ACCY	5.37
GCT_ACCX	5.37
CNLSC	2.05
CNSSC	1.61

Schematic



Description	Length (ft)	O.D. (in)	Weight (lb)
STD BLCH-14375 Standard 1-7/16" Braided Line Cable Head with 1" Fishing Neck	1.04	1.44	1.00
SO BS CENT-2750-4500 Slip Over 2-3/4" I.D. for 4-1/2" O.D. Casing Bow Spring Centralizer	1.33	3.25	10.00
RBT8acc-Probe275acc (FW1906-032) 2.75" Radial Corrosion with accelerometer	8.75	2.75	110.00
SO BS CENT-2750-4500 Slip Over 2-3/4" I.D. for 4-1/2" O.D. Casing Bow Spring Centralizer	1.33	3.25	10.00
GCacc-GCT275-0001 (110255) Probe 2.75" 6 Pin Gamma Ray - CCL w/ Temp	5.01	2.75	55.00
CNT-275Dig (FW1409-35) Probe Digital CNL	5.24	2.75	40.00
SO BS CENT-2750-4500 Slip Over 2-3/4" I.D. for 4-1/2" O.D. Casing Bow Spring Centralizer	1.33	3.25	10.00
Sealed-77835 77835	0.14	1.70	2.00

Dataset: caerus_bju_m33_fed_14b-32-496_rcbl_cnl.db: field/well/run1/main
Total length: 20.18 ft
Total weight: 238.00 lb
O.D.: 3.25 in

Company	Caerus Oil and Gas LLC.
Well	BJU M33A FED 14B-32-496
Field	Grand Valley
County	Garfield
State	Colorado

TWG
THE WIRELINE
GROUP

Radial Cement Bond
Gamma Ray
Casing Collar Log