

WELL NAME: HASSLER #27, API #: 043-40015, INSP. # 695109054



PHOTO 1: WELL SIGN





PHOTO 2: LOCATION





PHOTO 3: WELLHEAD AND EQUIPMENT





PHOTO 4: TANK BATTERY





PHOTO 5: GAUGE HATCH IS NOT LATCHED. Close and seal gauge hatches when not accessing tank per Rule 608.a.(9). 24 HOURS TO ADDRESS. Tanks will function as sealed and ventless with gas released only through a vapor control system or properly sized pressure relief valve. per Rule 608.a.(9). 24 HOURS TO INSTALL PRESSURE RELIEF VALVE. THIS IS THE SECOND NOTICE IMMEDIATE ACTION IS REQUIRED.



PHOTO 6: NO PRESSURE RELIEF VALVE INSTALLED ON CRUDE OIL TANK. Close and seal gauge hatches when not accessing tank per Rule 608.a.(9). 24 HOURS TO ADDRESS. Tanks will function as sealed and ventless with gas released only through a vapor control system or properly sized pressure relief valve. per Rule 608.a.(9). 24 HOURS TO INSTALL PRESSURE RELIEF VALVE. THIS IS THE SECOND NOTICE IMMEDIATE ACTION IS REQUIRED.

