



PHONE 522-1206 AREA 303

VIRG'S TESTERS, INC.

BOX 712 STERLING, COLORADO

Company Operating Well:

Buttes Gas & Oil Co.

Address:

See Slip

Contractor and Rig No.:

Murfin Drlg. Co. Rig # 4 1/2

Well Name and No.:

J. Nicklas # 2

County State

Weld Colorado

Sec. Twnp. Rng.

24 9 N 56 W


Ticket DST No. Tester

7617 1 Rittenhouse

Date of Test and Formation Tested

9-2-65 "D" Sand

T# 7617 R# 1105



	Field Pressure	Corrected Pressure	RESULTS		No. Final Copies	12
Initial Hydrostatic: A	3074	3078	Total Depth	5619	Interval Tested	5588 to 5619
Final Hydrostatic: G	3063	3057	Tool open	none	Min. before Initial Shut-in	none Min.
Initial Flow: D	98	113	Tool open	90	Min. Total Final Shut-in	30 Min.
Final Flow: E	404	410	Tool open @	4:45 p. M.	Mud Wt.	9.8 Viscosity 70
Initial Shut-in:			Did well flow Gas?	Yes	Oil?	No Water? No
Final Shut-in: F	1306	1316	Was blow measured?	No, was too small to measure.		
Pressure below bottom packer bled to:			Top Choke	1"	Bottom Choke	9/16"
			Size and Wt. D.P.	4 1/2"	16.60	
			Recorder No.	1105	Run at	5610 I.D. & Length of D.C.s
			Was this a straddle test?	No	Witnessed by:	Roland Young
			Recovery in Pipe	1125' total fluid.	90' clean oil - 180' heavily mud & gas cut oil (50% mud) and 855' water.	

REMARKS:


Tool opened with fair blow then built to strong blow in 2 minutes. Slight decrease after 30 minutes. Gas to surface in 41 minutes but was too small to measure. BHT 174°.

Test Conclusive.

Note: adjust test depths 5' down hole to agree with log depths.

T* 7618

R* 1105



Company Operating Well:

Buttes Gas & Oil Co.

Address:

See Slip

Contractor and Rig No.:

Murfin Drlg. Co. Rig # 4

Well Name and No.:

J. Nicklas # 2

County State

Weld Colorado

Sec. Twnp. Rng.

24 9 N 56 W

Ticket DST No. Tester

7618 2 Rittenhouse

Date of Test and Formation Tested

9-4-65 "J" Sand

	Field Pressure	Corrected Pressure	RESULTS		No. Final Copies
Initial Hydrostatic: A	3194	3198	Total Depth	5754	Interval Tested 5696 to 5706
Final Hydrostatic: G	3183	3176	Tool open	5	Min. before Initial Shut-in 30 Min.
Pre-Flow B	76	102	Tool open	93	Min. Total Final Shut-in 30 Min.
Initial Flow: D		222	Tool open @	7:35 p. M.	Mud Wt. 9.9 Viscosity 75
Final Flow: E	926	938	Did well flow Gas?	No	Oil? No Water? No
Initial Shut-in: C	1459	1465	Was blow measured?	No	
Final Shut-in: F	1459	1462	Top Choke	1"	Bottom Choke 9/16" Size and Wt. D.P. 4 1/2" FH
Pressure below bottom packer bled to:	2700	2650	Recorder No.	1105	Run at 5711 I.D. & Length of D.C.s 2 3/4" 88'
			Was this a straddle test?	Yes	Witnessed by: Roland Young
			Recovery in Pipe	2150'	water.

REMARKS:

Tool opened with weak blow. Built to strong blow in 6 minutes then decreased after 45 minutes. Good blow at end of test. BHT 174°. Packers slipped approx. 10" during test.

Test Conclusive.

CORE LABORATORIES, INC.

P.O. Box 1000, Rockwell, Texas

DALLAS TEXAS

Company **BUTTES OIL & GAS COMPANY**
 Well **NO. 2 NICKLAS**
 Field **WILDCAT**
 County **WELD** State **COLORADO**
 Location **NW NE 24-2N-56W**

Formation **"D" SAND**
 Core **DIAMOND**
 Drilling Fluid **WBM**
 Elevation **4429** KE est.
 Remarks **CONVENTIONAL ANALYSIS**

Page **1** of **1**
 File **RF-2-3127**
 Date Report **9/2/55**
 Analysts **PARKER**

CORE ANALYSIS RESULTS

Report made by **Core Laboratories, Inc.**

SAMPLE NUMBER	DEPTH FEET	PERMEABILITY MILLIDARIES		GRANULARITY PERCENT	SAND CONTENT PERCENT		TOTAL SAND PERCENT	PERCENT PRODUCTION	REMARKS
		VERTICAL	LABORATORY		GRANULARITY	PERCENT			
1	5585-86	2.1	0.6	8.2	6.1	26.8			ss, fg
2	88-89	140	109	13.4	11.2	35.1			ss, fg, VERTICAL FRACTURE
3	89-90	209	182	12.5	12.0	27.2			ss, fg
4	5590-91	38	14	12.0	7.5	36.8			ss, fg

NOTE: to agree w/ log, adjust
 5' down hole.

**BEST IMAGE
 AVAILABLE**

PRELIMINARY COPY

NOTE:

* REFER TO ATTACHED LETTER
 FOR COMPLETE CORE ANALYSIS IN INTERPRETATION RESERVED

2. CORE LABORATORIES, INC. PRESENTS INTERPRETATION OF RESULTS

These analyses, opinions or interpretations are based on observations and material supplied by the client to whom, and for whose exclusive and confidential use this report is made. The interpretations and opinions expressed represent the best judgment of Core Laboratories, Inc. and its officers and employees, who accept no responsibility and make no warranty or representation as to the productivity, proper operation, or profitability of any oil, gas or other mineral well or sand in connection with which such report is used or relied upon.