
Main Page
Log Viewer
Data Manager
Help
Log Viewer
Data Manager
Help
Main Page
Log Viewer
Data Manager
Help
Main Page
Log Viewer
Data Manager
Help
Main Page





Repeat Section

Log ran under 2800 PSI surface-induced pressure
5"=100'

Database File	0512352254_lizzy north 36-9hz_oxy.db
Dataset Pathname	cbl/pass1
Presentation Format	rbt-gct8acc
Dataset Creation	Mon Mar 04 08:58:45 2024
Charted by	Depth in Feet scaled 1:240





Calibration Report

Database File	0512352254_lizzy north 36-9hz_oxy.db
Dataset Pathname	cbl/pass1
Dataset Creation	Mon Mar 04 08:58:45 2024

Gamma Ray Calibration Report

Serial Number:	FW1304-53	
Tool Model:	50-GCT275-0000	
Performed:	Mon Feb 26 11:20:49 2024	
Calibrator Value:	150.0	GAPI
Background Reading:	68.9	cps
Calibrator Reading:	282.0	cps
Sensitivity:	0.8868	GAPI/cps

Inclinometer Calibration Report

Performed: Tue Feb 14 16:38:09 2023

	Low Read.	High Read.	Low Ref.	High Ref.	
X Accelerometer	-903.00	899.00	-1.00	1.00	gee
Y Accelerometer	-904.00	899.00	-1.00	1.00	gee
Z Accelerometer	7.93	-896.20	0.00	1.00	gee

Segmented Cement Bond Log Calibration Report

Serial Number:	100109_5.5	
Tool Model:	Probe27Sacc	
Calibration Casing Diameter:	5.500	in
Calibration Depth:	2158.601	ft

Master Calibration, performed Mon Feb 26 12:59:15 2024:

	Raw (v)		Calibrated (mv)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
3'	0.000	0.850	1.000	71.921	92.950	1.857
CAL	-0.014	1.001				
S	0.000	0.820	1.000	71.921	86.125	1.050
SUM						
S1	0.000	0.828	0.000	100.000	130.687	-0.001
S2	0.000	0.789	0.000	100.000	137.905	-0.001
S3	0.000	0.812	0.000	100.000	136.347	-0.001
S4	0.000	0.859	0.000	100.000	126.285	-0.001
S5	0.000	0.917	0.000	100.000	123.614	-0.001
S6	0.000	0.937	0.000	100.000	118.836	-0.001
S7	0.000	0.910	0.000	100.000	123.156	-0.001
S8	0.000	0.874	0.000	100.000	126.488	-0.001

Sensor	Offset (ft)	Schematic	Description	Length (ft)	O.D. (in)	Weight (lb
GCT_FMWR	14.89					
mSec_Count	14.89		Cable Head-Titan_144 1 7/16" Titan Cable Head	1.03	1.44	2.00
RBT_Status	14.89					
Error_Ct	14.89					
			SO BS CENT-2750-4500 Slip Over 2-3/4" I.D. for 4-1/2" O.D. Casing Bow Spring Centralizer	1.33	3.25	10.00
			RBT8acc-Probe27sacc (100109_5.5) 2.75" Radial Corrosion with accelerometer	8.75	2.75	110.00
WVFS8	9.35					
WVFS7	9.35					
WVFS6	9.35					
WVFS5	9.35					
WVFS4	9.35					
WVFS3	9.35					
WVFS2	9.35					
WVFS1	9.35					
WVFSFT	9.35					
WVFSFT	8.35					
RBT_HV	5.10					
RBT_ACCZ	5.10					
RBT_ACCY	5.10					
RBT_ACCX	5.10					
WVFSYNC	5.10					
WVFCAL	5.10					
GCT_HV	5.09					
CCLS2	4.14		SO BS CENT-2750-4500 Slip Over 2-3/4" I.D. for 4-1/2" O.D. Casing Bow Spring Centralizer	1.33	3.25	10.00
CCLS1	4.14					
GCT_Temp	3.59		GCT_acc-50-GCT275-0000 (FW1304-53) Probe 2.75" Gamma Ray - CCL w/Temp (Single Pin)	4.77	2.75	55.00
GR	2.72					
GCT_IntTemp	2.00					
GCT_ACCZ	0.33					
GCT_ACCY	0.33					
GCT_ACCX	0.33		Plug-FA108-0000 1.38" Bull Plug	0.33	1.38	1.00

Dataset:	0512352254_lizzy north 36-9hz_oxy.db: field/well/cbl/pass2
Total length:	14.89 ft
Total weight:	198.00 lb
O.D.:	3.25 in

Company	Occidental Petroleum Corp.
Well	Lizzy North 36-9HZ
Field	Wattenberg
County	Weld
State	Colorado
Country	USA