

OIL AND GAS CONSERVATION COMMISSION
OF THE STATE OF COLORADO

PLUGGING RECORD



00226816

INSTRUCTIONS

Within thirty (30) days after the plugging of any well, the owner or operator thereof shall file this form in duplicate for wells on Patented or Federal lands, and in triplicate for wells on State lands, give a detailed account of the manner in which the abandonment or plugging work was carried out, including the nature and quantities of materials used in plugging and the location and extent (by depths) of the plugs of different materials; records of the amount, size and location (by depths) of casings and junk left in the well; and a detailed statement of the volume and weight of mud fluid used.

Operator The California Company Field New Windsor Wilcat
Lease Name Adella Nash Well No. 1 County Weld
Location SW, NE Section 27 Township 7N Range 67W Meridian 6th P.M.
(Quarter Quarter)
1981 feet from N Section line and 1984 feet from E Section Line
N or S E or W

TOTAL DEPTH

4316 4327

DATE OF PLUGGING

5/2/60

DETAILS OF WORK

The subject well was plugged and abandoned May 2, 1960 as follows:

50 sx. cement 3887 to 4325 - across Sussex perms 4295-4312
15 sx. " 0 to 131 - surface plug

The following casing was left in the well:

Surface casing - 9 5/8", 40#, J-55 from zero - 131'
Oil string - 5 1/2", 14#, J-55 from zero - 4330'

The hole between the cement plugs was left full of gel mud weighing 9.0#/gal.

AJJ	
DVR	
WRS	
HHM	
JAM	
FJP	✓
JJD	✓
FILE	

I/we hereby swear (or affirm) that the statements herein made are a full and correct report:

Approved:

Date May 16 1960

Director

Company The California Company Date 5/12/60Address Box 1769, Casper, Wyoming Phone No. 23-4-6911By [Signature] Title Area Prod. Engr.
(Signature)