

396

COLORADO OIL AND GAS CONSERVATION COMMISSION  
SUNDRY NOTICES AND REPORTS OF WELLS



RECEIVED  
JUN 30 1953  
OIL & GAS  
CONSERVATION COMMISSION

(Indicate nature of data by checking below)

- Notice of intention to drill \_\_\_\_\_
- Notice of intention to change plans \_\_\_\_\_
- Notice of date for test of water shut-off \_\_\_\_\_
- Report on result of test of water shut-off \_\_\_\_\_
- Notice of intention to re-drill or repair well \_\_\_\_\_
- Notice of intention to clean out well \_\_\_\_\_
- Statement of shooting \_\_\_\_\_
- Statement of perforating \_\_\_\_\_
- Notice to pull or otherwise alter casing \_\_\_\_\_
- Notice of intention to abandon well   x
- Report of work done on well since previous report \_\_\_\_\_

Following is a (notice of intention to do work) June 29 19 53  
~~(report of work done)~~ (~~land~~) (patented) described as follows:

|                 |                   |                     |
|-----------------|-------------------|---------------------|
| <u>Colorado</u> | <u>Weld</u>       | <u>Wildcat</u>      |
| State           | County            | Field               |
| <u>1</u>        | <u>J. Nicklas</u> | <u>NW/4 17</u>      |
| (Well No.)      | (Lease)           | (Sec. and 1/4 Sec.) |
|                 |                   | <u>9N</u>           |
|                 |                   | <u>56W</u>          |
|                 |                   | (Range) (Meridian)  |

The well is located 330 ft. (N) of S Line and 330 ft. (E) of East line of NW/4 Section 17-9N-56W  
(S) (W)

The elevation above sea level is 4508 ft.

Details of Plan of Work: (State names of and expected depths to objective sands: Show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work.)

We propose to plug and abandon the captioned well by placing heavy mud, taken from the bottom of the mud pits, from 7270 ft. (total depth) to 5900 ft. A cement plug will then be placed from 5900 ft. to 5800 ft. (opposite Dakota sandstone) heavy mud will then be placed to 626 ft. (15 ft. below bottom of the surface pipe) with a cement plug from 626 ft. to 596 ft. Then heavy mud will be placed from 596 ft. to 15 ft. with a cement plug being spotted to the surface in such a manner as not to interfere with surface cultivation.

Approved: JUN 30 1953  
J. J. Zouichah  
Director

Company Shell Oil Co.  
Address Denham Bldg. Denver, Colo.  
By W. H. Inabrud  
Title Division Production Supt.

Submit reports of proposed work, for approval, on this form in Duplicate for patented lands and in Triplicate for school and state lands.  
Verbal approval was received to plug and abandon well on June 26, 1953.