

County Line 3229-22H



DESCRIPTION DEPTH		WELLBORE											Date	5/23/2024					
TOC (CBL Verified):		1,477'											WELL:	County Line 3229-22H	Pre-Frac WBD				
Sfc Casing Shoe:		2,506'											LOCATION:	SWSE Sec 31 01N635W 1643' FEL; 340' FSL					
													FORMATION:	C Chalk					
													API #:	05-123-52053					
													Field:	DJ Horizontal Niobrara					
													Spud:	02/07/24					
													Current Status:	Awaiting Completions					
													Well Type	Horizontal					
													Well Length	MRL					
													Casing and Tubular Data						
													Type	Size	Weight	Top	Bottom	Hole Size	Cement Type
													Surface	9 5/8	36.0 ppf	0'	2,506'	13.5"	15.8ppg Class G Neat
													Production	5 1/2	20.0 ppf	0'	16,256'	8.5"	13.2 Lead, 13.2 Tail
													Tubing	2 3/8	4.6 ppf	0'	n/a	n/a	
													Elevation Data						
													GL	5037	feet				
													KB	5056	feet				
													Difference	19	feet				
													*All depths from GL unless otherwise noted						
KOP:	7,924'												TPZ/ Heal Setback Depth (MD GL): 9,145'						
30 Deg:	7,924'												BPZ/ Toe Setback Depth (MD GL): 16,160'						
60 Deg:	8,640'												Production Casing Info: 5.5" 20# US Steel P110HP Freedom HTQ						
													Cement to Surface during 5.5" Job: 40 bbls						