



<div>FORM</div> <div>6</div> <div>Rev 11/20</div>	<div>State of Colorado</div> <div>Energy & Carbon Management Commission</div> <div>1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109</div>		<div><div></div></div>		<div>DE</div> <div>ET</div> <div>OE</div> <div>ES</div>
	<div>Replug By Other Operator</div> <div>Document Number: 403789553</div> <div>Date Received: 05/14/2024</div>				

WELL ABANDONMENT REPORT

This form is to be submitted as an Intent to Abandon whenever an abandonment is planned on a borehole. After the abandonment is complete, this form shall again be submitted as a Subsequent Report of the actual work completed. The approved intent shall be valid for six months after the approval date, after that period, a new intent will be required. Attachments required with the Intent to Abandon are wellbore diagrams of the current configuration and the proposed configuration with plugs set. A Subsequent Report of Abandonment shall indicate the actual work completed. Attachments required with a Subsequent Report are a wellbore diagram showing plugs that were set and casing remaining in the hole, the job summaries from all plugging contractors used, including wireline and cementing (third party verification) and any logs that may have been run during abandonment.

ECMC Operator Number: 10670		Contact Name: Mandie Flinn	
Name of Operator: BISON IV OPERATING LLC		Phone: (720) 261-4461	
Address: 518 17TH STREET SUITE 1800		Fax:	
City: DENVER	State: CO	Zip: 80202	Email: mflinn@bisonog.com
For "Intent" 24 hour notice required,		Name: Petrie, Erica	Tel: (303) 726-3822
ECMC contact:		Email: erica.petrie@state.co.us	

Type of Well Abandonment Report: ☒ Notice of Intent to Abandon ☐ Subsequent Report of Abandonment

API Number 05-123-14507-00		Well Number: 1	
Well Name: DEFORD			
Location: QtrQtr: NWSE	Section: 29	Township: 8N	Range: 59W Meridian: 6
County: WELD	Federal, Indian or State Lease Number:		
Field Name: WILDCAT	Field Number: 99999		

Only Complete the Following Background Information for Intent to Abandon

Latitude: 40.631325	Longitude: -103.999249
GPS Data: GPS Quality Value:	Type of GPS Quality Value: Date of Measurement:
Reason for Abandonment: <input type="checkbox"/> Dry <input type="checkbox"/> Production Sub-economic <input type="checkbox"/> Mechanical Problems	
<input checked="" type="checkbox"/> Other Offset Frac Reentry	
Casing to be pulled: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Estimated Depth:
Fish in Hole: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	If yes, explain details below
Wellbore has Uncemented Casing leaks: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	If yes, explain details below
Details:	

Current and Previously Abandoned Zones

Formation	Perf. Top	Perf. Btm	Abandoned Date	Method of Isolation	Plug Depth

Total: 0 zone(s)

Casing History

Casing Type	Size of Hole	Size of Casing	Grade	Wt/Ft	Csg/Liner Top	Setting Depth	Sacks Cmt	Cmt Btm	Cmt Top	Status
SURF	12+1/4	8+5/8	NA	24	0	210	130	210	0	VISU
OPEN HOLE	7+7/8				210	6880				

Date Run: 5/29/2024 Doc [#403789553] Well Name: DEFORD 1

Page 1 of 4

Plugging Procedure for Intent and Subsequent Report

CIBP #1: Depth _____ with _____ sacks cmt on top. CIBP #2: Depth _____ with _____ sacks cmt on top.
CIBP #3: Depth _____ with _____ sacks cmt on top. CIBP #4: Depth _____ with _____ sacks cmt on top.
CIBP #5: Depth _____ with _____ sacks cmt on top.

NOTE: Two(2) sacks cement required on all CIBPs.

Set 50 sks cmt from 6765 ft. to 6615 ft. Plug Type: OPEN HOLE Plug Tagged: ☐
Set 100 sks cmt from 6080 ft. to 5780 ft. Plug Type: OPEN HOLE Plug Tagged: ☐
Set 50 sks cmt from 1491 ft. to 1341 ft. Plug Type: OPEN HOLE Plug Tagged: ☒
Set _____ sks cmt from _____ ft. to _____ ft. Plug Type: _____ Plug Tagged: ☐
Set _____ sks cmt from _____ ft. to _____ ft. Plug Type: _____ Plug Tagged: ☐
Perforate and squeeze at _____ ft. with _____ sacks. Leave at least 100 ft. in casing _____ CICR Depth
Perforate and squeeze at _____ ft. with _____ sacks. Leave at least 100 ft. in casing _____ CICR Depth
Perforate and squeeze at _____ ft. with _____ sacks. Leave at least 100 ft. in casing _____ CICR Depth
(Cast Iron Cement Retainer Depth)

Set 145 sacks half in. half out surface casing from 450 ft. to 0 ft. Plug Tagged: ☒
Set _____ sacks at surface
Cut four feet below ground level, weld on plate Above Ground Dry-Hole Marker: ☐ Yes ☐ No
Set _____ sacks in rat hole Set _____ sacks in mouse hole

Additional Plugging Information for Subsequent Report Only

Casing Recovered: _____ ft. of _____ inch casing Number of Days from Setting Surface Plug to Capping or Sealing the Well: _____
Surface Plug Setting Date: _____ Cut and Cap Date: _____
*Wireline Contractor: _____ *Cementing Contractor: _____
Type of Cement and Additives Used: _____
Flowline/Pipeline has been abandoned per Rule 1105 ☐ Yes ☐ No

Technical Detail/Comments:

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: _____ Print Name: Mandie Flinn
Title: Operations Tech Date: 5/14/2024 Email: mflinn@bisonog.com

Based on the information provided herein, this Well Abandonment Report (Form 6) complies with ECMC Rules and applicable orders and is hereby approved.

ECMC Approved: Wolfe, Stephen Date: 5/29/2024

CONDITIONS OF APPROVAL, IF ANY LIST

Expiration Date: 11/28/2024

COA Type	Description
	<p>Plugging</p> <p>1) Provide electronic Form 42 Notice of MIRU 2 business days ahead of operations and electronic Form 42 Notice of Plugging Operations 48 hours prior to mobilizing for plugging operations.</p> <p>2) Plugs and squeezes will be placed as stated in the Plugging Procedure section of the approved NOIA unless revised by COA or prior approval from ECMC is obtained.</p> <p>3) The wellbore must be static prior to placing cement plugs which are to be a minimum of 100' in length for all but surface plugs. Mechanical isolation requires a 25' cement plug, minimum. For plugs not specified to be tagged, a tag is required if circulation is not maintained while pumping plug and displacing to depth. Wait on cement(WOC) a minimum of 4 hrs before tagging a plug. Tag at tops specified. Notify ECMC Area Engineer before adding cement to previous plug due to low cement top.</p> <p>4) Place a 50' plug (minimum) at the surface, both inside the inner most casing and in all annular spaces. Surface plugs shall be circulated to surface. Confirm cement to surface and complete isolation in all strings during cut and cap. After cut and prior to cap, verify isolation by either a 15 minute bubble test or 15 minute optical gas imaging recording. If there is indication of flow contact ECMC Engineering. Provide a statement on the 6 SRA which method was used and what was observed. Retain records of final isolation test for 5 years.</p> <p>5) With the Form 6 SRA operator must provide written documentation which positively affirms each COA has been addressed.</p> <p>6) Operator must wait a sufficient time on all plugs to achieve the intended design. If at any time during the plugging there is evidence of previously unreported pressure or fluid migration, contact ECMC Area Engineer before continuing operations.</p> <p>7) Plugging procedure has been modified as follows, See COA #3 for requirements to tag, Plug #1 - 6765-6615', 50 sx open hole plug, Plug #2 - 6080-5780', 100 sx open hole plug, Plug #3 - 1491-1341', 50 sx open hole plug, WOC and tag, Plug #4 - 450-0', 145 sx open hole plug, WOC and tag if not circulated to the surface, NOTE: change to depth, Plug #5 - 50' of cement at the surface in both the casing and the annulus per COA #4, if needed.</p>
	Submit "as drilled" GPS data on Subsequent Report of Abandonment. GPS data must meet the requirements of Rule 216.
2 COAs	

ATTACHMENT LIST

Att Doc Num	Name
403789553	FORM 6 INTENT SUBMITTED
403789567	WELLBORE DIAGRAM
403789568	WELLBORE DIAGRAM
403789569	PROPOSED PLUGGING PROCEDURE
403789571	SURFACE OWNER CONSENT
403789573	LOCATION PHOTO

Total Attach: 6 Files

General Comments

<u>User Group</u>	<u>Comment</u>	<u>Comment Date</u>
Engineer	Groundwater=Laramie-Fox Hills, Upper Pierre Deepest water well=1060(2mi, 23 records) Log=123-05497 2/7/55 GR=4897 L-FH base 410' UP 790-1441'	05/22/2024
OGLA	Location Assessment Specialist (LAS) review complete. Well is not in a HPH, not near surface waters or wetlands, and not near RBUs.	05/21/2024
Permit	No other forms in process. Reviewed attachments. Pass.	05/15/2024

Total: 3 comment(s)