

<div>FORM</div> <div>6</div> <div>Rev 11/20</div>	<div>State of Colorado</div> <div>Energy &amp; Carbon Management Commission</div> <div>1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109</div>		<div><div><div></div></div><div><div></div></div></div>		<div>DE</div> <div>ET</div> <div>OE</div> <div>ES</div>																																											
	<div>Document Number:</div> <div>403845153</div> <div>Date Received:</div> <div>07/03/2024</div>																																															
<div>WELL ABANDONMENT REPORT</div> <div><div><div>This form is to be submitted as an Intent to Abandon whenever an abandonment is planned on a borehole. After the abandonment is complete, this form shall again be submitted as a Subsequent Report of the actual work completed. The approved intent shall be valid for six months after the approval date, after that period, a new intent will be required. Attachments required with the Intent to Abandon are wellbore diagrams of the current configuration and the proposed configuration with plugs set. A Subsequent Report of Abandonment shall indicate the actual work completed. Attachments required with a Subsequent Report are a wellbore diagram showing plugs that were set and casing remaining in the hole, the job summaries from all plugging contractors used, including wireline and cementing (third party verification) and any logs that may have been run during abandonment.</div></div></div>																																																
<div><div><div>ECMC Operator Number: 28780</div><div>Contact Name: Deborah Abrams</div><div>Name of Operator: FAHEY OIL &amp; GAS</div><div>Phone: (303) 8942100</div><div>Address: 93 SOUTH COUNTY ROAD 159</div><div>Fax:</div><div>City: STRASBURG State: CO Zip: 80136</div><div>Email: deborah.abrams@state.co.us</div><div>For "Intent" 24 hour notice required, Name: Medina, Justin Tel: (720) 471-0006</div><div>ECMC contact: Email: justin.medina@state.co.us</div></div></div>																																																
<div>Type of Well Abandonment Report: <input checked="" type="checkbox"/> Notice of Intent to Abandon <input type="checkbox"/> Subsequent Report of Abandonment</div>																																																
<div><div><div>API Number 05-005-06445-00</div><div>Well Name: FRIEND &amp; MEYER</div><div>Well Number: 1 (OWP)</div><div>Location: QtrQtr: SESE Section: 2 Township: 4S Range: 63W Meridian: 6</div><div>County: ARAPAHOE Federal, Indian or State Lease Number:</div><div>Field Name: FAIRWAY Field Number: 22510</div></div></div>																																																
<div><div>Only Complete the Following Background Information for Intent to Abandon</div><div><div>Latitude: 39.725500 Longitude: -104.398620</div><div>GPS Data: GPS Quality Value: 2.9 Type of GPS Quality Value: PDOP Date of Measurement: 09/04/2010</div><div>Reason for Abandonment: <input type="checkbox"/> Dry <input type="checkbox"/> Production Sub-economic <input type="checkbox"/> Mechanical Problems</div><div><input checked="" type="checkbox"/> Other OWP</div><div>Casing to be pulled: <input type="checkbox"/> Yes <input type="checkbox"/> No Estimated Depth:</div><div>Fish in Hole: <input type="checkbox"/> Yes <input type="checkbox"/> No If yes, explain details below</div><div>Wellbore has Uncemented Casing leaks: <input type="checkbox"/> Yes <input type="checkbox"/> No If yes, explain details below</div><div>Details:</div></div></div>																																																
<div><div>Current and Previously Abandoned Zones</div><table><tr><th>Formation</th><th>Perf. Top</th><th>Perf. Btm</th><th>Abandoned Date</th><th>Method of Isolation</th><th>Plug Depth</th></tr><tr><td>J SAND</td><td>7622</td><td>7632</td><td></td><td></td><td></td></tr></table><div>Total: 1 zone(s)</div></div>					Formation	Perf. Top	Perf. Btm	Abandoned Date	Method of Isolation	Plug Depth	J SAND	7622	7632																																			
Formation	Perf. Top	Perf. Btm	Abandoned Date	Method of Isolation	Plug Depth																																											
J SAND	7622	7632																																														
<div><div>Casing History</div><table><tr><th>Casing Type</th><th>Size of Hole</th><th>Size of Casing</th><th>Grade</th><th>Wt/Ft</th><th>Csg/Liner Top</th><th>Setting Depth</th><th>Sacks Cmt</th><th>Cmt Btm</th><th>Cmt Top</th><th>Status</th></tr><tr><td>SURF</td><td>12+1/4</td><td>8+5/8</td><td>UNK</td><td>24</td><td>0</td><td>220</td><td>200</td><td>220</td><td>0</td><td>VISU</td></tr><tr><td>1ST</td><td>7+7/8</td><td>4+1/2</td><td>UNK</td><td>11.6</td><td>0</td><td>7748</td><td>175</td><td>7748</td><td>6980</td><td>CALC</td></tr><tr><td></td><td>7+7/8</td><td>4+1/2</td><td>UNK</td><td>Stage Tool</td><td></td><td>1477</td><td>0</td><td>1477</td><td>1476</td><td></td></tr></table></div>					Casing Type	Size of Hole	Size of Casing	Grade	Wt/Ft	Csg/Liner Top	Setting Depth	Sacks Cmt	Cmt Btm	Cmt Top	Status	SURF	12+1/4	8+5/8	UNK	24	0	220	200	220	0	VISU	1ST	7+7/8	4+1/2	UNK	11.6	0	7748	175	7748	6980	CALC		7+7/8	4+1/2	UNK	Stage Tool		1477	0	1477	1476	
Casing Type	Size of Hole	Size of Casing	Grade	Wt/Ft	Csg/Liner Top	Setting Depth	Sacks Cmt	Cmt Btm	Cmt Top	Status																																						
SURF	12+1/4	8+5/8	UNK	24	0	220	200	220	0	VISU																																						
1ST	7+7/8	4+1/2	UNK	11.6	0	7748	175	7748	6980	CALC																																						
	7+7/8	4+1/2	UNK	Stage Tool		1477	0	1477	1476																																							
<div><div>Date Run: 7/8/2024 Doc [#403845153] Well Name: FRIEND &amp; MEYER 1 (OWP)</div><div>Page 1 of 4</div></div>																																																

## Plugging Procedure for Intent and Subsequent Report

CIBP #1: Depth 7547 with 2 sacks cmt on top. CIBP #2: Depth \_\_\_\_\_ with \_\_\_\_\_ sacks cmt on top.  
CIBP #3: Depth \_\_\_\_\_ with \_\_\_\_\_ sacks cmt on top. CIBP #4: Depth \_\_\_\_\_ with \_\_\_\_\_ sacks cmt on top.  
CIBP #5: Depth \_\_\_\_\_ with \_\_\_\_\_ sacks cmt on top.

NOTE: Two(2) sacks cement required on all CIBPs.

Set 100 sks cmt from 810 ft. to 395 ft. Plug Type: ANNULUS Plug Tagged: ☐  
Set 35 sks cmt from 810 ft. to 395 ft. Plug Type: CASING Plug Tagged: ☒  
Set \_\_\_\_\_ sks cmt from \_\_\_\_\_ ft. to \_\_\_\_\_ ft. Plug Type: \_\_\_\_\_ Plug Tagged: ☐  
Set \_\_\_\_\_ sks cmt from \_\_\_\_\_ ft. to \_\_\_\_\_ ft. Plug Type: \_\_\_\_\_ Plug Tagged: ☐  
Set \_\_\_\_\_ sks cmt from \_\_\_\_\_ ft. to \_\_\_\_\_ ft. Plug Type: \_\_\_\_\_ Plug Tagged: ☐

Perforate and squeeze at 6738 ft. with 40 sacks. Leave at least 100 ft. in casing 6648 CICR Depth  
Perforate and squeeze at 2590 ft. with 40 sacks. Leave at least 100 ft. in casing 2500 CICR Depth  
Perforate and squeeze at 1495 ft. with 70 sacks. Leave at least 100 ft. in casing 1352 CICR Depth  
(Cast Iron Cement Retainer Depth)

Set \_\_\_\_\_ sacks half in. half out surface casing from \_\_\_\_\_ ft. to \_\_\_\_\_ ft. Plug Tagged: ☐

Set 90 sacks at surface

Cut four feet below ground level, weld on plate Above Ground Dry-Hole Marker: ☐ Yes ☐ No

Set \_\_\_\_\_ sacks in rat hole Set \_\_\_\_\_ sacks in mouse hole

### Additional Plugging Information for Subsequent Report Only

Casing Recovered: \_\_\_\_\_ ft. of \_\_\_\_\_ inch casing Number of Days from Setting Surface Plug  
Surface Plug Setting Date: \_\_\_\_\_ Cut and Cap Date: \_\_\_\_\_ to Capping or Sealing the Well: \_\_\_\_\_

\*Wireline Contractor: \_\_\_\_\_ \*Cementing Contractor: \_\_\_\_\_

Type of Cement and Additives Used: \_\_\_\_\_

Flowline/Pipeline has been abandoned per Rule 1105 ☐ Yes ☐ No

Technical Detail/Comments:

Perforate at 270' and pump 90 sacks

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: \_\_\_\_\_ Print Name: Deborah Abrams

Title: OWP Date: 7/3/2024 Email: deborah.abrams@state.co.us

Based on the information provided herein, this Well Abandonment Report (Form 6) complies with ECMC Rules and applicable orders and is hereby approved.

ECMC Approved: Jacobson, Eric Date: 7/8/2024

### CONDITIONS OF APPROVAL, IF ANY LIST

Expiration Date: 1/7/2025

COA Type	Description
	Operator shall implement measures to control venting, to protect health and safety, and to ensure that vapors and odors from well plugging operations do not constitute a nuisance or hazard to public welfare.
	CBL to be run prior to plugging to verify stage tool setting depth and existing coverage - submit to ECMC for verification of plugging orders prior to continuing plugging operations.
	<p>Prior to starting plugging operations a bradenhead test shall be performed if there has not been a reported bradenhead test within the 60 days immediately preceding the start of plugging operations.</p> <p>1) If, before opening the bradenhead valve, the beginning pressure is greater than 25 psi, sampling is required.</p> <p>2) If pressure remains at the conclusion of the test, or if any liquids were present during the test, sampling is required.</p> <p>The Form 17 shall be submitted within 10 days of the test. Sampling shall comply with Operator Guidance - Bradenhead Testing and Reporting Instructions. If samples are collected, copies of all final laboratory analytical results shall be provided to the ECMC within three (3) months of collecting the samples.</p> <p>If there is a need for sampling, contact ECMC engineering for verification of plugging procedure.</p>
	<p>Consistent with Rule 911.a, a Form 27 must be approved prior to cut and cap, conducting flowline abandonment, or removing production equipment. Allow 30 days for Director review of the Form 27; include the Form 27 document number on the Form 44 for offsite flowline abandonment (if applicable) and on the Form 6 Subsequent.</p> <p>Properly abandon flowlines per Rule 1105. If flowlines will be abandoned in place, include with the Form 27: pressure test results conducted in the prior 12 months as well as identification of any document numbers for a ECMC Spill/Release Report, Form 19, associated with the abandoned line.</p>
	<p>1) Provide electronic Form 42 Notice of MIRU 2 business days ahead of operations and electronic Form 42 Notice of Plugging Operations 48 hours prior to mobilizing for plugging operations. These are two separate notifications, required by Rules 405.e and 405.i.</p> <p>2) Prior to placing cement above the base of the Upper Pierre (2540') : verify that all fluid (liquid and gas) migration has been eliminated. If evidence of fluid migration or pressure remains, contact ECMC Engineer for an update to plugging orders.</p> <p>3) Pump surface casing shoe at 270' plug only after isolation has been verified. If surface casing cement is not circulated to surface, shut-in, WOC 4 hours then tag plug – must be at 170' or shallower and provide a minimum of 10 sx plug at the surface.</p> <p>4) Leave at least 100' of cement in the wellbore for each plug without mechanical isolation.</p> <p>5) After cut and prior to cap, verify isolation by either a 15 minute bubble test or 15 minute optical gas imaging recording. If there is indication of flow contact ECMC Engineering. Provide a statement on the 6SRA which method was used and what was observed. Retain records of final isolation test for 5 years.</p> <p>6) With the Form 6 SRA operator must provide written documentation which positively affirms each COA listed above has been addressed.</p>
5 COAs	

#### ATTACHMENT LIST

Att Doc Num	Name
403845153	FORM 6 INTENT SUBMITTED
403845166	WELLBORE DIAGRAM

Total Attach: 2 Files

### General Comments

<u>User Group</u>	<u>Comment</u>	<u>Comment Date</u>
OGLA	Location Assessment Specialist (LAS) review complete. Well is not near surface waters or wetlands, and not near RBUs.	07/08/2024
OGLA	Well is in a CPW mapped Pronghorn Winter Concentration Area High Priority Habitat. Although plugging and abandonment operations with heavy equipment will be allowed, the operator is strongly encouraged to avoid them from January 1 through April 30.	07/08/2024
Engineer	Well file verification not completed prior to approval of NOIA.	07/05/2024
Engineer	Deepest Water Well within 1 Mile – 600' SB5 Base of Fox Hills - 1445' SB5 Base of Lower Arapahoe - 949' SB5 Base of Upper Arapahoe - 685' SB5 Base of Denver - 424'  Denver / 5120 / 5383 / 134.8 / 424 / 161 / 36.67NNT Upper Arapahoe / 4859 / 5099 / 117.9 / 685 / 445 / 32.07NNT Lower Arapahoe / 4595 / 4784 / 77.5 / 949 / 760 / 21.08NT Laramie-Fox Hills / 4099 / 4285 / 121.8 / 1445 / 1259 / 29.23NT	07/05/2024
Permit	Confirmed as-drilled well location. Production reporting delinquent. Missing 9/2006, 12/2019, 6/2020-current. No other forms in process. Confirmed productive interval docnum: 378085. Reviewed WBDs. Pass.	07/03/2024

Total: 5 comment(s)