



00632115

STATE OF COLORADO  
OIL AND GAS CONSERVATION COMMISSION  
DEPARTMENT OF NATURAL RESOURCES

File in duplicate for Patented and Federal lands.  
File in triplicate for State lands.

RECEIVED

OCT 23 1984

5. LEASE DESIGNATION & SERIAL NO.  
COLD. OIL & GAS CONS. COMM.

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals.)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

N/A

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Mayberry

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

Greenwood

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 10-T34S-R41W

14. PERMIT NO.

83798

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3618 KB, 3610 GR

12. COUNTY

Baca

13. STATE

Colorado

16.

## Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐  
☐  
☐  
☐  
☐

PULL OR ALTER CASING

☐  
☐  
☒  
☐  
☐

FRACTURE TREAT

MULTIPLE COMPLETION

SHOOT OR ACIDIZE

ABANDON

REPAIR WELL

CHANGE PLANS

(Other)

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐  
☐  
☐  
☐  
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

☐  
☐  
☒  
☐  
☐

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

18. Date of work 10-11-83 - 10-14-83

\* Must be accompanied by a cement verification report.

Plugging and Abandonment Procedure  
Mayberry No. 3  
Section 10-T34S-R41W  
Baca County, Colorado

Detailed below is the approved plugging and abandonment procedure for the subject well. All depths are relative to the KB elevation of 3650' per the DIL - Laterolog run by Gearhart on August 8, 1983.

1. Set CIBP at 3000' and cap with 2 sacks cement.
2. Located free point of 7" casing at 2200'. Cut and pull casing for salvage.
3. Spotted 50 sacks cement from 1450' to 1350' (50' in and 50' out of surface casing shoe.)
4. Spotted 13 sacks cement from 3.5' to 5'.
5. Cut off surface 5' below ground level. Weld on steel cap with proper ID and fill hole with earth.

(See Attached Diagram)

19. I hereby certify that the foregoing is true and correct

SIGNED

T. A. Powers

TITLE

Admn. Supvr.

DATE

10-17-84

(This space for Federal or State office use)

APPROVED BY

William R. Smith

TITLE

DIRECTOR

DATE

NOV 9 1984

CONDITIONS OF APPROVAL, IF ANY:

O &amp; G Cons. Comm.



Post-It™ brand fax transmittal memo 7671 # of pages ▶

# of pages ▶

To Tommy Thompson

**From** 105CC

Co. 0xv

Co.

Dept.

Phone #

Fax # 405 749 2448

Fax #