



P&A Wellbore For State

Well Name: BOOTH C25-19

Original Hole [Land]		Well Header										
MD (ftK B)	Vertical schematic (actual)	Surface UWI 0512327162		Business Unit Rockies		Gov Auth Dist		Prod Tree Loc Land				
		Orig. KB to Gnd (ft) 14.00		Original Spud Date 12/21/2008		Abandon Date		Well Sub-Status TA		High...		
										N		
		Comment										
Surface Location (Congressional)												
Qtr 3 NE		Qtr 4 NW		Section 25	Twnshp 4	Twnsh... N	Range 64	Rng E/... W	Latitude (°) 40.28731165 4		Longitude (°) -104.503819341	
Wellbore Sections												
Section Des			Hole Size (in)			Top Depth (ftKB)			Btm Depth (ftKB)			
SURFACE			12 1/4			14.0			514.0			
PRODUCTION			7 7/8			514.0			6,978.0			
Casing Strings												
Csg Des			Run Date		OD (in)	Wt/Len (lb/ft)	Grade	Top Depth (MD) (ftKB)		Set Depth (MD) (ftKB)		
Surface			12/22/2008		8 5/8	24.00	J-55	14		502.3		
Production Casing			12/25/2008		4 1/2	11.60	M-80	14.2		6953		
Cement												
Des						Start Date		Top (ftKB)		Btm (ftKB)		
SURFACE CASING CEMENT						12/22/2008		14.0		502.3		
PRODUCTION CASING CEMENT						12/25/2008		1,438.0		6,953.0		
Zone Statuses												
Zone Name		Status Date	Status	Fluid Type	Job				Prod Method			
NIOBRARA		2/6/2009	PR		DRILLING/COMPLETION - ORIGINAL, 12/21/200...							
CODELL		2/6/2009	PR		DRILLING/COMPLETION - ORIGINAL, 12/21/200...							
Perforation Data												
Linked Zone			Explosive Type	Entered Shot Total	Top (ftKB)		Btm (ftKB)		Date			
NIOBRARA, Original Hole			A	32	6,556.0		6,572.0		2/5/2009			
NIOBRARA, Original Hole			B	32	6,616.0		6,632.0		2/5/2009			
CODELL, Original Hole			01	48	6,809.0		6,821.0		1/7/2009			
Stim/Frac Stage												
Zone				Start Date		Top (ftKB)		Btm (ftKB)				
NIOBRARA, Original Hole				2/5/2009		6,556.0		6,632.0				
CODELL, Original Hole				2/5/2009		6,809.0		6,821.0				
Other In Hole												
Run Date		Des			Make		OD (in)	Top (ftKB)	Btm (ftKB)			
3/8/2023		Cast Iron Bridge Plug w/ 2 SX Cement					3.9	6,472.0	6,498.0			
Logs												
Date		Type						Depth Top (MD) (ftKB)	Btm (ftKB)			
12/25/2008		Caliper/Comp. Density/Neutron/GR/SP/ML						2,490	6,965.0			
12/25/2008		DIL/GR/SP/Caliper						502	6,965.0			
1/7/2009		CBL/CCL/GR						1,166	6,880.0			
Wellbore Plug Back Total Depths												
Date		Type		Com						PBTD (ftKB)		
1/7/2009		FILL		TAG WITH WIRELINE AND LOGGING TOOLS.						6,891		
5/5/2009		PLUG REMNANTS		96.14' OF RAT HOLE						6,917		

Surface Casing Cement,
Casing, 12/22/2008 06:30;
14-502.3; 2008-12-22 06:30

Production Casing Cement,
Casing, 12/25/2008 11:30;
1438-6953; 2008-12-25
11:30; SPORADIC BOND
1600'-3002' & 4206'-5936'

3.9 in, Cast Iron Bridge Plug
w/ 2 SX Cement, 3/8/2023
08:30; 6472-6498; 2023-03-
08 08:30

6,556.0-6,572.0ftKB on
2/5/2009 12:03 (Perforated);
6556-6572; 2009-02-05
12:03

6,616.0-6,632.0ftKB on
2/5/2009 12:00 (Perforated);
6616-6632; 2009-02-05
12:00

6,809.0-6,821.0ftKB on
1/7/2009 10:30 (Perforated);
6809-6821; 2009-01-07
10:30

Production Casing Cement,
Casing, 12/25/2008 11:30
(plug); 6937-6953; 2008-12-
25 11:30; SPORADIC
BOND 1600'-3002' & 4206'-
5936'