



Wellbore Schematic Input Report

Well Name: KODAK SOUTH 15C

Original Hole [Land]			Well Header						
MD (ftOTH)	Incl (°)	Vertical schematic (actual)	Surface UWI 0512352097		Asset Team 10006302		Production Tree Location Land		
			Original RKB Elevation (ft) 4,771.00		Original KB to Ground (ft) 28.00		Original Spud Date 7/17/2023		Abandon Date
28.5	0.1	Wellhead, 9 5/8in; 29.5; 28 TVD; 1.51; 28-29.5 TVD; 28-29.5	Range 67W			Well Sub-Status PR			High Press... N
35.4	0.1	Casing joints, 9 5/8in; 1665.2; 35.5 TVD; 1,629.64; 35.5-1640.5 TVD; 35.5-1665.2	Directions To Well Litho Plate Dr.-Eastman Park Dr. West 1/10, South 1/10, East 1/10, South 7/10, West 1/10, South into.					Latitude (°) 40° 27' 9.043" N	Longitude (°) 104° 51' 50.483" W
72.8	0.2	Casing Joints, 5 1/2in; 3171.4; 28 TVD; 3,143.42; 28-3111.9 TVD; 28-3171.4	Comment						
1665.0	12.6	Casing joints, 9 5/8in; 1707.5; 1641.8 TVD; 40.96; 1641.8-1681.8 TVD; 1666.5-1707.5	Congressional Location						
1690.3	12.6		Quarter 3 SE	Quarter 4 SW	Section 26	Township 6	Twnshp N/S Dir N	Range 67	Range E/W Dir W
1707.3	12.5		Rig Operator						
2990.5	11.3		Rig/Unit Supervisor LOUIS GARCIA						
3171.3	12.7		Daily Cost Summary						
4004.3	12.3		Sum of Field Est (Cost) 0						
4725.4	3.8	Casing Joints, 5 1/2in; 6491; 3126.3 TVD; 3,304.76; 3126.3-6402.6 TVD; 3186.2-6491	Wellbore Plug Back Total Depths						
5316.6	0.4		Date 7/20/2023	PBTD (ftOTH)	Method		Com		
5908.1	0.4		Wellbore Sections						
6464.9	1.9		Section Des	Hole Size (in)		Top Depth (ftOTH)		Btm Depth (ftOTH)	
6491.1	3.2	Casing Joints, 5 1/2in; 7650.7; 6412.3 TVD; 1,149.92; 6412.3-7105.3 TVD; 6500.8-7650.7	Surface	13 1/2					
7084.6	45.2		Surface	13 1/2					
7118.1	49.2		Production	8 1/2					
7152.9	53.5		Zone Statuses						
7161.7	54.6		Zone Name		Status Date			Status	
7169.0	55.5								
7650.6	86.9		Casing Strings						
7795.9	87.8		Surface, Actual, <DepthBtm>ftOTH						
8227.0	91.3		Casing Description Surface	Run Date 6/5/2023	OD (in) 9 5/8	Wt/Len (l... 36.00	Grade J-55	Top Depth...	Set Depth...
8653.9	90.9	Casing Joints, 5 1/2in; 11948.6; 7106.5 TVD; 4,276.30; 7106.5-7095.8 TVD; 7672.3-11948.6	Production, Actual, <DepthBtm>ftOTH						
9076.1	89.8		Casing Description Production	Run Date 7/20/2023	OD (in) 5 1/2	Wt/Len (l... 20.00	Grade P-110	Top Depth...	Set Depth...
9460.0	89.5		Cement						
9839.9	90.4		Des		Start Date		Top (ftOTH)	Btm (ftOTH)	
10219.2	90.0		Surface		6/5/2023				
10946.9	90.9		Production Casing Cement		7/20/2023				
11298.9	91.8		Proposed Cement						
11649.9	91.5		Des					Top (ftOTH)	Btm (ftOTH)
11959.0	91.2								
12002.0	90.7		Tubing Strings						
12354.0	91.0		Tubing Description Tubing - Production	Run Date 6/11/2024	String... 2 3/8	ID (in) 2.000	Wt (lb/ft) 4.70	Grade L-80	Len (ft) 7,141.32
12705.1	89.6		Tubing Components						
13057.1	90.0		Item Des	OD (in)	Wt (lb/ft)	Grade	Jts	Len (ft)	Btm (ftOTH)
13409.1	90.1	Casing Joints, 5 1/2in; 15750.3; 7095.4 TVD; 3,779.54; 7095.4-7098.8 TVD; 11970.8-15750.3	Tubing Hanger	5	4.70	N-80	1	0.50	
13759.8	90.1		Tubing	2 3/8	4.70	L-80	1	32.28	
14111.9	90.2		Tubing Pup Joint	2 3/8	4.70	L-80	2	12.11	
14463.9	89.2		Tubing	2 3/8	4.70	L-80	50	1,617.40	
14815.0	89.4		Gas Lift Mandrel	4.283	4.70	N-80	1	4.10	
15167.0	88.3		Tubing	2 3/8	4.70	L-80	40	1,296.00	
15519.0	90.7		Gas Lift Mandrel	4.283	4.70	N-80	1	4.10	
15772.0	90.5		Tubing	2 3/8	4.70	L-80	31	1,009.67	
15870.1	89.2	Casing Joints, 5 1/2in; 16213.6; 7098.7 TVD; 441.58; 7098.7-7099 TVD; 15772-16213.6	Gas Lift Mandrel	4.283	4.70	N-80	1	4.10	
16213.6	90.7	Wet Shoe Sub, 5 1/2in; 16224.5; 7098.9 TVD; 5.85; 7098.9-7098.8 TVD; 16218.7-16224.5	Tubing	2 3/8	4.70	L-80	22	717.20	
16216.9	90.7		Gas Lift Mandrel	4.283	4.70	N-80	1	4.10	
16224.4	90.7	Float Collar, 5 1/2in; 16236.3; 7098.7 TVD; 1.83; 7098.7-7098.7 TVD; 16234.5-16236.3	Tubing	2 3/8	4.70	L-80	18	586.98	
16234.9	90.7		Gas Lift Mandrel	4.283	4.70	N-80	1	4.10	
16246.4	90.7	Float Shoe, 5 1/2in; 16248; 7098.6 TVD; 1.67; 7098.6-7098.5 TVD; 16246.3-16248	Tubing	2 3/8	4.70	L-80	18	587.52	
			Gas Lift Mandrel	4.283	4.70	N-80	1	4.10	
			Tubing	2 3/8	4.70	L-80	17	552.67	



Wellbore Schematic Input Report

Well Name: KODAK SOUTH 15C

Original Hole [Land]			Tubing Components								
MD (ftOTH)	Incl (°)	Vertical schematic (actual)	Item Des	OD (in)	Wt (lb/ft)	Grade	Jts	Len (ft)	Btm (ftOTH)	Btm (TVD) (ftOTH)	
			Gas Lift Mandrel	4.283	4.70	N-80	1	4.10			
			Tubing	2 3/8	4.70	L-80	19	615.60			
			X Nipple	3	4.70	N-80	1	0.93			
				1/16							
			Tubing	2 3/8	4.70	L-80	1	32.71			
			Gas Lift Mandrel	4.283	4.70	N-80	1	4.10			
			Tubing	2 3/8	4.70	L-80	1	30.61			
			On-Off Tool	4 1/2	4.70	N-80	1	1.53			
			Packer	4 1/2	4.70	N-80	1	7.19			
			Tubing Pup Joint	2 3/8	4.70	L-80	1	6.20			
			XN Nipple	3	4.70	N-80	1	1.01			
				1/16							
			Tubing Plug	3	4.70	N-80	1	0.41			
				1/16							
Other In Hole											
Run Date		Des			Make		OD (in)	Top (ftOTH)	Btm (ftOTH)		
Proposed Other In Hole											
Des			Make			OD (in)	Top (ftOTH)	Btm (ftOTH)			
Logs											
Date		Type					Depth Top (MD) (ftOTH)		Btm (ftOTH)		
Perforation Data											
Linked Zone				Sum of Entered Shot Total		Top (ftOTH)		Btm (ftOTH)		Date	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5/22/2024	
Codell, Original Hole				4						5	



Wellbore Schematic Input Report

Well Name: KODAK SOUTH 15C

Original Hole [Land]			Perforation Data				
MD (fROTH)	Incl (°)	Vertical schematic (actual)	Linked Zone	Sum of Entered Shot Total	Top (fROTH)	Btm (fROTH)	Date
28.5	0.1	Wellhead, 9 5/8in; 29.5; 28 TVD; 1.51; 28-29.5 TVD; 28-29.5	Codell, Original Hole	4			5/21/2024
35.4	0.1	Casing joints, 9 5/8in; 1665.2; 35.5 TVD; 1,629.64; 35.5-1640.5 TVD; 35.5-1665.2	Codell, Original Hole	4			5/21/2024
72.8	0.2	Casing Joints, 5 1/2in; 3171.4; 28 TVD; 3,143.42; 28-3111.9 TVD; 28-3171.4	Codell, Original Hole	4			5/21/2024
1,665.0	12.6	Casing joints, 9 5/8in; 1707.5; 1641.8 TVD; 40.96; 1641.8-1681.8 TVD; 1666.5-1707.5	Codell, Original Hole	4			5/21/2024
1,690.3	12.6		Codell, Original Hole	4			5/21/2024
1,707.3	12.5		Codell, Original Hole	4			5/21/2024
2,990.5	11.3		Codell, Original Hole	4			5/21/2024
3,171.3	12.7		Codell, Original Hole	4			5/21/2024
4,004.3	12.3		Codell, Original Hole	4			5/21/2024
4,725.4	3.8	Casing Joints, 5 1/2in; 6491; 3126.3 TVD; 3,304.76; 3126.3-6402.6 TVD; 3186.2-6491	Codell, Original Hole	4			5/21/2024
5,316.6	0.4		Codell, Original Hole	4			5/21/2024
5,908.1	0.4		Codell, Original Hole	4			5/21/2024
6,464.9	1.9		Codell, Original Hole	4			5/21/2024
6,491.1	3.2	Casing Joints, 5 1/2in; 7650.7; 6412.3 TVD; 1,149.92; 6412.3-7105.3 TVD; 6500.8-7650.7	Codell, Original Hole	4			5/20/2024
7,084.6	45.2		Codell, Original Hole	4			5/20/2024
7,118.1	49.2		Codell, Original Hole	4			5/20/2024
7,152.9	53.5		Codell, Original Hole	4			5/20/2024
7,161.7	54.6		Codell, Original Hole	4			5/20/2024
7,169.0	55.5		Codell, Original Hole	4			5/20/2024
7,650.6	86.9		Codell, Original Hole	4			5/20/2024
7,795.9	87.8		Codell, Original Hole	4			5/20/2024
8,227.0	91.3		Codell, Original Hole	4			5/20/2024
8,653.9	90.9		Codell, Original Hole	4			5/20/2024
9,076.1	89.8		Codell, Original Hole	4			5/20/2024
9,460.0	89.5	Casing Joints, 5 1/2in; 11948.6; 7106.5 TVD; 4,276.30; 7106.5-7095.8 TVD; 7672.3-11948.6	Codell, Original Hole	4			5/20/2024
9,839.9	90.4		Codell, Original Hole	4			5/20/2024
10,219.2	90.0		Codell, Original Hole	4			5/20/2024
10,946.9	90.9		Codell, Original Hole	4			5/20/2024
11,298.9	91.8		Codell, Original Hole	4			5/20/2024
11,649.9	91.5		Codell, Original Hole	4			5/20/2024
11,959.0	91.2		Codell, Original Hole	4			5/20/2024
12,002.0	90.7		Codell, Original Hole	4			5/20/2024
12,354.0	91.0		Codell, Original Hole	4			5/20/2024
12,705.1	89.6		Codell, Original Hole	4			5/20/2024
13,057.1	90.0		Codell, Original Hole	4			5/20/2024
13,409.1	90.1		Codell, Original Hole	4			5/20/2024
13,759.8	90.1	Casing Joints, 5 1/2in; 15750.3; 7095.4 TVD; 3,779.54; 7095.4-7098.8 TVD; 11970.8-15750.3	Codell, Original Hole	4			5/20/2024
14,111.9	90.2		Codell, Original Hole	4			5/20/2024
14,463.9	89.2		Codell, Original Hole	4			5/20/2024
14,815.0	89.4		Codell, Original Hole	4			5/20/2024
15,167.0	88.3		Codell, Original Hole	4			5/20/2024
15,519.0	90.7		Codell, Original Hole	4			5/20/2024
15,772.0	90.5		Codell, Original Hole	4			5/20/2024
15,870.1	89.2	Casing Joints, 5 1/2in; 16213.6; 7098.7 TVD; 441.58; 7098.7-7099 TVD; 15772-16213.6	Codell, Original Hole	4			5/20/2024
16,213.6	90.7	Wet Shoe Sub, 5 1/2in; 16224.5; 7098.9 TVD; 5.85; 7098.9-7098.8 TVD; 16218.7-16224.5	Codell, Original Hole	4			5/20/2024
16,216.9	90.7		Codell, Original Hole	4			5/20/2024
16,224.4	90.7	Float Collar, 5 1/2in; 16236.3; 7098.7 TVD; 1.83; 7098.7-7098.7 TVD; 16234.5-16236.3	Codell, Original Hole	4			5/20/2024
16,234.9	90.7		Codell, Original Hole	4			5/18/2024
16,246.4	90.7	Float Shoe, 5 1/2in; 16248; 7098.6 TVD; 1.67; 7098.6-7098.5 TVD; 16246.3-16248	Codell, Original Hole	4			5/18/2024
			Codell, Original Hole	4			5/18/2024



Wellbore Schematic Input Report

Well Name: KODAK SOUTH 15C

Original Hole [Land]			Perforation Data				
MD (fROTH)	Incl (°)	Vertical schematic (actual)	Linked Zone	Sum of Entered Shot Total	Top (fROTH)	Btm (fROTH)	Date
28.5	0.1	Wellhead, 9 5/8in; 29.5; 28 TVD; 1.51; 28-29.5 TVD; 28-29.5	Codell, Original Hole	4			5/18/2024
35.4	0.1	Casing joints, 9 5/8in; 1665.2; 35.5 TVD; 1,629.64; 35.5-1640.5	Codell, Original Hole	4			5/18/2024
72.8	0.2	TVD; 35.5-1665.2	Codell, Original Hole	4			5/18/2024
1,665.0	12.6	Casing Joints, 5 1/2in; 3171.4; 28 TVD; 3,143.42; 28-3111.9 TVD; 28-3171.4	Codell, Original Hole	4			5/18/2024
1,690.3	12.6	Casing joints, 9 5/8in; 1707.5; 1641.8 TVD; 40.96; 1641.8-1681.8 TVD; 1666.5-1707.5	Codell, Original Hole	4			5/18/2024
1,707.3	12.5		Codell, Original Hole	4			5/18/2024
2,990.5	11.3		Codell, Original Hole	4			5/18/2024
3,171.3	12.7		Codell, Original Hole	4			5/18/2024
4,004.3	12.3		Codell, Original Hole	4			5/18/2024
4,725.4	3.8	Casing Joints, 5 1/2in; 6491; 3126.3 TVD; 3,304.76; 3126.3-6402.6 TVD; 3186.2-6491	Codell, Original Hole	4			5/18/2024
5,316.6	0.4		Codell, Original Hole	4			5/19/2024
5,908.1	0.4		Codell, Original Hole	4			5/19/2024
6,464.9	1.9		Codell, Original Hole	4			5/19/2024
6,491.1	3.2	Casing Joints, 5 1/2in; 7650.7; 6412.3 TVD; 1,149.92; 6412.3-7105.3 TVD; 6500.8-7650.7	Codell, Original Hole	4			5/19/2024
7,084.6	45.2		Codell, Original Hole	4			5/19/2024
7,118.1	49.2		Codell, Original Hole	4			5/19/2024
7,152.9	53.5		Codell, Original Hole	4			5/19/2024
7,161.7	54.6		Codell, Original Hole	4			5/18/2024
7,169.0	55.5		Codell, Original Hole	4			5/18/2024
7,650.6	86.9		Codell, Original Hole	4			5/18/2024
7,795.9	87.8		Codell, Original Hole	4			5/18/2024
8,227.0	91.3		Codell, Original Hole	4			5/18/2024
8,653.9	90.9		Codell, Original Hole	4			5/18/2024
9,076.1	89.8		Codell, Original Hole	4			5/18/2024
9,460.0	89.5	Casing Joints, 5 1/2in; 11948.6; 7106.5 TVD; 4,276.30; 7106.5-7095.8 TVD; 7672.3-11948.6	Codell, Original Hole	4			5/18/2024
9,839.9	90.4		Codell, Original Hole	4			5/18/2024
10,219.2	90.0		Codell, Original Hole	4			5/18/2024
10,946.9	90.9		Codell, Original Hole	4			5/18/2024
11,298.9	91.8		Codell, Original Hole	4			5/18/2024
11,649.9	91.5		Codell, Original Hole	4			5/18/2024
11,959.0	91.2		Codell, Original Hole	4			5/18/2024
12,002.0	90.7		Codell, Original Hole	4			5/18/2024
12,354.0	91.0		Codell, Original Hole	4			5/18/2024
12,705.1	89.6		Codell, Original Hole	4			5/18/2024
13,057.1	90.0		Codell, Original Hole	4			5/18/2024
13,409.1	90.1		Codell, Original Hole	4			5/18/2024
13,759.8	90.1	Casing Joints, 5 1/2in; 15750.3; 7095.4 TVD; 3,779.54; 7095.4-7098.8 TVD; 11970.8-15750.3	Codell, Original Hole	4			5/18/2024
14,111.9	90.2		Codell, Original Hole	4			5/18/2024
14,463.9	89.2		Codell, Original Hole	4			5/18/2024
14,815.0	89.4		Codell, Original Hole	4			5/18/2024
15,167.0	88.3		Codell, Original Hole	4			5/18/2024
15,519.0	90.7		Codell, Original Hole	4			5/18/2024
15,772.0	90.5		Codell, Original Hole	4			5/18/2024
15,870.1	89.2	Casing Joints, 5 1/2in; 16213.6; 7098.7 TVD; 441.58; 7098.7-7099 TVD; 15772-16213.6	Codell, Original Hole	4			5/18/2024
16,213.6	90.7	Wet Shoe Sub, 5 1/2in; 16224.5; 7098.9 TVD; 5.85; 7098.9-7098.8 TVD; 16218.7-16224.5	Codell, Original Hole	4			5/18/2024
16,216.9	90.7		Codell, Original Hole	4			5/18/2024
16,224.4	90.7	Float Collar, 5 1/2in; 16236.3; 7098.7 TVD; 1.83; 7098.7-7098.7 TVD; 16234.5-16236.3	Codell, Original Hole	4			5/18/2024
16,234.9	90.7		Codell, Original Hole	4			5/18/2024
16,246.4	90.7	Float Shoe, 5 1/2in; 16248; 7098.6 TVD; 1.67; 7098.6-7098.5 TVD; 16246.3-16248	Codell, Original Hole	4			5/18/2024
			Codell, Original Hole	4			5/18/2024



Wellbore Schematic Input Report

Well Name: KODAK SOUTH 15C

Original Hole [Land]			Perforation Data						
MD (ftOTH)	Incl (°)	Vertical schematic (actual)	Linked Zone	Sum of Entered Shot Total	Top (ftOTH)	Btm (ftOTH)	Date		
			Codell, Original Hole	4			5/18/2024		
28.5	0.1	Wellhead, 9 5/8in; 29.5; 28 TVD; 1.51; 28-29.5 TVD; 28-29.5	Codell, Original Hole	4			5/18/2024		
35.4	0.1	Casing joints, 9 5/8in; 1665.2; 35.5 TVD; 1,629.64; 35.5-1640.5 TVD; 35.5-1665.2	Codell, Original Hole	4			5/18/2024		
72.8	0.2	Casing Joints, 5 1/2in; 3171.4; 28 TVD; 3,143.42; 28-3111.9 TVD; 28-3171.4	Codell, Original Hole	4			5/18/2024		
1,665.0	12.6		Codell, Original Hole	4			5/18/2024		
1,690.3	12.6	Casing joints, 9 5/8in; 1707.5; 1641.8 TVD; 40.96; 1641.8-1681.8 TVD; 1666.5-1707.5	Codell, Original Hole	4			5/18/2024		
1,707.3	12.5		Codell, Original Hole	4			5/18/2024		
2,990.5	11.3		Codell, Original Hole	4			5/18/2024		
3,171.3	12.7		Codell, Original Hole	4			5/17/2024		
4,004.3	12.3		Codell, Original Hole	4			5/17/2024		
4,725.4	3.8	Casing Joints, 5 1/2in; 6491; 3126.3 TVD; 3,304.76; 3126.3-6402.6 TVD; 3186.2-6491	Codell, Original Hole	4			5/17/2024		
5,316.6	0.4		Codell, Original Hole	4			5/17/2024		
5,908.1	0.4		Codell, Original Hole	4			5/17/2024		
6,464.9	1.9		Codell, Original Hole	4			5/17/2024		
6,491.1	3.2		Codell, Original Hole	4			5/17/2024		
7,084.6	45.2	Casing Joints, 5 1/2in; 7650.7; 6412.3 TVD; 1,149.92; 6412.3-7105.3 TVD; 6500.8-7650.7	Codell, Original Hole	4			5/17/2024		
7,118.1	49.2		Codell, Original Hole	4			5/17/2024		
7,152.9	53.5		Codell, Original Hole	4			5/17/2024		
7,161.7	54.6		Codell, Original Hole	4			5/17/2024		
7,169.0	55.5		Codell, Original Hole	4			5/17/2024		
7,650.6	86.9		Codell, Original Hole	4			5/17/2024		
7,795.9	87.8		Codell, Original Hole	4			5/17/2024		
8,227.0	91.3		Codell, Original Hole	6			4/9/2024		
8,653.9	90.9		Total					722	
9,076.1	89.8		Job Supply Amounts						
9,460.0	89.5	Casing Joints, 5 1/2in; 11948.6; 7106.5 TVD; 4,276.30; 7106.5-7095.8 TVD; 7672.3-11948.6	Supply Item Des	Job Supply Type	Uni...	Job Category	Total...	Total...	Total...
9,839.9	90.4		Daily Cost Breakdown by Category						
10,219.2	90.0		Field Est (Cost)	Description	Note				
10,946.9	90.9								
11,298.9	91.8								
11,649.9	91.5								
11,959.0	91.2								
12,002.0	90.7								
12,354.0	91.0								
12,705.1	89.6								
13,057.1	90.0								
13,409.1	90.1								
13,759.8	90.1	Casing Joints, 5 1/2in; 15750.3; 7095.4 TVD; 3,779.54; 7095.4-7098.8 TVD; 11970.8-15750.3							
14,111.9	90.2								
14,463.9	89.2								
14,815.0	89.4								
15,167.0	88.3								
15,519.0	90.7								
15,772.0	90.5								
15,870.1	89.2	Casing Joints, 5 1/2in; 16213.6; 7098.7 TVD; 441.58; 7098.7-7099 TVD; 15772-16213.6							
16,213.6	90.7	Wet Shoe Sub, 5 1/2in; 16224.5; 7098.9 TVD; 5.85; 7098.9-7098.8 TVD; 16218.7-16224.5							
16,216.9	90.7								
16,224.4	90.7	Float Collar, 5 1/2in; 16236.3; 7098.7 TVD; 1.83; 7098.7-7098.7 TVD; 16234.5-16236.3							
16,234.9	90.7								
16,246.4	90.7	Float Shoe, 5 1/2in; 16248; 7098.6 TVD; 1.67; 7098.6-7098.5 TVD; 16246.3-16248							