

FORM
2

Rev
05/22

State of Colorado

Energy & Carbon Management Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203
Phone: (303) 894-2100 Fax: (303) 894-2109



Document Number:

403897050

(SUBMITTED)

Date Received:

09/11/2024

APPLICATION FOR PERMIT TO

☒ Drill ☐ Deepen ☐ Re-enter ☐ Recomplete and Operate

Amend ☐

TYPE OF WELL OIL ☒ GAS ☐ COALBED ☐ OTHER: _____

Refill ☐

ZONE TYPE SINGLE ZONE ☒ MULTIPLE ZONES ☐ COMMINGLE ZONES ☐

Sidetrack ☐

Well Name: Fox Creek 12-63

Well Number: 34-23-2

Name of Operator: BISON IV OPERATING LLC

ECMC Operator Number: 10670

Address: 518 17TH STREET SUITE 1800

City: DENVER

State: CO

Zip: 80202

Contact Name: Rachel Milne

Phone: (720)370-8580

Fax: ()

Email: rmilne@bisonog.com

FINANCIAL ASSURANCE FOR PLUGGING, ABANDONMENT, AND RECLAMATION

ECMC Financial Assurance

☒ The Operator has provided or will provide Financial Assurance to the ECMC for this Well.

Surety ID Number (if applicable): 20230068

Federal Financial Assurance

☐ In checking this box, the Operator certifies that it has provided or will provide at least this amount of Financial Assurance to the federal government for this Well. (Per Rule702.a.)

Amount of Federal Financial Assurance \$ _____

WELL LOCATION INFORMATION

Surface Location

QtrQtr: NENE Sec: 34 Twp: 12N Rng: 63W Meridian: 6

FNL/FSL

FEL/FWL

Footage at Surface: 461 Feet FNL 816 Feet FEL

Latitude: 40.971871

Longitude: -104.412385

GPS Data:

GPS Quality Value: 1.4

Type of GPS Quality Value: PDOP

Date of Measurement: 04/12/2017

Ground Elevation: 5352

Field Name: HEREFORD

Field Number: 34200

Well Plan: is ☐ Directional ☒ Horizontal (highly deviated) ☐ Vertical

If Well plan is Directional or Horizontal attach Deviated Drilling Plan and Directional Data.

Subsurface Locations

Top of Productive Zone (TPZ)

Sec: 26 Twp: 12N Rng: 63W

Footage at TPZ: 150 FSL 2432 FWL

Measured Depth of TPZ: 8964

True Vertical Depth of TPZ: 7407

FNL/FSL

FEL/FWL

Base of Productive Zone (BPZ)Sec: 23 Twp: 12N Rng: 63WFootage at BPZ: 289 FNL 2483 FWLMeasured Depth of BPZ: 19018True Vertical Depth of BPZ: 7407 FNL/FSL FEL/FWL**Bottom Hole Location (BHL)**Sec: 23 Twp: 12N Rng: 63WFootage at BHL: 189 FNL 2483 FWL

FNL/FSL

FEL/FWL

LOCAL GOVERNMENT PERMITTING INFORMATIONCounty: WELDMunicipality: N/A

Is the Surface Location of this Well in an area designated as one of State interest and subject to the requirements of § 24-65.1-108 C.R.S.? Yes

Per § 34-60-106(1)(f)(I)(A) C.R.S., the following questions pertain to the Relevant Local Government approval of the siting of the proposed Oil and Gas Location.

SB 19-181 provides that when "applying for a permit to drill," operators must include proof that they sought a local government siting permit and the disposition of that permit application, or that the local government does not have siting regulations. § 34-60-106(1)(f)(I) (A) C.R.S.

Does the Relevant Local Government regulate the siting of Oil and Gas Locations, with respect to this Location? ☒ Yes ☐ No

☒ If yes, in checking this box, I hereby certify that an application has been filed with the local government with jurisdiction to approve the siting of the proposed oil and gas location.

The disposition of the application filed with the Relevant Local Government is: Waived Date of Final Disposition: _____

Comments: Location built prior to WOGLA process.

SURFACE AND MINERAL OWNERSHIP AT WELL'S OIL & GAS LOCATION

Surface Owner of the land at this Well's Oil and Gas Location: ☒ Fee ☐ State ☐ Federal ☐ Indian

Mineral Owner beneath this Well's Oil and Gas Location: ☒ Fee ☐ State ☐ Federal ☐ Indian

Surface Owner Protection Bond (if applicable): _____ Surety ID Number (if applicable): _____

MINERALS DEVELOPED BY WELL

The ownership of all the minerals that will be developed by this Well is (check all that apply):

☒ Fee☐ State☐ Federal☐ Indian☐ N/A**LEASE INFORMATION**

Using standard QtrQtr, Section, Township, Range format describe one entire mineral lease as follows:

* If this Well is within a unit, describe a lease that will be developed by the Well.

* If this Well is not subject to a unit, describe the lease that will be produced by the Well.

(Attach a Lease Map or Lease Description or Lease if necessary.)

12N 63W Section 26: SW

Total Acres in Described Lease: 160 Described Mineral Lease is: ☒ Fee ☐ State ☐ Federal ☐ Indian

Federal or State Lease # _____

SAFETY SETBACK INFORMATION

Distance from Well to nearest:

Building: 1713 Feet
Building Unit: 1948 Feet
Public Road: 1276 Feet
Above Ground Utility: 464 Feet
Railroad: 5280 Feet
Property Line: 461 Feet

INSTRUCTIONS:

- Specify all distances per Rule 308.b.(1).
- Enter 5280 for distance greater than 1 mile.
- Building - nearest building of any type. If nearest Building is a Building Unit, enter same distance for both.
- Building Unit – as defined in 100 Series Rules.

OBJECTIVE FORMATIONS

Objective Formation(s)	Formation Code	Spacing Order Number(s)	Unit Acreage Assigned to Well	Unit Configuration (N/2, SE/4, etc.)
NIOBRARA	NBRR	421-115	1280	T12N R63W Sec 23 and 26: ALL Portions in CO

Federal or State Unit Name (if appl):

Unit Number:

SUBSURFACE MINERAL SETBACKS

Enter 5280 for distance greater than 1 mile.

Is this Well within a unit? Yes

If YES:

Enter the minimum distance from the Completed Zone of this Well to the Unit Boundary: 150 Feet

Enter the minimum distance from the Completed Zone of this Well to the Completed Zone of an offset Well within the same unit permitted or completed in the same formation: 6 Feet

If NO:

Enter the minimum distance from the Completed Zone of this Well to the Lease Line of the described lease: Feet

Enter the minimum distance from the Completed Zone of this Well to the Completed Zone of an offset Well producing from the same lease and permitted or completed in the same formation: Feet

Exception Location

☐ If this Well requires the approval of a Rule 401.c Exception Location, enter the Rule or spacing order number and attach the Exception Location Request and Waivers.

SPACING & FORMATIONS COMMENTS

DRILLING PROGRAM

Proposed Total Measured Depth: 19118 Feet

TVD at Proposed Total Measured Depth 7407 Feet

Distance from the proposed wellbore to nearest existing or proposed wellbore belonging to another operator, including plugged wells:

Enter distance if less than or equal to 1,500 feet: _____ Feet ☒ No well belonging to another operator within 1,500 feet

Will a closed-loop drilling system be used? Yes

Is H₂S gas reasonably expected to be encountered during drilling operations at concentrations greater than or equal to 100 ppm? No If yes, attach an H₂S Drilling Plan unless a plan was already submitted with the Form 2A per Rule 304.c.(10).

Will there be hydraulic fracture treatment at a depth less than 2,000 feet in this well? No

Will salt sections be encountered during drilling? No

Will salt based (>15,000 ppm Cl) drilling fluids be used? No

Will oil based drilling fluids be used? Yes

BOP Equipment Type: ☒ Annular Preventor ☒ Double Ram ☒ Rotating Head ☐ None

Beneficial reuse or land application plan submitted? No

Reuse Facility ID: _____ or Document Number: _____

CASING PROGRAM

Casing Type	Size of Hole	Size of Casing	Grade	Wt/Ft	Csg/Liner Top	Setting Depth	Sacks Cmt	Cmt Btm	Cmt Top
CONDUCTOR	26	16	N/A	37	0	80	50	80	0
SURF	13+1/2	9+5/8	J55	36	0	1900	787	1900	0
1ST	8+1/2	5+1/2	HCP110	20	0	19118	2074	19118	1700

☐ Conductor Casing is NOT planned

POTENTIAL FLOW AND CONFINING FORMATIONS

Zone Type	Formation /Hazard	Top M.D.	Top T.V.D.	Bottom M.D.	Bottom T.V.D.	TDS (mg/L)	Data Source	Comment
Groundwater	Fox Hills	971	971	1371	1371	0-500	DWR	
Groundwater	Base Fox Hills	1371	1371	4371	4319	0-500	DWR	
Hydrocarbon	Parkman	4371	4319	4834	4711			
Confining Layer	Pierre	4834	4711	5567	5249			
Hydrocarbon	Sussex	5567	5249	6071	5603			
Confining Layer	Pierre	6071	5603	6652	6012			
Hydrocarbon	Shannon	6652	6012	6948	6220			
Confining Layer	Pierre	6948	6220	8362	7204			
Confining Layer	Sharon Springs	8362	7204	8558	7309			
Hydrocarbon	Niobrara	8558	7309	19118	7407			Bottom TVD is bottom of the well and not bottom of the formation; the formation is not planned to be exited.

OPERATOR COMMENTS AND SUBMITTAL

Comments

Distance from completed zone of this wellbore to nearest completed zone of an offset well within the same unit permitted or completed in the same formation is to the PR Fox Creek 3-26H (05-123-31417) operated by BISON IV OPERATING LLC, this distance was measured via Anti Collision. No 408.u is attached, as Bison is the operator of the offset well. Bison is aware that the Fox Creek 3-26H wellbore is within 150' of the well being permitted via this Form 2.

This well has a bottom-hole location beyond the unit boundary setback. The bottom of the completed interval will be within the unit boundary setback at 289' FNL and 2483' FWL of Section 23. The wellbore beyond the unit boundary setback will be physically isolated and will not be completed.

BHL was measured to the section line which is in the State of Wyoming, the entire wellbore is in the State of Colorado and is going to be completed 150' from the state line as per the spacing order.

Subsequent Form 9 Doc # 403812604 was submitted on 6/10/2024 to transfer subject well. OWE shows operator after transfer.

This application is in a Comprehensive Area Plan _____ No _____ CAP #: _____
Oil and Gas Development Plan Name _____ OGDID ID#: _____
Location ID: 444342

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: _____ Print Name: Alison Parker

Title: Regulatory Analyst Date: 9/11/2024 Email: aparker@bisonog.com

Based on the information provided herein, this Application for Permit-to-Drill complies with ECMC Rules, applicable orders, and SB 19-181 and is hereby approved.

ECMC Approved: _____ Director of ECMC Date: _____
Expiration Date: _____

API NUMBER

05

CONDITIONS OF APPROVAL, IF ANY LIST

All representations, stipulations and conditions of approval stated in the Form 2A for this location shall constitute representations, stipulations and conditions of approval for this Form 2 Permit-to-Drill and are enforceable to the same extent as all other representations, stipulations and conditions of approval stated in this Permit-to-Drill.

COA Type

Description

0 COA

Best Management Practices

No BMP/COA Type

Description

1	Drilling/Completion Operations	Blowout Prevention Equipment ("BOPE"): A double ram annular preventer will be used during drilling.
---	--------------------------------	-----------------------------------------------------------------------------------------------------

2	Drilling/Completion Operations	Anti-collision: Operator will perform an anti-collision evaluation of all active (producing, shut in, or temporarily abandoned) offset wellbores that have the potential of being within 150 feet of a proposed well prior to drilling operations for the proposed well. Notice shall be given to all offset operators prior to drilling.
3	Drilling/Completion Operations	Alternative Logging Program - One of the first wells drilled on the pad will be logged with Open Hole Resistivity Log and Gamma Ray Log from the kick-off point to into the surface casing. All wells on the pad will have a cement bond log with gamma-ray run on production casing (or on intermediate casing if production liner is run) into the surface casing. The horizontal portion of every well will be logged with a measured-while-drilling gamma-ray log. The Form 5, Completion Report, for each well on the pad will list all logs run and have those logs attached. The Form 5 for a well without open-hole logs shall clearly state "Alternative Logging Program - No open-hole logs were run" and shall clearly identify (by API#, well name & number) the well in which open-hole logs were run.
4	Drilling/Completion Operations	When a skid is performed, if a previous well on that pad has completed a full BOPE test within the past 21 days, then the only required BOPE tests are for the BOPE connections that were broken during skid. The purpose of this is to prevent the wear and tear on the choke line and kill line valves. The annular and double rams will be tested as per usual, and all broken connections will also be tested (annular to 70% of rated pressure, all other values and connections will be tested to full rated pressure). Under no circumstances will 21 days be exceeded without completing a full BOPE Test to all connections including all choke and kill line valves. Daily function test/activation of pipe rams are still required in addition to a preventer operator test on each trip.

Total: 4 comment(s)

ATTACHMENT LIST

<u>Att Doc Num</u>	<u>Name</u>
403898084	WELL LOCATION PLAT
403900090	OTHER
403900091	DEVIATED DRILLING PLAN
403900095	DIRECTIONAL DATA
403917562	OffsetWellEvaluations Data

Total Attach: 5 Files

General Comments

<u>User Group</u>	<u>Comment</u>	<u>Comment Date</u>
		Stamp Upon Approval

Total: 0 comment(s)