

FORM  
5A

Rev  
09/20

State of Colorado

Energy & Carbon Management Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



DE	ET	OE	ES
----	----	----	----

Document Number:  
403801596

Date Received:  
05/23/2024

COMPLETED INTERVAL REPORT

The completed interval Report, Form 5A, shall be submitted within thirty (30) days of completing a formation (successful or not), when a formation is temporarily abandoned or permanently abandoned, for a recompletion, reperforation or restimulation, or when a formation is commingled. Fill out a section for each formation. Attach as many pages as required to fully describe the work. List in order of completion.

1. ECMC Operator Number: <u>10261</u>	4. Contact Name: <u>Robert Carney</u>
2. Name of Operator: <u>BAYSWATER EXPLORATION &amp; PRODUCTION LLC</u>	Phone: <u>(720) 881-4509</u>
3. Address: <u>730 17TH ST STE 500</u>	Fax: _____
City: <u>DENVER</u> State: <u>CO</u> Zip: <u>80202</u>	Email: <u>RCarney@bayswater.us</u>

5. API Number <u>05-123-51625-00</u>	6. County: <u>WELD</u>
7. Well Name: <u>Blehm</u>	Well Number: <u>5</u>
8. Location: QtrQtr: <u>Lot 3</u> Section: <u>18</u> Township: <u>7N</u> Range: <u>66W</u> Meridian: <u>6</u>	
9. Field Name: <u>WATTENBERG</u> Field Code: <u>90750</u>	

### Completed Interval

FORMATION: CARLILE Status: COMMINGLED Treatment Type: \_\_\_\_\_

Treatment Date: \_\_\_\_\_ End Date: \_\_\_\_\_ Date this Formation was Completed: \_\_\_\_\_

Perforations Top: 13225 Bottom: 17795 No. Holes: 1370 Hole size: \_\_\_\_\_ Open Hole:

Describe the Formation Treatment, including the following: type of fluid used (gel, slickwater, etc.), type and concentration of acid used (HCl, HF, etc.), types and amounts of proppant(s) used, depth details of multiple zones, and method used to determine flowback volume.

Carlile perforated from 13,225'- 13,328'; 13,734'- 14,676'; 15,427'- 15,604'; and 17,713'- 17,795'.

This formation is commingled with another formation:  Yes  No

Total fluid used in treatment (bbl): \_\_\_\_\_ Max pressure during treatment (psi): \_\_\_\_\_

Total gas used in treatment (mcf): \_\_\_\_\_ Fluid density at initial fracture (lbs/gal): \_\_\_\_\_

Type of gas used in treatment: \_\_\_\_\_ Min frac gradient (psi/ft): \_\_\_\_\_

Total acid used in treatment (bbl): \_\_\_\_\_ Number of staged intervals: \_\_\_\_\_

Recycled or Reused Fluids used in treatment (bbl): \_\_\_\_\_ Flowback volume recovered (bbl): \_\_\_\_\_

Fresh water used in treatment (bbl): \_\_\_\_\_ Disposition method for flowback: \_\_\_\_\_

Total proppant used (lbs): \_\_\_\_\_

**Fracture stimulations must be reported on FracFocus.org**

#### Test Information:

Hours: \_\_\_\_\_ Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_

Calculated 24 hour rate: Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_ GOR: \_\_\_\_\_

Test Method: \_\_\_\_\_ Casing PSI: \_\_\_\_\_ Tubing PSI: \_\_\_\_\_ Choke Size: \_\_\_\_\_

Gas Disposition: \_\_\_\_\_ Gas Type: \_\_\_\_\_ Btu Gas: \_\_\_\_\_ API Gravity Oil: \_\_\_\_\_

Tubing Size: \_\_\_\_\_ Tubing Setting Depth: \_\_\_\_\_ Tbg setting date: \_\_\_\_\_ Packer Depth: \_\_\_\_\_

Reason for Non-Production: \_\_\_\_\_

Date formation Abandoned: \_\_\_\_\_ Squeeze:  Yes  No If yes, number of sacks cmt \_\_\_\_\_

\*\* Bridge Plug Depth: \_\_\_\_\_ \*\* Sacks cement on top: \_\_\_\_\_ \*\* Wireline and Cement Job Summary must be attached.

FORMATION: CODELL Status: COMMINGLED Treatment Type: \_\_\_\_\_

Treatment Date: \_\_\_\_\_ End Date: \_\_\_\_\_ Date this Formation was Completed: \_\_\_\_\_

Perforations Top: 8053 Bottom: 17713 No. Holes: 1370 Hole size: \_\_\_\_\_ Open Hole:

Describe the Formation Treatment, including the following: type of fluid used (gel, slickwater, etc.), type and concentration of acid used (HCl, HF, etc.), types and amounts of proppant(s) used, depth details of multiple zones, and method used to determine flowback volume.

Codell was perforated from 8,053'- 13,225'; 13,508'- 13,734'; 14,676'-15,287'; and 15,604'- 17,713'.

This formation is commingled with another formation:  Yes  No

Total fluid used in treatment (bbl): \_\_\_\_\_ Max pressure during treatment (psi): \_\_\_\_\_

Total gas used in treatment (mcf): \_\_\_\_\_ Fluid density at initial fracture (lbs/gal): \_\_\_\_\_

Type of gas used in treatment: \_\_\_\_\_ Min frac gradient (psi/ft): \_\_\_\_\_

Total acid used in treatment (bbl): \_\_\_\_\_ Number of staged intervals: \_\_\_\_\_

Recycled or Reused Fluids used in treatment (bbl): \_\_\_\_\_ Flowback volume recovered (bbl): \_\_\_\_\_

Fresh water used in treatment (bbl): \_\_\_\_\_ Disposition method for flowback: \_\_\_\_\_

Total proppant used (lbs): \_\_\_\_\_

Fracture stimulations must be reported on FracFocus.org

Test Information:

Hours: Bbl oil: Mcf Gas: Bbl H2O:
Date: Calculated 24 hour rate: Bbl oil: Mcf Gas: Bbl H2O: GOR:
Test Method: Casing PSI: Tubing PSI: Choke Size:
Gas Disposition: Gas Type: Btu Gas: API Gravity Oil:
Tubing Size: Tubing Setting Depth: Tbg setting date: Packer Depth:
Reason for Non-Production:
Date formation Abandoned: Squeeze: Yes No If yes, number of sacks cmt
\*\* Bridge Plug Depth: \*\* Sacks cement on top: \*\* Wireline and Cement Job Summary must be attached.

FORMATION: FORT HAYS Status: COMMINGLED Treatment Type:

Treatment Date: End Date: Date this Formation was Completed:
Perforations Top: 7899 Bottom: 15427 No. Holes: 1370 Hole size: Open Hole:

Describe the Formation Treatment, including the following: type of fluid used (gel, slickwater, etc.), type and concentration of acid used (HCl, HF, etc.), types and amounts of proppant(s) used, depth details of multiple zones, and method used to determine flowback volume.

Ft Hays was perforated from 7,899'- 8,053'; 13,328'- 13,508'; and 15,287'- 15,427'.

This formation is commingled with another formation: Yes No
Total fluid used in treatment (bbl): Max pressure during treatment (psi):
Total gas used in treatment (mcf): Fluid density at initial fracture (lbs/gal):
Type of gas used in treatment: Min frac gradient (psi/ft):
Total acid used in treatment (bbl): Number of staged intervals:
Recycled or Reused Fluids used in treatment (bbl): Flowback volume recovered (bbl):
Fresh water used in treatment (bbl): Disposition method for flowback:
Total proppant used (lbs):

Fracture stimulations must be reported on FracFocus.org

Test Information:

Hours: Bbl oil: Mcf Gas: Bbl H2O:
Date: Calculated 24 hour rate: Bbl oil: Mcf Gas: Bbl H2O: GOR:
Test Method: Casing PSI: Tubing PSI: Choke Size:
Gas Disposition: Gas Type: Btu Gas: API Gravity Oil:
Tubing Size: Tubing Setting Depth: Tbg setting date: Packer Depth:
Reason for Non-Production:
Date formation Abandoned: Squeeze: Yes No If yes, number of sacks cmt
\*\* Bridge Plug Depth: \*\* Sacks cement on top: \*\* Wireline and Cement Job Summary must be attached.

FORMATION: NIOBRARA Status: COMMINGLED Treatment Type:

Treatment Date: End Date: Date this Formation was Completed:
Perforations Top: 7813 Bottom: 7899 No. Holes: 1370 Hole size: Open Hole:

Describe the Formation Treatment, including the following: type of fluid used (gel, slickwater, etc.), type and concentration of acid used (HCl, HF, etc.), types and amounts of proppant(s) used, depth details of multiple zones, and method used to determine flowback volume.

Niobrara was perforated from 7,813'- 7,899'.

This formation is commingled with another formation:  Yes  No

Total fluid used in treatment (bbl): \_\_\_\_\_ Max pressure during treatment (psi): \_\_\_\_\_

Total gas used in treatment (mcf): \_\_\_\_\_ Fluid density at initial fracture (lbs/gal): \_\_\_\_\_

Type of gas used in treatment: \_\_\_\_\_ Min frac gradient (psi/ft): \_\_\_\_\_

Total acid used in treatment (bbl): \_\_\_\_\_ Number of staged intervals: \_\_\_\_\_

Recycled or Reused Fluids used in treatment (bbl): \_\_\_\_\_ Flowback volume recovered (bbl): \_\_\_\_\_

Fresh water used in treatment (bbl): \_\_\_\_\_ Disposition method for flowback: \_\_\_\_\_

Total proppant used (lbs): \_\_\_\_\_

**Fracture stimulations must be reported on FracFocus.org**

**Test Information:**

\_\_\_\_\_ Hours: \_\_\_\_\_ Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_

Calculated 24 hour rate: Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_ GOR: \_\_\_\_\_

Test Method: \_\_\_\_\_ Casing PSI: \_\_\_\_\_ Tubing PSI: \_\_\_\_\_ Choke Size: \_\_\_\_\_

Gas Disposition: \_\_\_\_\_ Gas Type: \_\_\_\_\_ Btu Gas: \_\_\_\_\_ API Gravity Oil: \_\_\_\_\_

Tubing Size: \_\_\_\_\_ Tubing Setting Depth: \_\_\_\_\_ Tbg setting date: \_\_\_\_\_ Packer Depth: \_\_\_\_\_

Reason for Non-Production: \_\_\_\_\_

Date formation Abandoned: \_\_\_\_\_ Squeeze:  Yes  No If yes, number of sacks cmt \_\_\_\_\_

\*\* Bridge Plug Depth: \_\_\_\_\_ \*\* Sacks cement on top: \_\_\_\_\_ \*\* Wireline and Cement Job Summary must be attached.

FORMATION: NIOBRARA-FORT HAYS-CODELL-CARLILE Status: PRODUCING Treatment Type: HYDRAULIC FRACTURING

Treatment Date: 06/23/2022 End Date: 07/14/2022 Date this Formation was Completed: 09/21/2022
Perforations Top: 7813 Bottom: 17835 No. Holes: 1370 Hole size: 0.433 Open Hole:

Describe the Formation Treatment, including the following: type of fluid used (gel, slickwater, etc.), type and concentration of acid used (HCl, HF, etc.), types and amounts of proppant(s) used, depth details of multiple zones, and method used to determine flowback volume.

267 bbls 15% HCl; 12,942 bbls Pump Down; 402,804 bbls FR Water. 978,980 lbs 100 Mesh Premium White sand; 11,463,138 lbs 30/50 Premium White sand; 1,524,720 lbs 40/70 Premium White sand. Flowback volume metered.

This formation is commingled with another formation: Yes No

Total fluid used in treatment (bbl): 416013 Max pressure during treatment (psi): 9109
Total gas used in treatment (mcf): 0 Fluid density at initial fracture (lbs/gal): 8.33
Type of gas used in treatment: Min frac gradient (psi/ft): 0.84
Total acid used in treatment (bbl): 267 Number of staged intervals: 51
Recycled or Reused Fluids used in treatment (bbl): 0 Flowback volume recovered (bbl): 1920
Fresh water used in treatment (bbl): 415746 Disposition method for flowback: DISPOSAL
Total proppant used (lbs): 13966838

Fracture stimulations must be reported on FracFocus.org

Test Information:

09/21/2022 Hours: 24 Bbl oil: 264 Mcf Gas: 196 Bbl H2O: 1152
Calculated 24 hour rate: Bbl oil: 264 Mcf Gas: 196 Bbl H2O: 1152 GOR: 742
Test Method: Flowback Casing PSI: 0 Tubing PSI: 2659 Choke Size: 14/64
Gas Disposition: SOLD Gas Type: WET Btu Gas: 1401 API Gravity Oil: 41
Tubing Size: 2 + 3/8 Tubing Setting Depth: 7775 Tbg setting date: 09/02/2022 Packer Depth: 7775

Reason for Non-Production:

Date formation Abandoned: Squeeze: Yes No If yes, number of sacks cmt

\*\* Bridge Plug Depth: \*\* Sacks cement on top: \*\* Wireline and Cement Job Summary must be attached.

Comment:

After the approval of the original Form 5A (doc #403253329), errors were found in the 3rd party frac summary report. The report has been corrected and this submittal is to report the corrected completion information.

Actual TPZ: 1924' FNL & 286' FEL, Section 13-T7N-R67W
Actual BPZ: 1948' FNL & 290' FWL, Section 14-T7N-R67W

The wellbore beyond the unit boundary setback is physically isolated with a plug and Bayswater certifies that none of the wellbore beyond the setback was completed.

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: Print Name: Kelsi Welch
Title: Permitting & Compliance Date: 5/23/2024 Email: Kelsi.welch@iptwell.com

ATTACHMENT LIST

Table with 2 columns: Att Doc Num, Name. Rows: 403801596 FORM 5A SUBMITTED, 403801639 OPERATIONS SUMMARY

Total Attach: 2 Files

**General Comments**

**User Group**

**Comment**

**Comment Date**

		Stamp Upon Approval
--	--	---------------------

Total: 0 comment(s)