

Base of Productive Zone (BPZ)

Sec: 20 Twp: 5N Rng: 66W Footage at BPZ: 1284 FNL 2503 FWL
Measured Depth of BPZ: 18420 True Vertical Depth of BPZ: 7398 FNL/FSL FEL/FWL

Bottom Hole Location (BHL)

Sec: 20 Twp: 5N Rng: 66W Footage at BHL: 1285 FNL 2553 FWL
FNL/FSL FEL/FWL

LOCAL GOVERNMENT PERMITTING INFORMATION

County: WELD Municipality: Greeley

Is the Surface Location of this Well in an area designated as one of State interest and subject to the requirements of § 24-65.1-108 C.R.S.? Yes

Per § 34-60-106(1)(f)(I)(A) C.R.S., the following questions pertain to the Relevant Local Government approval of the siting of the proposed Oil and Gas Location.

SB 19-181 provides that when "applying for a permit to drill," operators must include proof that they sought a local government siting permit and the disposition of that permit application, or that the local government does not have siting regulations. § 34-60-106(1)(f)(I)(A) C.R.S.

Does the Relevant Local Government regulate the siting of Oil and Gas Locations, with respect to this Location? [X] Yes [] No

[X] If yes, in checking this box, I hereby certify that an application has been filed with the local government with jurisdiction to approve the siting of the proposed oil and gas location.

The disposition of the application filed with the Relevant Local Government is: Approved Date of Final Disposition: 08/17/2023

Comments: 1041WOGLA23-0037 was approved on 8/17/2023

SURFACE AND MINERAL OWNERSHIP AT WELL'S OIL & GAS LOCATION

Surface Owner of the land at this Well's Oil and Gas Location: [X] Fee [] State [] Federal [] Indian

Mineral Owner beneath this Well's Oil and Gas Location: [X] Fee [] State [] Federal [] Indian

Surface Owner Protection Bond (if applicable): Surety ID Number (if applicable):

MINERALS DEVELOPED BY WELL

The ownership of all the minerals that will be developed by this Well is (check all that apply):

- [X] Fee
- [] State
- [] Federal
- [] Indian
- [] N/A

LEASE INFORMATION

Using standard QtrQtr, Section, Township, Range format describe one entire mineral lease as follows:

* If this Well is within a unit, describe a lease that will be developed by the Well.

* If this Well is not subject to a unit, describe the lease that will be produced by the Well.

(Attach a Lease Map or Lease Description or Lease if necessary.)

Township 5 North - Range 67 West Section 24: SE4

Total Acres in Described Lease: 160 Described Mineral Lease is: Fee State Federal Indian

Federal or State Lease # _____

SAFETY SETBACK INFORMATION

Distance from Well to nearest:

Building: 2146 Feet
Building Unit: 2292 Feet
Public Road: 1833 Feet
Above Ground Utility: 2113 Feet
Railroad: 5280 Feet
Property Line: 233 Feet

INSTRUCTIONS:

- Specify all distances per Rule 308.b.(1).
- Enter 5280 for distance greater than 1 mile.
- Building - nearest building of any type. If nearest Building is a Building Unit, enter same distance for both.
- Building Unit – as defined in 100 Series Rules.

OBJECTIVE FORMATIONS

Objective Formation(s)	Formation Code	Spacing Order Number(s)	Unit Acreage Assigned to Well	Unit Configuration (N/2, SE/4, etc.)
NIOBRARA	NBRR	407-3556	2230	Township 5 North, Range 66 West Section 19: All Section 20: W2 Township 5 North, Range 67 West Section 23: All Section 24: All

Federal or State Unit Name (if appl): _____ Unit Number: _____

SUBSURFACE MINERAL SETBACKS

Enter 5280 for distance greater than 1 mile.

Is this Well within a unit? Yes

If YES:

Enter the minimum distance from the Completed Zone of this Well to the Unit Boundary: 151 Feet

Enter the minimum distance from the Completed Zone of this Well to the Completed Zone of an offset Well within the same unit permitted or completed in the same formation: 295 Feet

If NO:

Enter the minimum distance from the Completed Zone of this Well to the Lease Line of the described lease: _____ Feet

Enter the minimum distance from the Completed Zone of this Well to the Completed Zone of an offset Well producing from the same lease and permitted or completed in the same formation: _____ Feet

Exception Location

If this Well requires the approval of a Rule 401.c Exception Location, enter the Rule or spacing order number and attach the Exception Location Request and Waivers. _____

SPACING & FORMATIONS COMMENTS

DRILLING PROGRAMProposed Total Measured Depth: 18470 Feet TVD at Proposed Total Measured Depth 7398 Feet

Distance from the proposed wellbore to nearest existing or proposed wellbore belonging to another operator, including plugged wells:

Enter distance if less than or equal to 1,500 feet: 135 Feet No well belonging to another operator within 1,500 feetWill a closed-loop drilling system be used? YesIs H₂S gas reasonably expected to be encountered during drilling operations at concentrations greater than or equal to 100 ppm? No If yes, attach an H₂S Drilling Plan unless a plan was already submitted with the Form 2A per Rule 304.c.(10).Will there be hydraulic fracture treatment at a depth less than 2,000 feet in this well? NoWill salt sections be encountered during drilling? NoWill salt based (>15,000 ppm Cl) drilling fluids be used? NoWill oil based drilling fluids be used? YesBOP Equipment Type: Annular Preventor Double Ram Rotating Head NoneBeneficial reuse or land application plan submitted? No

Reuse Facility ID: _____ or Document Number: _____

CASING PROGRAM

<u>Casing Type</u>	<u>Size of Hole</u>	<u>Size of Casing</u>	<u>Grade</u>	<u>Wt/Ft</u>	<u>Csg/Liner Top</u>	<u>Setting Depth</u>	<u>Sacks Cmt</u>	<u>Cmt Btm</u>	<u>Cmt Top</u>
CONDUCTOR	26	16	A-52A	36.94	0	80	175	80	0
SURF	13+1/2	9+5/8	J-55	36	0	1850	633	1850	0
1ST	8+1/2	5+1/2	P-110	17	0	18470	2163	18470	

 Conductor Casing is NOT planned**POTENTIAL FLOW AND CONFINING FORMATIONS**

<u>Zone Type</u>	<u>Formation /Hazard</u>	<u>Top M.D.</u>	<u>Top T.V.D.</u>	<u>Bottom M.D.</u>	<u>Bottom T.V.D.</u>	<u>TDS (mg/L)</u>	<u>Data Source</u>	<u>Comment</u>
Confining Layer	Pierre Shale	0	0	545	545			
Groundwater	UPIR/Pawnee Aquifer	545	545	1513	1508	1001-10000	Other	COGCC UPWQ Study
Confining Layer	Pierre Shale	1513	1508	4018	3864			
Hydrocarbon	Parkman	4018	3864	4426	4245			
Confining Layer	Pierre Shale	4426	4245	4655	4460			
Hydrocarbon	Sussex	4655	4460	4919	4708			
Confining Layer	Pierre Shale	4919	4708	5184	4956			
Hydrocarbon	Shannon	5184	4956	5393	5152			
Confining Layer	Pierre Shale	5393	5152	7548	7150			
Subsurface Hazard	Sharon Springs Shale	7548	7150	7598	7187			least competent shales
Hydrocarbon	Niobrara	7598	7187	18470	7398			Nio Target

OPERATOR COMMENTS AND SUBMITTAL

Comments

PDC Energy shall isolate both the Fox Hills and UPIR/Pawnee Aquifers with surface casing from hydrocarbon bearing zones and exposure to oil-based drilling fluid. PDC Energy also agrees to not expose the UPIR/Pawnee Aquifers to oil-based mud.

Fox Hills is not anticipated to be encountered.

The nearest well in the same formation is located on the same pad, the WINDOM 3NA operated by PDC Energy Inc. Measured in 2D.

The distance to another wellbore belonging to an outside operator is the D.L. PHILLIPS #24-24 (05-123-19879) Operated by NOBLE ENERGY INC, status TA. The distance was calculated using the anti-collision summary. 408.u consent attached.

Wells within 150':

SW GREELEY #18-20 05-123-26603 (PA) 27' operated by PDC ENERGY INC, no 408.u is required, well has been plugged and abandoned.

This well has a bottom-hole location beyond the unit boundary setback. The bottom of the completed interval will be within the unit boundary setback at 1284' FNL and 2503' FWL of Section 20. The wellbore beyond the unit boundary setback will be physically isolated and will not be completed.

This application is in a Comprehensive Area Plan Yes CAP #: 210200012

Oil and Gas Development Plan Name Cameron 2 OGDP ID#: 485239

Location ID: 485814

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: _____ Print Name: Kim Bauer

Title: Regulatory Analyst II Date: 7/18/2024 Email: kimberlybauer@chevron.com

Operator must have a valid water right or permit allowing for industrial use or purchased water from a seller that has a valid water right or permit allowing for industrial use, otherwise an application for a change in type of use is required under Colorado law. Operator must also use the water in the location set forth in the water right decree or well permit, otherwise an application for a change in place of use is required under Colorado law. Section 37-92-103(5), C.R.S. (2011).

Based on the information provided herein, this Application for Permit-to-Drill complies with ECMC Rules, applicable orders, and SB 19-181 and is hereby approved.

ECMC Approved:  Director of ECMC Date: 9/15/2024

Expiration Date: 12/08/2032

API NUMBER
05 123 52698 00

CONDITIONS OF APPROVAL, IF ANY LIST

All representations, stipulations and conditions of approval stated in the Form 2A for this location shall constitute representations, stipulations and conditions of approval for this Form 2 Permit-to-Drill and are enforceable to the same extent as all other representations, stipulations and conditions of approval stated in this Permit-to-Drill.

COA Type	Description
Drilling/Completion Operations	The Operator will insure the wellbore beyond the unit boundary setback is physically isolated and is not completed. In the Operator Comments on the Form 5A the operator will (1) report the footages from the section lines of the bottom of the completed interval (2) describe how the wellbore beyond the unit boundary setback is physically isolated and (3) certify that none of the wellbore beyond the setback was completed.

Drilling/Completion Operations	<p>1) Submit Form 42 electronically to ECMC 2 business days prior to MIRU (spud notice) for the first well activity with a rig on the pad and provide 2 business day spud notice via Form 42 for all subsequent wells drilled on the pad.</p> <p>2) Comply with Rule 408.j. and provide cement coverage from TD to a minimum of 500' above Niobrara. Verify coverage with a cement bond log.</p> <p>3) Oil based drilling fluid can only be used after all groundwater has been isolated.</p>
Drilling/Completion Operations	<p>Per Order 1-232, Bradenhead tests shall be performed according to the following schedule and Form 17 submitted within 10 days of each test:</p> <p>1) Within 60 days of rig release, prior to stimulation. If any pressure greater than 200 psi is observed or if there is continuous flow, Operator must contact ECMC engineering for approval prior to stimulation.</p> <p>2) If a delayed completion, a second test is required between 6-9 months after rig release and must be conducted prior to stimulation. If any pressure greater than 200 psi is observed or if there is continuous flow, Operator must contact ECMC engineering for approval prior to stimulation.</p> <p>3) A post-production test within 60 days after first sales, as reported on the Form 10, Certificate of Clearance.</p>
Drilling/Completion Operations	<p>Operator acknowledges the proximity of the listed wells. Operator agrees to: provide mitigation option 1 or 2 (per the Offset Well Evaluation and Hydraulic Fracturing Operator Guidance Document) to mitigate the situation, ensure all applicable documentation is submitted based on the selected mitigation option chosen, and submit a Form 42 ("OFFSET MITIGATION COMPLETED") stating that appropriate mitigation occurred and that it has been completed, prior to the hydraulic stimulation of this well.</p> <p>PDC ENERGY INC 123-11720 PHILLIPS * #1 NOBLE ENERGY INC 123-18368 D.L. PHILLIPS *24-21 NOBLE ENERGY INC 123-18369 D.L. PHILLIPS *24-22 NOBLE ENERGY INC 123-18983 GOLDBERG *N 24-2 PDC ENERGY INC 123-13483 LUNDVALL UP *2-19 PDC ENERGY INC 123-13484 LUNDVALL UP *7-19 NOBLE ENERGY INC 123-20564 HSR-LUNDVALL *8-19 NOBLE ENERGY INC 123-21109 GOLDBERG N *24-8</p> <p>Operator acknowledges the proximity of the listed non-operated wells. Operator assures that this offset list will be remediated per the Offset Well Evaluation and Hydraulic Fracturing Operator Guidance Document (option 4). Operator will submit a Form 42 ("OFFSET MITIGATION COMPLETED") stating that appropriate mitigation will be completed, during the hydraulic stimulation of this well. This Form 42 shall be filed 48 hours prior to stimulation. A Bradenhead test will be performed on the offset wells listed below within 30 days prior to the beginning of stimulation of this well. A Bradenhead test will be performed on the offset wells listed below within 30 days of the end of stimulation of this well. Surface and production casing pressures of this offset well list will be actively monitored during stimulation of this well. If there is indication of communication between the stimulation treatment and an offset well, treatment will be stopped and ECMC Engineering notified. Within 60 days after stimulation is complete, a Form 4 Sundry shall be submitted for each offset well on this list describing how Option 4 work was completed and include a summary of the monitoring details.</p> <p>PDC ENERGY INC 123-49916 Sanford *03N PDC ENERGY INC 123-49919 Sanford *04NA PDC ENERGY INC 123-49920 Sanford *10N PDC ENERGY INC 123-49921 Sanford *01C PDC ENERGY INC 123-49926 Sanford *08C PDC ENERGY INC 123-49932 Sanford *02N</p>
Drilling/Completion Operations	<p>Operator will log two (2) additional wells during the first rig occupation with open-hole resistivity log with gamma-ray log from the kick-off point into the surface casing for the two stratigraphically deepest wells on each side/direction of the pad for a total of three wells logged.</p>
5 COAs	

Best Management Practices

<u>No</u>	<u>BMP/COA Type</u>	<u>Description</u>
1	Drilling/Completion Operations	During and Post stimulation: PDC Energy Inc will comply with the COGCC Policy for Bradenhead Monitoring During Hydraulic Fracturing Treatments in the Greater Wattenberg Area dated 5/29/12.`
2	Drilling/Completion Operations	If a skid is performed for the subject well, then the only required BOPE tests are for the BOPE connection bonnet seal breaks, as long as a full BOPE test was performed at the beginning of the pad, and as long as all necessary BOPE tests are completed at least every 30 days during the pad operations.`
3	Drilling/Completion Operations	Operator will perform anti-collision evaluation of all active (producing, shut-in, or temporarily abandoned) offset wellbores that have the potential of being within 150' of the proposed well prior to drilling operations.`
4	Drilling/Completion Operations	One of the first wells drilled on the pad during the first rig occupation will be logged with open-hole resistivity log with gamma-ray log from the kick-off point into the surface casing for one of the stratigraphically deepest wells on the pad. All wells on the pad will have a cement bond log with gamma-ray run on production casing (or on intermediate casing if production liner is run) into the surface casing. The horizontal portion of every well will be logged with a measured-while-drilling gamma-ray log. The Form 5, Completion Report, for each well on the pad will list all logs run and have those logs attached. The Form 5 for a well without open-hole logs will state "Alternative Logging Program - No open-hole logs were run" and will clearly identify the type of log and the well (by API#) in which open-hole logs were run.`

Total: 4 comment(s)

ATTACHMENT LIST

<u>Att Doc Num</u>	<u>Name</u>
403770510	FORM 2 SUBMITTED
403770532	WELL LOCATION PLAT
403789959	SURFACE AGRMT/SURETY
403795065	OffsetWellEvaluations Data
403816215	DEVIATED DRILLING PLAN
403816216	STIMULATION SETBACK CONSENT
403816892	DIRECTIONAL DATA
403921384	OFFSET WELL EVALUATION

Total Attach: 8 Files

General Comments

<u>User Group</u>	<u>Comment</u>	<u>Comment Date</u>
Permit	Final Review Completed.	08/06/2024
Permit	Permitting review complete	07/16/2024
OGLA	The Commission approved OGDG #485239 on December 20, 2023 for the Oil and Gas Location related to this Form 2. OGLA task passed.	06/13/2024

Total: 3 comment(s)