

Speed Goat Fed 3432-07H



DESCRIPTION DEPTH WELLBORE

Date 9/12/2024

WELL: Speed Goat Fed 3432-07H Pre-Frac WBD

LOCATION: NENE Sec 24 9N58W
327' FNL; 961' FEL

FORMATION: Nio B

API #: 05-123-52506

Field: DJ Horizontal Niobrara

Spud: 04/13/24

Current Status: Awaiting Completions

Well Type Horizontal

Well Length XXRL

Casing and Tubular Data

Type	Size	Weight	Top	Bottom	Hole Size	Cement Type
Surface	9 5/8	36.0 ppf	0'	1,560'	13.5"	15.8ppg Class G
Production	5 1/2	20.0 ppf	0'	20,268'	8.5"	13.2# Elasticem Lead,
Tubing	2 3/8	4.6 ppf	0'	n/a	n/a	13.2# Neocem Tail

Elevation Data

GL	4722	feet
KB	4743	feet
Difference	21	feet
*All depths from GL unless otherwise noted		

TPZ/ Heal Setback Depth (MD GL): 7,383'
BPZ/ Toe Setback Depth (MD GL): 20,181'
Production Casing Info: 5.5" 20# US Steel P110HP Freedom HTQ
Cement to Surface during 5.5" Job: 50 bbls

Sfc Casing Shoe: 1,560'

TOC (CBL Verified): 1,248'

Formation Tops

TOP (MD RKB)		TOP (TVD RKB)	
Fox Hills	21'	Fox Hills	21'
Pierre	471'	Pierre	471'
Upper Pierre Aquifer	890'	Upper Pierre Aquifer	886'
Pierre	1,377'	Pierre	1,352'
Parkman	3,662'	Parkman	3,176'
Sussex	4,513'	Sussex	3,806'
Pierre	5,006'	Pierre	4,174'
Shannon	5,400'	Shannon	4,468'
Pierre	6,008'	Pierre	4,925'
Sharon Springs	6,756'	Sharon Springs	5,461'
Niobrara	6,894'	Niobrara	5,534'
-	-	-	-
-	-	-	-
-	-	-	-

KOP: 6,330'

30 Deg: 6,330'

60 Deg: 6,868'

Max TVD: 6,868'

7,595'

7,382'

20,160'

20,219'

20,160'

20,283'

Air Lock Sub (GL):

Land Point (GL):

Toe Initiation Sleeve

Float Collar

Production Csg Shoe TD