



## P&A Wellbore Diagram

Operator: Prairie Operating Co

Operator #: 10819

Well Name: Weitzel 8-3

Location: Weld, CO

API: 05-123-09370

Legal: SWSW 8-7N-60W

### Current

### Proposed

Deepest Water Well (1 mile): 526'

#### Well History

Spud Date: 04/01/1978

Perfs: J-Sand 6972' - 6978'

J-Sand: 6984' - 6992'

Plug Date: 11/10/1978

Liner TOC: ' (CALC)

S.C. 1.2: 0' - 28'

10 sacks of cement

Surface Hole: 12.25"

Surface Casing:

8.625" 24# @ 253'

190 sacks of cement

S.C. 1.2: 190' - 145'

15 sacks of cement

O.H. 2.1: 400' - 325'

25 sacks of cement

P.C. 2.2: 5930' - 5830'

10 sacks of cement

Casing Stub: 5,930'

P.C. 3.1: 6950' - 6850'

10 sacks of cement

P.C.32.2: 5930' - 5830'

10 sacks of cement

Production Hole: 7.875"

Production Casing:

4.5" 10.5# @ 7004'

125 sacks of cement

TD: 7017'

175 sx  
0-550'

145 sx  
1,500'-2,000'

120 sx on top  
6200' - CICR  
6,300' - Perfs

#### Formations

Fox Hills (Btm)	496'
Upper Pierre (Btm)	1838'
Sussex (Top)	3436'
Shannon (Top)	4678'
Niobrara (Top)	6219'
Codell (Top)	6502'
J-Sand (Top)	6972'

#### Legend

Existing Cement

Cement Pumped

CIBP

CICR

6972' - 6978'

6984' - 6992'

Class G 15.8# 1.19ft3/sack 20% OH Excess