

FORM
2
Rev
05/22

State of Colorado
Energy & Carbon Management Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203
Phone: (303) 894-2100 Fax: (303) 894-2109



Document Number:

403862322

Date Received:

08/07/2024

APPLICATION FOR PERMIT TO

Drill Deepen Re-enter Recomplete and Operate

Amend

TYPE OF WELL OIL GAS COALBED OTHER: _____

Refile

ZONE TYPE SINGLE ZONE MULTIPLE ZONES COMMINGLE ZONES

Sidetrack

Well Name: CE 5-68 Well Number: 11-10-11H
Name of Operator: BISON IV OPERATING LLC ECMC Operator Number: 10670
Address: 518 17TH STREET SUITE 1800
City: DENVER State: CO Zip: 80202
Contact Name: Rachel Milne Phone: (720)370-8580 Fax: ()
Email: rmilne@bisonog.com

FINANCIAL ASSURANCE FOR PLUGGING, ABANDONMENT, AND RECLAMATION

ECMC Financial Assurance

The Operator has provided or will provide Financial Assurance to the ECMC for this Well.

Surety ID Number (if applicable): 20170115

Federal Financial Assurance

In checking this box, the Operator certifies that it has provided or will provide at least this amount of Financial Assurance to the federal government for this Well. (Per Rule702.a.)

Amount of Federal Financial Assurance \$ _____

WELL LOCATION INFORMATION

Surface Location

QtrQtr: SENE Sec: 11 Twp: 5N Rng: 68W Meridian: 6

Footage at Surface: 2284 Feet FNL 489 Feet FEL

Latitude: 40.415440 Longitude: -104.965940

GPS Data: GPS Quality Value: 1.7 Type of GPS Quality Value: PDOP Date of Measurement: 06/10/2022

Ground Elevation: 4980

Field Name: WATTENBERG Field Number: 90750

Well Plan: is Directional Horizontal (highly deviated) Vertical

If Well plan is Directional or Horizontal attach Deviated Drilling Plan and Directional Data.

Subsurface Locations

Top of Productive Zone (TPZ)

Sec: 11 Twp: 5N Rng: 68W Footage at TPZ: 2500 FSL 750 FEL

Measured Depth of TPZ: 7602 True Vertical Depth of TPZ: 7254 FNL/FSL FEL/FWL

Base of Productive Zone (BPZ)

Sec: 10 Twp: 5N Rng: 68W Footage at BPZ: 2498 FSL 1700 FWL
Measured Depth of BPZ: 15602 True Vertical Depth of BPZ: 7254 FNL/FSL FEL/FWL

Bottom Hole Location (BHL)

Sec: 10 Twp: 5N Rng: 68W Footage at BHL: 2498 FSL 1700 FWL
FNL/FSL FEL/FWL

LOCAL GOVERNMENT PERMITTING INFORMATION

County: LARIMER Municipality: N/A

Is the Surface Location of this Well in an area designated as one of State interest and subject to the requirements of § 24-65.1-108 C.R.S.? Yes

Per § 34-60-106(1)(f)(I)(A) C.R.S., the following questions pertain to the Relevant Local Government approval of the siting of the proposed Oil and Gas Location.

SB 19-181 provides that when "applying for a permit to drill," operators must include proof that they sought a local government siting permit and the disposition of that permit application, or that the local government does not have siting regulations. § 34-60-106(1)(f)(I)(A) C.R.S.

Does the Relevant Local Government regulate the siting of Oil and Gas Locations, with respect to this Location? [X] Yes [] No

[X] If yes, in checking this box, I hereby certify that an application has been filed with the local government with jurisdiction to approve the siting of the proposed oil and gas location.

The disposition of the application filed with the Relevant Local Government is: Approved Date of Final Disposition: 08/25/2023

Comments: Oil and Gas Development Permit PZ#22-00181 Approved 8/25/2023

SURFACE AND MINERAL OWNERSHIP AT WELL'S OIL & GAS LOCATION

Surface Owner of the land at this Well's Oil and Gas Location: [X] Fee [] State [] Federal [] Indian

Mineral Owner beneath this Well's Oil and Gas Location: [X] Fee [] State [] Federal [] Indian

Surface Owner Protection Bond (if applicable): Surety ID Number (if applicable):

MINERALS DEVELOPED BY WELL

The ownership of all the minerals that will be developed by this Well is (check all that apply):

- [X] Fee
- [] State
- [] Federal
- [] Indian
- [] N/A

LEASE INFORMATION

Using standard QtrQtr, Section, Township, Range format describe one entire mineral lease as follows:

* If this Well is within a unit, describe a lease that will be developed by the Well.

* If this Well is not subject to a unit, describe the lease that will be produced by the Well.

(Attach a Lease Map or Lease Description or Lease if necessary.)

T5NR68W Sec 2: SW/4, Sec 3: E/2SW, SE/4 and other lands for a total of 1182 acres.

Total Acres in Described Lease: 1182 Described Mineral Lease is: Fee State Federal Indian

Federal or State Lease # _____

SAFETY SETBACK INFORMATION

Distance from Well to nearest:

Building: 1033 Feet
Building Unit: 1136 Feet
Public Road: 489 Feet
Above Ground Utility: 385 Feet
Railroad: 2842 Feet
Property Line: 365 Feet

INSTRUCTIONS:

- Specify all distances per Rule 308.b.(1).
- Enter 5280 for distance greater than 1 mile.
- Building - nearest building of any type. If nearest Building is a Building Unit, enter same distance for both.
- Building Unit – as defined in 100 Series Rules.

OBJECTIVE FORMATIONS

Objective Formation(s)	Formation Code	Spacing Order Number(s)	Unit Acreage Assigned to Well	Unit Configuration (N/2, SE/4, etc.)
CODELL	CODL	407-3546	1685	T5N, R68W, Section 2: S $\frac{1}{2}$; Section 3: E $\frac{1}{2}$ SW $\frac{1}{4}$, SE $\frac{1}{4}$; Section 10: E $\frac{1}{2}$ W $\frac{1}{2}$, E $\frac{1}{2}$; Section 11: All

Federal or State Unit Name (if appl): _____ Unit Number: _____

SUBSURFACE MINERAL SETBACKS

Enter 5280 for distance greater than 1 mile.

Is this Well within a unit? Yes

If YES:

Enter the minimum distance from the Completed Zone of this Well to the Unit Boundary: 356 Feet

Enter the minimum distance from the Completed Zone of this Well to the Completed Zone of an offset Well within the same unit permitted or completed in the same formation: 923 Feet

If NO:

Enter the minimum distance from the Completed Zone of this Well to the Lease Line of the described lease: _____ Feet

Enter the minimum distance from the Completed Zone of this Well to the Completed Zone of an offset Well producing from the same lease and permitted or completed in the same formation: _____ Feet

Exception Location

If this Well requires the approval of a Rule 401.c Exception Location, enter the Rule or spacing order number and attach the Exception Location Request and Waivers. _____

SPACING & FORMATIONS COMMENTS

DRILLING PROGRAM

Proposed Total Measured Depth: 15602 Feet TVD at Proposed Total Measured Depth 7254 Feet

Distance from the proposed wellbore to nearest existing or proposed wellbore belonging to another operator, including plugged wells:
 Enter distance if less than or equal to 1,500 feet: 150 Feet No well belonging to another operator within 1,500 feet

Will a closed-loop drilling system be used? Yes

Is H₂S gas reasonably expected to be encountered during drilling operations at concentrations greater than or equal to 100 ppm? No If yes, attach an H₂S Drilling Plan unless a plan was already submitted with the Form 2A per Rule 304.c.(10).

Will there be hydraulic fracture treatment at a depth less than 2,000 feet in this well? No

Will salt sections be encountered during drilling? No

Will salt based (>15,000 ppm Cl) drilling fluids be used? No

Will oil based drilling fluids be used? Yes

BOP Equipment Type: Annular Preventor Double Ram Rotating Head None

Beneficial reuse or land application plan submitted? No

Reuse Facility ID: _____ or Document Number: _____

CASING PROGRAM

Casing Type	Size of Hole	Size of Casing	Grade	Wt/Ft	Csg/Liner Top	Setting Depth	Sacks Cmt	Cmt Btm	Cmt Top
CONDUCTOR	26	16	N/A	37	0	80	50	80	0
SURF	13+1/2	9+5/8	J55	36	0	1900	787	1900	0
1ST	8+1/2	5+1/2	HCP110	20	0	15602	1654	15602	

Conductor Casing is NOT planned

POTENTIAL FLOW AND CONFINING FORMATIONS

Zone Type	Formation /Hazard	Top M.D.	Top T.V.D.	Bottom M.D.	Bottom T.V.D.	TDS (mg/L)	Data Source	Comment
Groundwater	Upper Pierre	534	534	1035	1034	0-500	DWR	
Confining Layer	Pierre	1035	1034	3533	3524			
Hydrocarbon	Parkman	3533	3524	4130	4119			
Hydrocarbon	Sussex	4130	4119	4580	4568			
Hydrocarbon	Shannon	4580	4568	6874	6852			
Confining Layer	Sharon Springs	6874	6852	6939	6913			
Hydrocarbon	Niobrara	6939	6913	7404	7220			
Hydrocarbon	Fort Hays	7404	7220	7496	7244			
Hydrocarbon	Codell	7496	7244	15602	7254			Bottom TVD is bottom of the well and not bottom of the formation; the formation is not planned to be exited.

OPERATOR COMMENTS AND SUBMITTAL

Comments

CONDITIONS OF APPROVAL, IF ANY LIST

All representations, stipulations and conditions of approval stated in the Form 2A for this location shall constitute representations, stipulations and conditions of approval for this Form 2 Permit-to-Drill and are enforceable to the same extent as all other representations, stipulations and conditions of approval stated in this Permit-to-Drill.

<u>COA Type</u>	<u>Description</u>
Drilling/Completion Operations	Operator will log two (2) additional wells during the first rig occupation with open-hole resistivity log with gamma-ray log from the kick-off point into the surface casing for the stratigraphically deepest wells for a total of three wells logged.
Drilling/Completion Operations	1) Submit Form 42 electronically to ECMC 2 business days prior to MIRU (spud notice) for the first well activity with a rig on the pad and provide 2 business day spud notice via Form 42 for all subsequent wells drilled on the pad. 2) Comply with Rule 408.j. and provide cement coverage from TD to a minimum of 500' above Niobrara. Verify coverage with a cement bond log.
Drilling/Completion Operations	Per COGCC Order 1-232, Bradenhead tests shall be performed according to the following schedule and Form 17 submitted within 10 days of each test: 1) Within 60 days of rig release, prior to stimulation. If any pressure greater than 200 psi is observed or if there is continuous flow, Operator must contact ECMC engineering for approval prior to stimulation. 2) If a delayed completion, a second test is required between 6-9 months after rig release and must be conducted prior to stimulation. If any pressure greater than 200 psi is observed or if there is continuous flow, Operator must contact ECMC engineering for approval prior to stimulation. 3) A post-production test within 60 days after first sales, as reported on the Form 10, Certificate of Clearance.
3 COAs	

Best Management Practices

<u>No</u>	<u>BMP/COA Type</u>	<u>Description</u>
1	Drilling/Completion Operations	Blowout Prevention Equipment ("BOPE"): A double ram annular preventer will be used during drilling.
2	Drilling/Completion Operations	Anti-collision: Operator will perform an anti-collision evaluation of all active (producing, shut in, or temporarily abandoned) offset wellbores that have the potential of being within 150 feet of a proposed well prior to drilling operations for the proposed well. Notice shall be given to all offset operators prior to drilling.
3	Drilling/Completion Operations	Alternative Logging Program - One of the first wells drilled on the pad will be logged with Open Hole Resistivity Log and Gamma Ray Log from the kick-off point to into the surface casing. All wells on the pad will have a cement bond log with gamma-ray run on production casing (or on intermediate casing if production liner is run) into the surface casing. The horizontal portion of every well will be logged with a measured-while-drilling gamma-ray log. The Form 5, Completion Report, for each well on the pad will list all logs run and have those logs attached. The Form 5 for a well without open-hole logs shall clearly state "Alternative Logging Program - No open-hole logs were run" and shall clearly identify (by API#, well name & number) the well in which open-hole logs were run.

4	Drilling/Completion Operations	When a skid is performed, if a previous well on that pad has completed a full BOPE test within the past 21 days, then the only required BOPE tests are for the BOPE connections that were broken during skid. The purpose of this is to prevent the wear and tear on the choke line and kill line valves. The annular and double rams will be tested as per usual, and all broken connections will also be tested (annular to 70% of rated pressure, all other values and connections will be tested to full rated pressure). Under no circumstances will 21 days be exceeded without completing a full BOPE Test to all connections including all choke and kill line valves. Daily function test/activation of pipe rams are still required in addition to a preventer operator test on each trip.
---	--------------------------------	--

Total: 4 comment(s)

ATTACHMENT LIST

<u>Att Doc Num</u>	<u>Name</u>
403862322	FORM 2 SUBMITTED
403872518	WELL LOCATION PLAT
403872521	OTHER
403872522	DEVIATED DRILLING PLAN
403872691	DIRECTIONAL DATA
403880813	OffsetWellEvaluations Data
403964158	OFFSET WELL EVALUATION

Total Attach: 7 Files

General Comments

<u>User Group</u>	<u>Comment</u>	<u>Comment Date</u>
Permit	With operators concurrence corrected the mineral lease information and added OH Logging COA and distance to unit boundary. Final Review Completed.	10/14/2024
OGLA	The Commission approved OGDG #483259 on November 29, 2023 for the Oil and Gas Location related to this Form 2. OGLA task passed.	08/11/2024

Total: 2 comment(s)