

---

# FLUID LEAK DETECTION PLAN

**Wavetech  Helium, Inc.**

**1 Wavetech Hadachek Trust 21-23**

Sec. 23 T13S R43W (NE/4 NW/4)

Cheyenne County, Colorado

Surface: Fee

Submitted as an accompaniment to the Form 2A Application.

December 7, 2023

Revised: September 11, 2024

## **Wavetech Helium, Inc. Cheyenne County, Colorado**

### **Fluid Leak Detection Plan**

#### **Project Summary:**

Wavetech Helium, Inc.'s ("Wavetech's") proposed 1 Wavetech Hadacheck Trust 21-23 "Location" is in Sec. 23 T13S R43W in Cheyenne County, Colorado. Wavetech plans to drill and test this conventional well which will produce helium containing natural gas, water, and possibly oil. All gas production will go directly to the existing Ladder Creek Pipeline gathering system at the tie-in point in Sec. 22 T13S R43W (NW/4 NW/4). The Ladder Creek Pipeline is operated by Tumbleweed Midstream. The gas processing facility will be on lands outside of this Oil and Gas Development Plan. This well will be drilled, perforated, and tested. The proposed location is fee surface and fee minerals with a total pad disturbance of  $\pm 2.6$  acres. The graded site elevation is expected to be approximately 4,099'. No federal surface or minerals are involved in this project. All operations would be conducted in compliance with all federal, state, and local applicable laws, rules, and regulations.

#### **Plan:**

The contents of this Fluid Leak Detection Plan (Plan) addresses Wavetech's Cheyenne County, Colorado Helium production. This Plan has been prepared in accordance with good engineering practices to prevent and mitigate damage to the environment from a potential leak or spill. This Plan will be in effect during drilling and completions operations and during production operations.

The 1 Wavetech Hadacheck Trust 21-23 Location is proposed in Sec. 23 T13S R43W (NE/4 NW/4). Total disturbance will be approximately 10.2 acres, including wellpad, access road, and pipeline. Working pad surface will be 2.1 acres and 1.0 acres after interim reclamation. Road disturbance is 0.9 acres and 0.5 acres after interim reclamation. Surface and mineral ownership is fee and all access to the site is located on fee surface. The ungraded site elevation will be approximately 4,099' feet. Pad and road construction is anticipated to take one week with drilling two weeks and completion/testing an additional two weeks.

The production facilities will operate 24 hours per day, 7 days per week, and are maintained by a lease operator who regularly inspects the facility and performs daily routine maintenance. The production facilities for production operations will be placed on the wellpad. The natural gas and helium will be processed by Tumbleweed at their processing facility on lands outside of this Oil and Gas Development Plan. Procedures for reporting discharges are provided in the Wavetech Emergency Response Plan which includes contact numbers and spill reporting guidelines.

Wavetech will review and evaluate this Plan at least once every year. As a result of this review, non-technical changes may be made to the Plan to ensure that the document is current and up to date. Such non-technical changes may include updating contact names, phone numbers, or addresses. In addition to non-technical changes, this Plan may be amended to include more effective prevention and control technology if the technology has been field-proven at the time of the review and will significantly reduce the likelihood of a discharge.

## **Best Management Practices**

### **Containment**

The primary spill containment methods are steel secondary containment sufficiently impervious to contain oil or other released fluids. Secondary containments are constructed around all above ground storage tanks (AST). They are enough to hold the shell capacity of the largest tank located within the containment plus sufficient freeboard for precipitation (a 25-year, 24-hour storm event).

Production facilities must have appropriate containment and/or diversionary structures or equipment to prevent a discharge. The entire containment system, including the walls and floor, must be capable of containing fluid and must be constructed so that any discharge from a primary containment system, such as a tank, will not escape the containment system before cleanup occurs.

All ASTs have adequate capacity to assure that they will not overflow if a pumper is delayed in making regularly scheduled rounds.

Above ground piping is restricted to areas directly around the wellhead, separator, flare and ASTs.

Secondary containment and other spill prevention and control methods for facility transfer and loading/unloading areas include the following:

- Load out lines and valves are located within the containment. At those facilities where the load out is not completely within the containment, the piping is sloped back towards the tank or vessel as a spill prevention and control method.
- Drip pans and load line buckets must be adequately sized to contain all discharge, drips and leaks inside the containment system.
- Drip pans and load line buckets must be inspected by the Lease Operators on routine rounds and emptied as needed.

All produced water vacuum truck operators are equipped and trained to contain small leaks, spills or drips that might occur during unloading of ASTs.

In the event of a discharge, the Pumper will use spill cleanup materials and equipment to contain the discharge.

### **Inspections, Tests, and Records**

Wavetech operators are responsible for inspecting assigned facilities as part of their regular work routine. All above ground pipes, valves, and facilities are inspected as a part of the routine operations. The inspections include an assessment of the general condition of flange joints, valve glands and bodies, drip pans, load line buckets, pipeline supports, and other such items. Drainage ditches and other watercourses in and around the facilities are inspected for leaks on a regular basis. All malfunctions, improper operation of equipment, evidence of leakage, spills, stained or discolored soil, etc. are logged and communicated in a timely manner to the supervisor for proper response. Best Management Practices (BMP's) will be:

- Daily audio, visual, and olfactory (AVO) inspection of all above ground facilities.
- Daily production monitoring.
- Audio and visual inspections twice daily during drilling and completion operations.

All flowlines, gathering lines, associated valves and equipment are compatible with the type of production fluids/gases, their potential corrosivity, volume, and pressure, and other conditions expected in the operational environment. The above ground flowlines, gathering lines, and associated appurtenances are inspected on a regular schedule for leaks, corrosion, or other conditions that could lead to a discharge. Corrective actions will be taken and needed repairs will be made for conditions identified during the inspection. Any spills will be promptly removed, or stabilization and remediation actions will be initiated.

Personnel visually inspect the outside of all ASTs routinely for signs of deterioration and maintenance needs. All tanks, flow-through vessels, tank supports, and foundations undergo a visual inspection for integrity and to ensure no pitting or rusting.

Wavetech also conducts, at a minimum, an annual pressure testing of flowlines as per COGCC requirements. Wavetech's standard protocol for pressure testing of flowlines, dump lines, and facility equipment involve the following key steps:

- Isolate flowline at header and install appropriate gauge;
- Pressure flowline using well head pressure, preferably maximum casing pressure and isolate well head;
- Allow pressure to stabilize;
- Record beginning pressure/time on the Facility Pressure Test Report (F.P.T.R.);
- Monitor for 30 minutes;
- At the end of 30 minutes record pressure/time at end of test on F.P.T.R.;
- Any loss of pressure needs immediate action taken (e.g. eliminate isolation points as source, hydro test for final confirmation);
- If flowline fails test, isolate well and turn in work order;
- If flowline tests good, return well back to normal production; and,
- Turn in Facility Pressure Test Report to a supervisor.

Records of Inspection reports are maintained at the Wavetech field office for a period of three years.

Any leak discovered in a flowline or appurtenances is promptly addressed by shutting in the well and isolating the damaged portion of the line. The faulty piece of equipment is then repaired or replaced.

### **Drilling and Completion Operations**

Wavetech will have the following during Drilling Operations.

- All potential pollution sources will have secondary containment.
- Daily inspections and preventive maintenance on the drillsite.
- Spill response, containment, and cleanup.
- Completion of the wells will be single interval perforation and will not require fracture stimulation.

### **Leak Response**

After discovery of a leak, specific steps are taken, including immediate response, reporting, and containment and cleanup. Pumpers will have emergency contact information with them at all times to ensure immediate and appropriate response. Some of the key steps include:

- Account for onsite personnel, assure their safety, and evacuate if a fire, explosion, or exposure hazard exists. Remove all sources of ignition, position fire suppression equipment and alert the local Fire Department if necessary. Shut off pumps and close valves that allow fluids and gases to flow to the segment of the system causing the spill/release.
- Restrict access and alert adjacent property owners/operators as warranted by the incident and make internal notifications. Wavetech's EHS professionals will make external notifications to applicable regulatory agencies.
- As safety allows, on scene personnel will contain the spill, if appropriate, and prevent or divert spilled fluids from approaching structures or draining towards waterways or storm drains.
- Initiate cleanup and waste management activities will be done in conjunction with a Wavetech EHS professional. Wavetech EHS professionals will complete all required written notifications or reports. The EHS professional will conduct a spill assessment and determine any additional cleanup actions as needed.

**Personnel, Training, and Discharge Prevention Measures**

Wavetech's EHS department has been designated as the primary point of contact for discharge prevention and response.

At a minimum, Wavetech field personnel are trained in the following related topics:

- General facility operations;
- Spill control equipment;
- Operation and maintenance of equipment to prevent discharges;
- Containment, vessel, tank and piping inspection and maintenance;
- Spill response, containment and cleanup;
- Company policies on reporting and responding to spills;
- Applicable pollution control laws, rules, and regulations;
- Daily audio, visual, and olfactory (AVO) inspection of all above ground facilities.
- Daily production monitoring.
- Approved Instrument Monitoring Method (AIMM) Inspections with "FLIR" technology Camera on a bi-monthly basis and at other times as needed and appropriate.
- Audio and visual inspections twice daily during drilling and completion operations.