

FORM
2
Rev
05/22

State of Colorado Energy & Carbon Management Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203
Phone: (303) 894-2100 Fax: (303) 894-2109



Document Number:

403930708

Date Received:

09/30/2024

APPLICATION FOR PERMIT TO

Drill Deepen Re-enter Recomplete and Operate

Amend

TYPE OF WELL OIL GAS COALBED OTHER: _____

Refile

ZONE TYPE SINGLE ZONE MULTIPLE ZONES COMMINGLE ZONES

Sidetrack

Well Name: KBL 1830 Well Number: 18H
Name of Operator: VERDAD RESOURCES LLC ECMC Operator Number: 10651
Address: 1125 17TH STREET SUITE 550
City: DENVER State: CO Zip: 80202
Contact Name: Allison Schieber Phone: (720)8456909 Fax: ()
Email: regulatory@verdadresources.com

FINANCIAL ASSURANCE FOR PLUGGING, ABANDONMENT, AND RECLAMATION

ECMC Financial Assurance

The Operator has provided or will provide Financial Assurance to the ECMC for this Well.

Surety ID Number (if applicable): 2030030

Federal Financial Assurance

In checking this box, the Operator certifies that it has provided or will provide at least this amount of Financial Assurance to the federal government for this Well. (Per Rule702.a.)

Amount of Federal Financial Assurance \$ _____

WELL LOCATION INFORMATION

Surface Location

QtrQtr: NWSE Sec: 19 Twp: 2N Rng: 63W Meridian: 6

Footage at Surface: 1805 Feet FSL 1931 Feet FEL

Latitude: 40.121603 Longitude: -104.477747

GPS Data: GPS Quality Value: 2.2 Type of GPS Quality Value: PDOP Date of Measurement: 09/04/2024

Ground Elevation: 4861

Field Name: WATTENBERG Field Number: 90750

Well Plan: is Directional Horizontal (highly deviated) Vertical

If Well plan is Directional or Horizontal attach Deviated Drilling Plan and Directional Data.

Subsurface Locations

Top of Productive Zone (TPZ)

Sec: 18 Twp: 2N Rng: 63W Footage at TPZ: 2170 FSL 1229 FEL

Measured Depth of TPZ: 10441 True Vertical Depth of TPZ: 6736 FNL/FSL FEL/FWL

Base of Productive Zone (BPZ)

Sec: 30 Twp: 2N Rng: 63W Footage at BPZ: 460 FSL 1200 FEL

Measured Depth of BPZ: 22724 True Vertical Depth of BPZ: 6736 FNL/FSL FEL/FWL

Bottom Hole Location (BHL)

Sec: 30 Twp: 2N Rng: 63W Footage at BHL: 370 FSL 1199 FEL

FNL/FSL FEL/FWL

LOCAL GOVERNMENT PERMITTING INFORMATION

County: WELD Municipality: N/A

Is the Surface Location of this Well in an area designated as one of State interest and subject to the requirements of § 24-65.1-108 C.R.S.? Yes

Per § 34-60-106(1)(f)(I)(A) C.R.S., the following questions pertain to the Relevant Local Government approval of the siting of the proposed Oil and Gas Location.

SB 19-181 provides that when "applying for a permit to drill," operators must include proof that they sought a local government siting permit and the disposition of that permit application, or that the local government does not have siting regulations. § 34-60-106(1)(f)(I)(A) C.R.S.

Does the Relevant Local Government regulate the siting of Oil and Gas Locations, with respect to this Location? Yes No

If yes, in checking this box, I hereby certify that an application has been filed with the local government with jurisdiction to approve the siting of the proposed oil and gas location.

The disposition of the application filed with the Relevant Local Government is: Approved Date of Final Disposition: 11/14/2019

Comments: 1041WOGLA19-0009

SURFACE AND MINERAL OWNERSHIP AT WELL'S OIL & GAS LOCATION

Surface Owner of the land at this Well's Oil and Gas Location: Fee State Federal Indian

Mineral Owner beneath this Well's Oil and Gas Location: Fee State Federal Indian

Surface Owner Protection Bond (if applicable): _____ Surety ID Number (if applicable): _____

MINERALS DEVELOPED BY WELL

The ownership of all the minerals that will be developed by this Well is (check all that apply):

- Fee
- State
- Federal
- Indian
- N/A

LEASE INFORMATION

Using standard QtrQtr, Section, Township, Range format describe one entire mineral lease as follows:

- * If this Well is within a unit, describe a lease that will be developed by the Well.
 - * If this Well is not subject to a unit, describe the lease that will be produced by the Well.
- (Attach a Lease Map or Lease Description or Lease if necessary.)

T2N R63W: E2, E2W2 Section 18
 Part of the E2 lying South of the Railroad ROW Section 19
 W2 Section 20

Total Acres in Described Lease: 1308 Described Mineral Lease is: Fee State Federal Indian
 Federal or State Lease # _____

SAFETY SETBACK INFORMATION

Distance from Well to nearest:

Building: 1639 Feet
 Building Unit: 1691 Feet
 Public Road: 950 Feet
 Above Ground Utility: 1309 Feet
 Railroad: 821 Feet
 Property Line: 717 Feet

INSTRUCTIONS:

- Specify all distances per Rule 308.b.(1).
- Enter 5280 for distance greater than 1 mile.
- Building - nearest building of any type. If nearest Building is a Building Unit, enter same distance for both.
- Building Unit – as defined in 100 Series Rules.

OBJECTIVE FORMATIONS

Objective Formation(s)	Formation Code	Spacing Order Number(s)	Unit Acreage Assigned to Well	Unit Configuration (N/2, SE/4, etc.)
NIOBRARA	NBRR	407-2326	1600	T2N R63W Section 18 S2 Section 19 ALL Section 30 ALL

Federal or State Unit Name (if appl): _____ Unit Number: _____

SUBSURFACE MINERAL SETBACKS

Enter 5280 for distance greater than 1 mile.

Is this Well within a unit? Yes

If YES:

Enter the minimum distance from the Completed Zone of this Well to the Unit Boundary: 460 Feet

Enter the minimum distance from the Completed Zone of this Well to the Completed Zone of an offset Well within the same unit permitted or completed in the same formation: 720 Feet

If NO:

Enter the minimum distance from the Completed Zone of this Well to the Lease Line of the described lease: _____ Feet

Enter the minimum distance from the Completed Zone of this Well to the Completed Zone of an offset Well producing from the same lease and permitted or completed in the same formation: _____ Feet

Exception Location

If this Well requires the approval of a Rule 401.c Exception Location, enter the Rule or spacing order number and attach the Exception Location Request and Waivers. _____

SPACING & FORMATIONS COMMENTS

T2N R63W Section 18 S2 Section 19 ALL Section 30 ALL

DRILLING PROGRAM

Proposed Total Measured Depth: 22814 Feet TVD at Proposed Total Measured Depth 6736 Feet

Distance from the proposed wellbore to nearest existing or proposed wellbore belonging to another operator, including plugged wells:

Enter distance if less than or equal to 1,500 feet: 541 Feet No well belonging to another operator within 1,500 feet

Will a closed-loop drilling system be used? Yes

Is H₂S gas reasonably expected to be encountered during drilling operations at concentrations greater than or equal to 100 ppm? No If yes, attach an H₂S Drilling Plan unless a plan was already submitted with the Form 2A per Rule 304.c.(10).

Will there be hydraulic fracture treatment at a depth less than 2,000 feet in this well? No

Will salt sections be encountered during drilling? No

Will salt based (>15,000 ppm Cl) drilling fluids be used? No

Will oil based drilling fluids be used? Yes

BOP Equipment Type: Annular Preventor Double Ram Rotating Head None

Beneficial reuse or land application plan submitted? No

Reuse Facility ID: _____ or Document Number: _____

CASING PROGRAM

Casing Type	Size of Hole	Size of Casing	Grade	Wt/Ft	Csg/Liner Top	Setting Depth	Sacks Cmt	Cmt Btm	Cmt Top
CONDUCTOR	24	16	astm	65	0	80	92	80	0
SURF	13+1/2	9+5/8	j55	36	0	1907	518	1907	0
1ST	8+1/2	5+1/2	p110	20	0	22814	2778	22814	0

Conductor Casing is NOT planned

POTENTIAL FLOW AND CONFINING FORMATIONS

Zone Type	Formation /Hazard	Top M.D.	Top T.V.D.	Bottom M.D.	Bottom T.V.D.	TDS (mg/L)	Data Source	Comment
Groundwater	ARAPAHOE	0	0	185	185	1001-10000	USGS	USGS-400753104251501 (3400mg/L)
Groundwater	FOX HILLS	185	185	732	730	501-1000	USGS	USGS-400539104270301 (539 mg/L)
Confining Layer	PIERRE	732	730	1284	1262			
Groundwater	UPPER PIERRE POROSITY	1284	1262	1830	1751	1001-10000	Other	CO DNR Report Project Number 2141
Confining Layer	PIERRE	1830	1751	5287	3758			
Hydrocarbon	PARKMAN	5287	3758	5739	3986			
Confining Layer	PIERRE	5739	3986	5920	4077			
Hydrocarbon	SUSSEX	5920	4077	6768	4505			
Confining Layer	PIERRE	6768	4505	7617	4933			
Hydrocarbon	SHANNON	7617	4933	8224	5239			
Confining Layer	PIERRE	8224	5239	9904	6546			
Hydrocarbon	SHARON SPRINGS	9904	6546	9950	6576			
Hydrocarbon	NIOBRARA	9950	6576	22814	6736			

OPERATOR COMMENTS AND SUBMITTAL

Comments

This location has been built. This well is a refile of KBL 1918 06H API 05-123-50885. The name, SHL,TPZ, BPZ, BHL, drilling information, casing information, and associated attachments have been changed. The distance from the proposed well to the nearest portion of offset wellbore in the same formation is the KBL 1830 19H measured in 2D. The distance from the proposed well to the nearest well belonging to another operator is Berglund Meyers 42-19 (API 05-123-14249) operated by Simmons Energy DA status, measured in 3D using anti collision report attached as other.

This well has a bottom-hole location beyond the unit boundary setback. The bottom of the completed interval will be within the unit boundary setback at 460' FSL and 1200' FEL of Section 30 2N 63W. The wellbore beyond the unit boundary setback will be physically isolated and will not be completed.

This application is in a Comprehensive Area Plan No CAP #: _____

Oil and Gas Development Plan Name _____ OGDID #: _____


Location ID: 471229

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: _____ Print Name: Allison Schieber

Title: regulatory Date: 9/30/2024 Email: regulatory@verdadresources.c

Operator must have a valid water right or permit allowing for industrial use or purchased water from a seller that has a valid water right or permit allowing for industrial use, otherwise an application for a change in type of use is required under Colorado law. ~~Operator must also use the water in the location set forth in the water right decree or well permit, otherwise an application for a change in place of use is required under Colorado law. Section 37-92-103(5), C.R.S. (2019).~~ Based on the information provided herein, this Application for Permit-to-Drill complies with ECMC Rules, applicable orders, and SB 19-181 and is hereby approved.

ECMC Approved: 

Director of ECMC

Date: 11/13/2024

Expiration Date: 11/12/2027

API NUMBER 05 123 50885 00

CONDITIONS OF APPROVAL, IF ANY LIST

All representations, stipulations and conditions of approval stated in the Form 2A for this location shall constitute representations, stipulations and conditions of approval for this Form 2 Permit-to-Drill and are enforceable to the same extent as all other representations, stipulations and conditions of approval stated in this Permit-to-Drill.

COA Type	Description
Drilling/Completion Operations	Operator will ensure the wellbore beyond the unit boundary setback is physically isolated and is not completed. In the Operator Comments on the Form 5A the operator will (1) report the footages from the section lines of the bottom of the completed interval (2) describe how the wellbore beyond the unit boundary setback is physically is physically isolated and (3) certify that none of the wellbore beyond the setback was completed.
	This Location and its associated Form 2A materials was fully evaluated during the review of this APD in accordance with the current Rules. This APD complies with all Colorado ECMC Rules and Staff does not anticipate any significant potential direct adverse impacts to public health, safety, welfare, the environment, and wildlife resources. OGLA task passed.
Drilling/Completion Operations	Per Order 1-232, Bradenhead tests shall be performed according to the following schedule and Form 17 submitted within 10 days of each test: 1) Within 60 days of rig release, prior to stimulation. If any pressure greater than 200 psi, must contact ECMC engineer prior to stimulation. 2) If a delayed completion, 6 months after rig release and prior to stimulation. If any pressure greater than 200 psi, must contact ECMC engineer prior to stimulation. 3) A post-production test within 60 days after first sales, as reported on the Form 10, Certificate of Clearance.
Drilling/Completion Operations	1) Submit Form 42 electronically to ECMC 2 business days prior to MIRU (Spud Notice), for the first well/activity on the pad and provide 2 business days spud notice for all subsequent wells drilled on the pad. 2) Comply with Rule 408.j and provide cement coverage from the end of production casing to a minimum of 500' above Niobrara. Verify coverage with cement bond log. 3) Oil-based drilling fluid is to be used only after all aquifers are covered.
Drilling/Completion Operations	Operator acknowledges the proximity of the listed non-producing well(s). Operator agrees to provide mitigation Option 3 (per the DJ Basin Horizontal Offset Policy) to mitigate the situation, ensure all applicable documentation is submitted, and submit Form 42(s) "OFFSET MITIGATION COMPLETED" for the remediated well(s), referencing the API Number of the proposed horizontal wells stating what appropriate mitigation occurred and that it has been completed, prior to the hydraulic stimulation of the proposed wells. Berglund Myers 1 (API NO 123-11868)

5 COAs

Best Management Practices

<u>No</u>	<u>BMP/COA Type</u>	<u>Description</u>
1	Drilling/Completion Operations	Alternative Logging Program - One of the first wells drilled on the pad will be logged with Open Hole Resistivity Log and Gamma Ray Log from the kick-off point to into the surface casing. All wells on the pad will have a cement bond log with gamma-ray run on production casing (or on intermediate casing if production liner is run) into the surface casing. The horizontal portion of every well will be logged with a Measured while drilling gamma-ray log. The form 5, Completion Report, for each well on the pad will list all logs run and have those logs attached. The Form 5 for a well without Open hole logs shall clearly state "Alternative Logging Program - No open-hole logs were run" and shall clearly identify (by API#, well name & number) the well in which Open hole logs were run.
2	Drilling/Completion Operations	Upon initial rig-up and at least once every thirty (30) days during drilling operations thereafter, pressure testing of the casing string and each component of the blowout prevention equipment including flange connections shall be performed to seventy percent (70%) of working pressure or seventy percent (70%) of the internal yield of casing, whichever is less. Pressure testing shall be conducted and the documented results shall be retained by the operator for inspection by the Director for a period of one (1) year. Activation of the pipe rams for function testing shall be conducted on a daily basis when practicable.
3	Drilling/Completion Operations	Operator will perform anti-collision evaluation of all active (producing, shut-in, of temporarily abandoned) offset wellbores that have the potential of being within 150' feet of the proposed well prior to drilling operations. Notice shall be given to all offset operators prior to drilling.

Total: 3 comment(s)

ATTACHMENT LIST

<u>Att Doc Num</u>	<u>Name</u>
403930708	FORM 2 SUBMITTED
403940167	OffsetWellEvaluations Data
403940196	DEVIATED DRILLING PLAN
403940198	OTHER
403940199	WELL LOCATION PLAT
403940206	DIRECTIONAL DATA
403993949	OFFSET WELL EVALUATION

Total Attach: 7 Files

General Comments

<u>User Group</u>	<u>Comment</u>	<u>Comment Date</u>
Permit	Final Review Completed.	10/30/2024
Permit	Email received and made the following changes with concurrence from operator: 1) Spacing Order edited to 407-2326. 2) COA added: Operator will not complete beyond the unit boundary setback at the BHL. 3) Comment under submit tab added regarding BHL beyond unit boundary setback. Permit Review Complete	10/28/2024
Permit	Email sent to operator regarding: 1) Order listed is for pooling not spacing 2) COA for BHL beyond the unit boundary setback 3) Comment on submit tab regarding BHL beyond the unit boundary setback.	10/28/2024
Engineer	Offset Wells Evaluated.	10/04/2024

Total: 4 comment(s)