



STATE OF COLORADO
GAS CONSERVATION COMMISSION
DEPARTMENT OF NATURAL RESOURCES

10308997

RECEIVED

SEP 29 1982

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

5. LEASE DESIGNATION & SERIAL NO.

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 12, T1N-R93W

12. COUNTY

Rio Blanco

13. STATE

Colorado

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Dry Hole

2. NAME OF OPERATOR

Coors Energy Company

(303) 278-7030

3. ADDRESS OF OPERATOR

PO Box 467, Golden, Colorado 80401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

See also space 17 below.)

At surface

1119'FWL, 1410'FSL

At proposed prod. zone

NWSEW

14. PERMIT NO.

82 1383

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6648'GL

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL.

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON

CHANGE PLANS.

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated dates of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

18. Date of work

9/23/82

* Must be accompanied by a cement verification report.

Top of Frontier:

3200'

Top of Niobrara:

2200'

8/31/82 Spudded well

9/1 to

9/9/82 Drilled 12-1/4" hole to 691', set 13-3/8" casing at 64 feet, cemented with 100 sacks of cement.

9/10 to

9/11/82 Drilled 12 1/4" hole to 783', set 8-5/8" casing at 778', cemented w/550 sacks cement.

9/12 to

9/21/82 Drilled 7-7/8" hole to 3507'.

9/22/82 Logged well, ran FDL-CNL, DIL-LL8 from 3507-778'.

9/23/82 P&A well. Spotted 50 sks cement from 3250-3150', spotted 50 sks from 2250-2150', spotted 20 sks 791-741'. Spotted 10 sks on top. Will install dry hole marker on top of hole in the near future. See attached P&A cement verification report.

Note: Well was P&A as per instructions from Mr. Wayne Rogers of the OGCC 9/19/82.

19. I hereby certify that the foregoing is true and correct

SIGNED

R. L. Martin

TITLE V.P. Oil & Gas Production

DATE

9-27-82

(This space for Federal or State office use)

DIRECTOR

APPROVED BY

TITLE

O & G Cons. Comm.

DATE

OCT 7 1982

CONDITIONS OF APPROVAL, IF ANY:



00038438