Company: Fram Operating LLC
Well: Eberly 23-4 (OWP)
Field:
County: Moffat
State: Colorado
Rig: Ensign 115
Job Number: 24-0000
Run Number: 1
Run Date: 7/1/2024
Operator Witness:
Service Supervisor: Jeff Rose
Permanent Datum: Ground Level
Elevation: 6,999.00 ft
Log Measured From: Ground Level
Drilling Measured From: Ground Level
Depth Driller: 7,381.00 ft
Depth Logger: 7,381.00 ft
Bottom Logged Interval: 7,381.00 ft
Top Logged Interval: 6,900.00 ft
Casing Driller Size: 8.625 in @ 1,000.00 ft
Casing Logger Size: 8.625 in @ 1,000.00 ft
Bit Size: 7.875 in
Type Fluid in Hole: Water Based Mud
Density: 8.40 lb/gal
Viscosity: 28 s/qt
PH: 9.0
Fluid Loss: 8.0 cc
Source of Sample: Flowline
Rm @ Measured Temp: 0.000 ohm-m @ 0.00 °F
Rmf @ Measured Temp: 0.000 ohm-m @ 0.00 °F
Rmc @ Measured Temp: 0.000 ohm-m @ 0.00 °F
Source of Rmf and Rmc: Measured
Rm @ BHT: 0.000 ohm-m @ 0.00 °F
Time Since Circulation: 0.00 hr
Max Recorded Temperature: 0.00 °F
Equipment Number: 1
Location: Craig
Recorded By: Jeff Rose
Witnessed By:
Logging Disclaimer
All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These conditions may not be modified by any representative except in writing signed over the corporate seal of Operator.
Comments
Log ran as per customer request
Log correlated to 'E' @ Ground Level
***** Thank You For Using The Wireline Group *****
Main Pass 5" = 100' (0 PSI)
Repeat Pass 5" = 100' (0 PSI)
Company: Fram Operating LLC
Well: Eberly 23-4 (OWP)
Field:
County: Moffat
State: Colorado
Rig: Ensign 115
Job Number: 24-0000
Run Number: 1
Run Date: 7/1/2024
Operator Witness:
Service Supervisor: Jeff Rose
Permanent Datum: Ground Level
Elevation: 6,999.00 ft
Log Measured From: Ground Level
Drilling Measured From: Ground Level
Depth Driller: 7,381.00 ft
Depth Logger: 7,381.00 ft
Bottom Logged Interval: 7,381.00 ft
Top Logged Interval: 6,900.00 ft
Casing Driller Size: 8.625 in @ 1,000.00 ft
Casing Logger Size: 8.625 in @ 1,000.00 ft
Bit Size: 7.875 in
Type Fluid in Hole: Water Based Mud
Density: 8.40 lb/gal
Viscosity: 28 s/qt
PH: 9.0
Fluid Loss: 8.0 cc
Source of Sample: Flowline
Rm @ Measured Temp: 0.000 ohm-m @ 0.00 °F
Rmf @ Measured Temp: 0.000 ohm-m @ 0.00 °F
Rmc @ Measured Temp: 0.000 ohm-m @ 0.00 °F
Source of Rmf and Rmc: Measured
Rm @ BHT: 0.000 ohm-m @ 0.00 °F
Time Since Circulation: 0.00 hr
Max Recorded Temperature: 0.00 °F
Equipment Number: 1
Location: Craig
Recorded By: Jeff Rose
Witnessed By:
Gamma Ray Calibration Report
Serial Number: 24-0000
Detector: 4.5" NaI
Calibrator Value: 24.5
Background Reading: 24.5
Calibration Date: 2/8/2024
Gamma Ray Calibration Report
Serial Number: 24-0000
Detector: 4.5" NaI
Calibrator Value: 24.5
Background Reading: 24.5
Calibration Date: 2/8/2024
Repeatability Log Calibration Report
Serial Number: 24-0000
Detector: Natural Gamma
Calibration Gamma Diameter: 4.500 in
Calibration Length: 20.00 ft
Neutron Calibration, performed in Fall Bay, ID 10-CT-36-2024
Run 1a
Zero Cal Zero Cal
Air 0.313 0.302 0.250 51.196 48.194 1.190
Water 0.313 0.302 0.250 47.196 45.191 1.190
SS 0.313 0.302 0.250 100.000 100.000 1.190
LS 0.313 0.302 0.250 100.000 100.000 1.190
DOL 0.313 0.302 0.250 100.000 100.000 1.190
ANH 0.313 0.302 0.250 100.000 100.000 1.190
SAL 0.313 0.302 0.250 100.000 100.000 1.190
Limestone Porosity 0.313 0.302 0.250 100.000 100.000 1.190
Sandstone Porosity 0.313 0.302 0.250 100.000 100.000 1.190
Dolomite Porosity 0.313 0.302 0.250 100.000 100.000 1.190
Anhydrite Porosity 0.313 0.302 0.250 100.000 100.000 1.190
Salt Porosity 0.313 0.302 0.250 100.000 100.000 1.190
Calibration Report
Serial Number: 24-0000
Detector: 4.5" NaI
Calibrator Value: 24.5
Background Reading: 24.5
Calibration Date: 2/8/2024
Internal Reference Calibration, performed Not Performed
Run 1a
Zero Cal Zero Cal
CAL 0.000 0.000 0.000 4.750 4.750 0.000
Air Zero Calibration, performed Fall Bay, ID 10-CT-36-2024
Run 1a
Zero Cal Zero Cal
A 0.000 0.000 0.000 0.000
B 0.000 0.000 0.000 0.000
C 0.000 0.000 0.000 0.000
D 0.000 0.000 0.000 0.000
E 0.000 0.000 0.000 0.000
F 0.000 0.000 0.000 0.000
G 0.000 0.000 0.000 0.000
H 0.000 0.000 0.000 0.000
Instrument Calibration Report
Performed: Thu Jul 25 15:46:49 2024
Low Read High Read Low Ref High Ref
K Autocalibrate 427.01 804.46 0.00 1.00 gps
K Autocalibrate 456.00 864.00 0.00 1.00 gps
K Autocalibrate 1.47 888.18 0.00 1.00 gps
Sensor Offset (ft) Schematic Description Length (ft) O.D. (in) Weight (lb)
Cable Head, TTC 1.00 1.69 11.00
HNGR 6.42
WTBR 6.42
WTBR 6.42
WTBR 6.42
WTBR 6.42
WTBR 6.42
WTBR 6.42
TMP_ACCUC 6.42
TMP_ACCUC 6.42
WTBR 6.42
DEV_SAT-Mag 1.00
Centralizer, 7 7/8" Blade, 8 1/2" OD, Spring Bow Type Centralizer 0.50 3.75 10.00
Natural Gamma Flex Sonde (GFXT-A) 5.00, Natural Gamma Flex Sonde (GFXT-A) 5.00 10.00 3.63 110.00
Centralizer, 7 7/8" Blade, 8 1/2" OD, Spring Bow Type Centralizer 0.50 3.75 10.00
Cable Head, TTC 1.00 1.69 11.00