

Speed Goat Fed 3432-06H



DESCRIPTION	DEPTH	WELLBORE	DRILLING DEPTHS																																																												
Date 1/22/2025																																																															
WELL: Speed Goat Fed 3432-06H LOCATION: NENE 34 9N 58W 6 311 FNL 961 FEL County: Weld FORMATION: Nio C API #: 05-123-52503 Field: DJ Horizontal NBRR-FH-CODL-CL Spud: 04/14/24 Current Status: Producing Well Type Horizontal Well Length XXRL																																																															
Casing and Tubular Data																																																															
			<table border="1"> <thead> <tr> <th>Type</th> <th>Hole Size</th> <th>Pipe Size</th> <th>Grade</th> <th>Weight</th> <th>Pipe Top</th> <th>Setting Dep</th> <th>Sacks Cmt</th> <th>Cmt Btm</th> <th>Cmt Top</th> <th>Slurry Yield</th> <th>Slurry Weight</th> </tr> </thead> <tbody> <tr> <td>Conductor</td> <td>26</td> <td>16</td> <td>ASTM</td> <td>65.0 ppf</td> <td>0'</td> <td>80'</td> <td>92</td> <td>80'</td> <td>0'</td> <td>2. ft3/sack</td> <td>14.0 ppg</td> </tr> <tr> <td>Surface</td> <td>13 1/2</td> <td>9 5/8</td> <td>J55</td> <td>36.0 ppf</td> <td>0'</td> <td>1,560'</td> <td>698</td> <td>1,560'</td> <td>0'</td> <td>1.6 ft3/sack</td> <td>13.9 ppg</td> </tr> <tr> <td>Production Tubing</td> <td>8 1/2</td> <td>5 1/2</td> <td>P110</td> <td>20.0 ppf</td> <td>0'</td> <td>19,963'</td> <td>2,902</td> <td>19,963'</td> <td>78'</td> <td>1.6 ft3/sack</td> <td>13.2 ppg</td> </tr> <tr> <td></td> <td>n/a</td> <td>2 3/8</td> <td>n/a</td> <td>4.6 ppf</td> <td>n/a</td> <td>n/a</td> <td>n/a</td> <td>n/a</td> <td>n/a</td> <td>n/a</td> <td>n/a</td> </tr> </tbody> </table>	Type	Hole Size	Pipe Size	Grade	Weight	Pipe Top	Setting Dep	Sacks Cmt	Cmt Btm	Cmt Top	Slurry Yield	Slurry Weight	Conductor	26	16	ASTM	65.0 ppf	0'	80'	92	80'	0'	2. ft3/sack	14.0 ppg	Surface	13 1/2	9 5/8	J55	36.0 ppf	0'	1,560'	698	1,560'	0'	1.6 ft3/sack	13.9 ppg	Production Tubing	8 1/2	5 1/2	P110	20.0 ppf	0'	19,963'	2,902	19,963'	78'	1.6 ft3/sack	13.2 ppg		n/a	2 3/8	n/a	4.6 ppf	n/a	n/a	n/a	n/a	n/a	n/a	n/a
Type	Hole Size	Pipe Size	Grade	Weight	Pipe Top	Setting Dep	Sacks Cmt	Cmt Btm	Cmt Top	Slurry Yield	Slurry Weight																																																				
Conductor	26	16	ASTM	65.0 ppf	0'	80'	92	80'	0'	2. ft3/sack	14.0 ppg																																																				
Surface	13 1/2	9 5/8	J55	36.0 ppf	0'	1,560'	698	1,560'	0'	1.6 ft3/sack	13.9 ppg																																																				
Production Tubing	8 1/2	5 1/2	P110	20.0 ppf	0'	19,963'	2,902	19,963'	78'	1.6 ft3/sack	13.2 ppg																																																				
	n/a	2 3/8	n/a	4.6 ppf	n/a	n/a	n/a	n/a	n/a	n/a	n/a																																																				
		KOP	6,062'																																																												
Perf Depths																																																															
			7,114' to 19,822'																																																												
Formation Tops																																																															
			Fox Hills 21 ft Niobrara 6,538 ft Codell n/a ft																																																												
Additional Information																																																															
Completion Type Plug & Perf																																																															
Lift Type Flowing																																																															
Last Workover n/a																																																															
Elevation Data																																																															
			GL 4722 feet KB 4743 feet Difference 21 feet																																																												
Tubing BHA																																																															
9-5/8" Surface Casing:	1,560'																																																														
2-3/8" Production Tubing:	n/a	Lateral	7,084'																																																												
PBTD 19915'																																																															
5-1/2" Production Casing :	19,963'	TVD MD	5,825' 19,977'																																																												