

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

C-0103355

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Gov't-Funk

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

Sawbuck

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

8-2N-R58W

12. COUNTY OR PARISH

Morgan

Colorado

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

A. T. Skaer

3. ADDRESS OF OPERATOR

924 Patterson Building, Denver, Colorado 80202

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

C-NE-SE Sec. 8, T2N, Rg. 58W

14. PERMIT NO.

67-193

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

SUBSEQUENT REPORT OF:

REPAIRING WELL


ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Move in Donnelly Casing Pulling Co. rig, dump sand from PBTD of 5950' to 5880' to cover perf. 5903.5' to 5905.5', dump 5 sack cement plug. Fill hole with mud and water, work pipe free; shoot off at free point, which would be approx 5144' (Top Niobrara); fill hole up to 135' from surface; set 15 sack cement plug across bottom surface pipe; fill hole to 20' of surface; set 10 sack cement plug to base of cellar. Weld cap over top surface pipe; clean up location.
Note: M. F. Funk--Surface owner does not want surface marker.

Verbal Approval 7/17/67
by E. R. Haymaker

00105269

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

DATE

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

COLO. OIL & GAS COMM.

*See Instructions on Reverse Side