

Monaco Engineering, Inc.

HYDROCARBON ANALYSIS LOG

COMPANY **KISSINGER PETROLEUM CORPORATION**

WELL **FORD #6-8**

COUNTY **BACA**

STATE **COLORADO**

LOCATION **C SE NW SEC 8 T34S R44W**

ELEVATION **K.B. 4127'**

DATE LOGGED FROM **5/26/78**

TO

DEPTH LOGGED FROM **1700'**

TO

ENGINEER **THOMAS HALLIDAY**

G.L. 4120'

LEGEND

✓✓✓ ANHYDRITE ▨ DOLOMITE ▬ COAL
 XXX ARKOSE ▨ LIMESTONE ▬ SHALE
 AAA CHERT ▬ SANDSTONE ▬

HYDROCARBON GASES

TOTAL GAS FROM CUTTINGS ———
 TOTAL GAS FROM HOT WIRE

CHROMATOGRAPH ANALYSIS

1 - METHANE 3 - PROPANE 4 - BUTANES
 2 - ETHANE 5 - PENTANES

ABBREVIATIONS

NB NEW BIT
 NR NO RETURNS
 CO CIRCULATE OUT
 DST DRILL STEM TEST

REMARKS,

MUD CHARACTERISTICS

WT - VIS - FILT - CK - PH - CL - OIL

DRILLING RATE

MINUTES PER FT.

DEPTH

LITHOLOGY

POISSON'S RATIO

REPLACE PUMP MOTOR - DOWN 16 HRS.

RECEIVED

JUN 12 1978

COLO. OIL & GAS CONS. COMM.

HOLE IN PIPE - TRIP OUT - DOWN 9 HRS.

LAG = 50 MIN.: 8 OZ. CARBIDE / 55 UNITS H.W.

SH GY SL WXY SATNY

SS F-MG CLR-WH CLY FILL ABNT
ANG CSE QTZ

SH GY-DK GY FIS-SLTY SL SDY

SS CLR QTZ CG ANG V UNCONS
WH CLY FILL

CHT TRANSLUC

LS DK GY MICXL
8.9-45-10.2-2-9.0-4800-0%

SH GY-BLK INCR SLTY SL MICA
TR PYR

LS GY SLTY SL SUG TR PP POR

SH GY-BLK AA LMY

LS AA MICXL ARG

LS CHKY WH-GY ARG FRI
SL POR

SH BLK-RED BRN FIS SL WXY CARB
8.8-35-10.0-2-9.0-5200-0%

SH AA CARB

6/7/78

6/8/78



SCANNED

Monaco Engineering, Inc.

HYDROCARBON ANALYSIS LOG

COMPANY **KISSINGER PETROLEUM CORPORATION**

WELL **FORD #6-8**

COUNTY **BACA**

STATE **COLORADO**

LOCATION **C SE NW SEC 8 T34S R44W**

DATE LOGGED FROM **5/26/78**

TO

ELEVATION **K.B. 4127'**

DEPTH LOGGED FROM **1700'**

TO

ENGINEER **THOMAS HALLIDAY**

G.L. 4120'

LEGEND

VVV ANHYDRITE
 XXX ARKOSE
 AAA CHERT
 DOLOMITE
 LIMESTONE
 SANDSTONE
 COAL
 SHALE

HYDROCARBON GASES

TOTAL GAS FROM CUTTINGS
 TOTAL GAS FROM HOT WIRE

CHROMATOGRAPH ANALYSIS

1 - METHANE
 2 - ETHANE
 3 - PROPANE
 4 - BUTANES
 5 - PENTANES

ABBREVIATIONS

NB NEW BIT
 NR NO RETURNS
 CO CIRCULATE OUT
 DST DRILL STEM TEST

REMARKS

MUD CHARACTERISTICS

WT - VIS - FILT - CK - PH - CL - DIL

DRILLING RATE

MINUTES PER FT.

DEPTH

LITHOLOGY

POISSON'S RATIO

6/7/78

6/8/78

REPLACE PUMP MOTOR - DOWN 16 HRS.

RECEIVED
RECEIVED

JUN 12 1978

COLO. OIL & GAS CONS. COMM.
 COLO. OIL & GAS CONS. COMM.

SH GY SL WXY SATNY

SS F-MG CLR-WH CLY FILL ABNT
ANG CSE QTZ

SH GY-DK GY FIS-SLTY SL SDY

SS CLR QTZ CG ANG V UNCONS
WH CLY FILL

CHT TRANSLUC

LS DK GY MICXL
8.9-45-10.2-2-9.0-4800-0%

SH GY-BLK INCR SLTY SL MICA
TR PYR

LS GY SLTY SL SUG TR PP POR

SH GY-BLK AA LMY

LS AA MICXL ARG

LS CHKY WH-GY ARG FRI
SL POR

SH BLK-RED BRN FIS SL WXY CARB
8.8-35-10.0-2-9.0-5200-0%

SH AA CARB

HOLE IN PIPE - TRIP OUT : DOWN 9 HRS.

LAG=50 MIN:8 OZ. CARBIDE/55 UNITS H.W.