

Replug By Other Operator

Document Number:
404264086

Date Received:
07/07/2025

WELL ABANDONMENT REPORT

This form is to be submitted as an Intent to Abandon whenever an abandonment is planned on a borehole. After the abandonment is complete, this form shall again be submitted as a Subsequent Report of the actual work completed. The approved intent shall be valid for six months after the approval date, after that period, a new intent will be required. Attachments required with the Intent to Abandon are wellbore diagrams of the current configuration and the proposed configuration with plugs set. A Subsequent Report of Abandonment shall indicate the actual work completed. Attachments required with a Subsequent Report are a wellbore diagram showing plugs that were set and casing remaining in the hole, the job summaries from all plugging contractors used, including wireline and cementing (third party verification) and any logs that may have been run during abandonment.

ECMC Operator Number: 10670 Contact Name: Rachel Milne

Name of Operator: BISON IV OPERATING LLC Phone: (720) 3708580

Address: 518 17TH STREET SUITE 1800 Fax: _____

City: DENVER State: CO Zip: 80202 Email: rmlne@bisonog.com

For "Intent" 24 hour notice required, Name: Petrie, Erica Tel: (303) 726-3822

ECMC contact: Email: erica.petrie@state.co.us

Type of Well Abandonment Report: Notice of Intent to Abandon Subsequent Report of Abandonment

API Number 05-123-05364-00

Well Name: CHILDS Well Number: 1

Location: QtrQtr: NESE Section: 14 Township: 7N Range: 60W Meridian: 6

County: WELD Federal, Indian or State Lease Number: _____

Field Name: WILDCAT Field Number: 99999

Only Complete the Following Background Information for Intent to Abandon

Latitude: 40.573401 Longitude: -104.052905

GPS Data: GPS Quality Value: 1.2 Type of GPS Quality Value: PDOP Date of Measurement: 06/21/2025

Reason for Abandonment: Dry Production Sub-economic Mechanical Problems

Other replug

Casing to be pulled: Yes No Estimated Depth: _____

Fish in Hole: Yes No If yes, explain details below

Wellbore has Uncemented Casing leaks: Yes No If yes, explain details below

Details: _____

Current and Previously Abandoned Zones

Formation	Perf. Top	Perf. Btm	Abandoned Date	Method of Isolation	Plug Depth

Total: 0 zone(s)

Casing History

Casing Type	Size of Hole	Size of Casing	Grade	Wt/Ft	Csg/Liner Top	Setting Depth	Sacks Cmt	Cmt Btm	Cmt Top	Status
SURF	12+1/4	8+5/8	NA	26	0	112	50	112	0	VISU
OPEN HOLE	7+7/8				112	6960				

Plugging Procedure for Intent and Subsequent Report

CIBP #1: Depth _____ with _____ sacks cmt on top. CIBP #2: Depth _____ with _____ sacks cmt on top.
CIBP #3: Depth _____ with _____ sacks cmt on top. CIBP #4: Depth _____ with _____ sacks cmt on top.
CIBP #5: Depth _____ with _____ sacks cmt on top.

NOTE: Two(2) sacks cement required on all CIBPs.

Set 100 sks cmt from 6107 ft. to 5807 ft. Plug Type: OPEN HOLE Plug Tagged:
Set 60 sks cmt from 1529 ft. to 1379 ft. Plug Type: OPEN HOLE Plug Tagged:
Set _____ sks cmt from _____ ft. to _____ ft. Plug Type: _____ Plug Tagged:
Set _____ sks cmt from _____ ft. to _____ ft. Plug Type: _____ Plug Tagged:
Set _____ sks cmt from _____ ft. to _____ ft. Plug Type: _____ Plug Tagged:

Perforate and squeeze at _____ ft. with _____ sacks. Leave at least 100 ft. in casing _____ CICR Depth
Perforate and squeeze at _____ ft. with _____ sacks. Leave at least 100 ft. in casing _____ CICR Depth
Perforate and squeeze at _____ ft. with _____ sacks. Leave at least 100 ft. in casing _____ CICR Depth
Perforate and squeeze at _____ ft. with _____ sacks. Leave at least 100 ft. in casing _____ CICR Depth
Perforate and squeeze at _____ ft. with _____ sacks. Leave at least 100 ft. in casing _____ CICR Depth
Perforate and squeeze at _____ ft. with _____ sacks. Leave at least 100 ft. in casing _____ CICR Depth
Perforate and squeeze at _____ ft. with _____ sacks. Leave at least 100 ft. in casing _____ CICR Depth
Perforate and squeeze at _____ ft. with _____ sacks. Leave at least 100 ft. in casing _____ CICR Depth

(Cast Iron Cement Retainer Depth)

Set 160 sacks half in. half out surface casing from 500 ft. to 0 ft. Plug Tagged:
Set _____ sacks at surface
Cut four feet below ground level, weld on plate Above Ground Dry-Hole Marker: Yes No
Set _____ sacks in rat hole Set _____ sacks in mouse hole

Additional Plugging Information for Subsequent Report Only

Casing Recovered: _____ ft. of _____ inch casing Number of Days from Setting Surface Plug to Capping or Sealing the Well: _____
Surface Plug Setting Date: _____ Cut and Cap Date: _____

*Wireline Contractor: _____ *Cementing Contractor: _____

Type of Cement and Additives Used: _____

Flowline/Pipeline has been abandoned per Rule 1105 Yes No

Technical Detail/Comments:

Existing plug from 6920' - 6780'

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: _____ Print Name: Rachel Milne
Title: Regulatory Manager Date: 7/7/2025 Email: rmilne@bisonog.com

Based on the information provided herein, this Well Abandonment Report (Form 6) complies with ECMC Rules and applicable orders and is hereby approved.

ECMC Approved: Wolfe, Stephen Date: 7/22/2025

CONDITIONS OF APPROVAL, IF ANY LIST

Expiration Date: 1/21/2026

COA Type	Description
	<p>Plugging</p> <p>1) Provide electronic Form 42 Notice of MIRU 2 business days ahead of operations and electronic Form 42 Notice of Plugging Operations 48 hours prior to mobilizing for plugging operations.</p> <p>2) Plugs and squeezes will be placed as stated in the Plugging Procedure section of the approved NOIA unless revised by COA or prior approval from ECMC is obtained.</p> <p>3) The wellbore must be static prior to placing cement plugs which are to be a minimum of 100' in length for all but surface plugs. Mechanical isolation requires a 25' cement plug (minimum) on top. For plugs not specified to be tagged, a tag is required if circulation is not maintained while pumping plug and displacing to depth. Wait on cement(WOC) a minimum of 4 hrs before tagging a plug. Tag at tops specified. Notify ECMC Area Engineer of a high(shallow) tag or before adding cement to a previous plug due to a low(deep) cement top.</p> <p>4) Place a 50' cement plug (minimum) at the surface, both inside the inner most casing and in all annular spaces. Surface plugs shall be circulated to surface. Confirm cement to surface and complete isolation in all strings during cut and cap. After cut and prior to cap, verify isolation by either a 15 minute bubble test or 15 minute optical gas imaging observation. If there is any indication of flow contact ECMC Engineering before proceeding. Provide a statement on the 6 SRA as to which method was used and what was observed. Retain records of final isolation test for 5 years.</p> <p>5) With the Form 6 SRA operator must provide written documentation which positively affirms each COA has been addressed.</p> <p>6) Operator must wait a sufficient time on all plugs to achieve the intended design. If at any time during the plugging there is evidence of previously unreported pressure or fluid migration, contact ECMC Area Engineer before continuing operations.</p> <p>7) Plugging procedure has been approved as follows,</p> <p>Previous abandonment plug to remain at 6920-6780',</p> <p>Plug #1 - 6107-5807', 100 sx open hole plug, NOTE: depth change,</p> <p>Verify that there is no pressure or fluid migration before pumping Plug #2, contact ECMC Area Engineer for instructions if otherwise,</p> <p>Plug #2 - 1529-1379', 60 sx open hole plug, WOC and tag, NOTE: volume change,</p> <p>Plug #3 - 500-0', 160 sx open hole plug, NOTE: depth change,</p> <p>Plug #4 - 50' of cement at the surface in both the casing and the annulus per COA #4.</p>
	<p>Reported "as drilled" GPS data is inaccurate. Submit accurate "as drilled" GPS data on Subsequent Report of Abandonment. GPS data must meet the requirements of Rule 216</p>

2 COAs

ATTACHMENT LIST

Att Doc Num	Name
404264086	FORM 6 INTENT SUBMITTED
404264151	LOCATION PHOTO
404264170	WELLBORE DIAGRAM
404264175	WELLBORE DIAGRAM
404264179	PROPOSED PLUGGING PROCEDURE
404268505	SURFACE OWNER CONSENT

Total Attach: 6 Files

General Comments

<u>User Group</u>	<u>Comment</u>	<u>Comment Date</u>
Agency	Groundwater - Laramie-Fox Hills, Upper Pierre Deepest water well- 400'(28 records, 2mi) GR=4906(+16') Log - 123-05364 3/23/56 GR=4890 L-FH base 400' UP 740-1460'	07/17/2025
OGLA	Location is in CPW mapped Pronghorn Winter Concentration and Mule Deer Severe Winter Range High Priority Habitats. Although plugging and abandonment operations with heavy equipment will be allowed, the Operator is strongly encouraged to avoid them between December 1 through April 30.	07/08/2025
Permit	-Permit Review Complete	07/07/2025
Permit	-Requesting Operator to retake GPS coordinates, current coordinates are 50' away - No zones to report as per document number 215607 -No production reports to verified -Sent back to draft since the surface owners consent has the incorrect surface location	07/03/2025

Total: 4 comment(s)