

**WELL ABANDONMENT REPORT**

This form is to be submitted as an Intent to Abandon whenever an abandonment is planned on a borehole. After the abandonment is complete, this form shall again be submitted as a Subsequent Report of the actual work completed. The approved intent shall be valid for six months after the approval date, after that period, a new intent will be required. Attachments required with the Intent to Abandon are wellbore diagrams of the current configuration and the proposed configuration with plugs set. A Subsequent Report of Abandonment shall indicate the actual work completed. Attachments required with a Subsequent Report are a wellbore diagram showing plugs that were set and casing remaining in the hole, the job summaries from all plugging contractors used, including wireline and cementing (third party verification) and any logs that may have been run during abandonment.

Document Number:  
 404318888  
 Date Received:  
 09/03/2025

ECMC Operator Number: 10633 Contact Name: Trey Sloan  
 Name of Operator: CRESTONE PEAK RESOURCES OPERATING LLC Phone: (918) 534-6637  
 Address: 555 17TH STREET SUITE 3700 Fax: \_\_\_\_\_  
 City: DENVER State: CO Zip: 80202 Email: tsloan@civiresources.com

**For "Intent" 24 hour notice required,** Name: Medina, Justin Tel: (720) 471-0006  
 Email: justin.medina@state.co.us  
**ECMC contact:**

Type of Well Abandonment Report:  Notice of Intent to Abandon  Subsequent Report of Abandonment

API Number 05-005-06590-00  
 Well Name: AIRLINE ROAD- STATE Well Number: 15-12  
 Location: QtrQtr: SWSE Section: 12 Township: 5S Range: 65W Meridian: 6  
 County: ARAPAHOE Federal, Indian or State Lease Number: 70/8271-S  
 Field Name: WILDCAT Field Number: 99999

*Only Complete the Following Background Information for Intent to Abandon*

Latitude: 39.625675 Longitude: -104.610930  
 GPS Data: GPS Quality Value: \_\_\_\_\_ Type of GPS Quality Value: Accuracy in Meters Date of Measurement: 02/04/1973  
 Reason for Abandonment:  Dry  Production Sub-economic  Mechanical Problems  
 Other Re-enter to Re-plug  
 Casing to be pulled:  Yes  No Estimated Depth: \_\_\_\_\_  
 Fish in Hole:  Yes  No If yes, explain details below  
 Wellbore has Uncemented Casing leaks:  Yes  No If yes, explain details below  
 Details: \_\_\_\_\_

**Current and Previously Abandoned Zones**

Formation	Perf. Top	Perf. Btm	Abandoned Date	Method of Isolation	Plug Depth

Total: 0 zone(s)

**Casing History**

Casing Type	Size of Hole	Size of Casing	Grade	Wt/Ft	Csg/Liner Top	Setting Depth	Sacks Cmt	Cmt Btm	Cmt Top	Status
SURF	12+1/4	8+5/8	N/A	24	0	190	150	190	0	VISU
OPEN HOLE	7+7/8				190	8603				

## Plugging Procedure for Intent and Subsequent Report

CIBP #1: Depth \_\_\_\_\_ with \_\_\_\_\_ sacks cmt on top. CIBP #2: Depth \_\_\_\_\_ with \_\_\_\_\_ sacks cmt on top.  
CIBP #3: Depth \_\_\_\_\_ with \_\_\_\_\_ sacks cmt on top. CIBP #4: Depth \_\_\_\_\_ with \_\_\_\_\_ sacks cmt on top.  
CIBP #5: Depth \_\_\_\_\_ with \_\_\_\_\_ sacks cmt on top.

NOTE: Two(2) sacks cement required on all CIBPs.

Set 85 sks cmt from 7750 ft. to 7500 ft. Plug Type: OPEN HOLE Plug Tagged:   
Set 70 sks cmt from 3200 ft. to 3000 ft. Plug Type: OPEN HOLE Plug Tagged:   
Set \_\_\_\_\_ sks cmt from \_\_\_\_\_ ft. to \_\_\_\_\_ ft. Plug Type: \_\_\_\_\_ Plug Tagged:   
Set \_\_\_\_\_ sks cmt from \_\_\_\_\_ ft. to \_\_\_\_\_ ft. Plug Type: \_\_\_\_\_ Plug Tagged:   
Set \_\_\_\_\_ sks cmt from \_\_\_\_\_ ft. to \_\_\_\_\_ ft. Plug Type: \_\_\_\_\_ Plug Tagged:

Perforate and squeeze at \_\_\_\_\_ ft. with \_\_\_\_\_ sacks. Leave at least 100 ft. in casing \_\_\_\_\_ CICR Depth  
Perforate and squeeze at \_\_\_\_\_ ft. with \_\_\_\_\_ sacks. Leave at least 100 ft. in casing \_\_\_\_\_ CICR Depth  
Perforate and squeeze at \_\_\_\_\_ ft. with \_\_\_\_\_ sacks. Leave at least 100 ft. in casing \_\_\_\_\_ CICR Depth  
Perforate and squeeze at \_\_\_\_\_ ft. with \_\_\_\_\_ sacks. Leave at least 100 ft. in casing \_\_\_\_\_ CICR Depth  
Perforate and squeeze at \_\_\_\_\_ ft. with \_\_\_\_\_ sacks. Leave at least 100 ft. in casing \_\_\_\_\_ CICR Depth  
Perforate and squeeze at \_\_\_\_\_ ft. with \_\_\_\_\_ sacks. Leave at least 100 ft. in casing \_\_\_\_\_ CICR Depth  
Perforate and squeeze at \_\_\_\_\_ ft. with \_\_\_\_\_ sacks. Leave at least 100 ft. in casing \_\_\_\_\_ CICR Depth  
Perforate and squeeze at \_\_\_\_\_ ft. with \_\_\_\_\_ sacks. Leave at least 100 ft. in casing \_\_\_\_\_ CICR Depth

(Cast Iron Cement Retainer Depth)

Set 730 sacks half in. half out surface casing from 2170 ft. to 0 ft. Plug Tagged:   
Set \_\_\_\_\_ sacks at surface  
Cut four feet below ground level, weld on plate Above Ground Dry-Hole Marker:  Yes  No  
Set \_\_\_\_\_ sacks in rat hole Set \_\_\_\_\_ sacks in mouse hole

### Additional Plugging Information for Subsequent Report Only

Casing Recovered: \_\_\_\_\_ ft. of \_\_\_\_\_ inch casing Number of Days from Setting Surface Plug to Capping or Sealing the Well: \_\_\_\_\_  
Surface Plug Setting Date: \_\_\_\_\_ Cut and Cap Date: \_\_\_\_\_

\*Wireline Contractor: \_\_\_\_\_ \*Cementing Contractor: \_\_\_\_\_

Type of Cement and Additives Used: \_\_\_\_\_

Flowline/Pipeline has been abandoned per Rule 1105  Yes  No

Technical Detail/Comments:

Proposed WBD Attached.  
CPW consult is not required for big game HPH.  
Unable to confirm csg grade with historical documentation (used N/A).  
- Surface owner consultation attached  
- Location Photos attached  
Operator will use secondary containment for all tanks and other liquid containment.

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: \_\_\_\_\_ Print Name: Aubrey Noonan  
Title: Sr. Regulatory Analyst Date: 9/3/2025 Email: regulatory@civiresources.com

Based on the information provided herein, this Well Abandonment Report (Form 6) complies with ECMC Rules and applicable orders and is hereby approved.

**CONDITIONS OF APPROVAL, IF ANY LIST**

Expiration Date: 3/17/2026

<b>COA Type</b>	<b>Description</b>
	Operator committed to the following Best Management Practices under the Technical Detail/ Comments section on the Submit Tab: Operator will use secondary containment for all tanks and other liquid containment.
	"As-Drilled" well location GPS data has not been reported for this well. Operator will obtain the GPS data pursuant to Rule 216 and submit it on the Form 6 Subsequent Report of Abandonment.
	1) Provide electronic Form 42 Notice of MIRU 2 business days ahead of operations and electronic Form 42 Notice of Plugging Operations 48 hours prior to mobilizing for plugging operations. These are two separate notifications, required by Rules 405.e and 405.i. 2) Pump surface casing shoe plug at 2170' only after isolation has been verified. If surface casing cement is not circulated to surface, shut-in, WOC 4 hours then tag plug – must be at 140' or shallower and provide a minimum of 10 sx plug at the surface. 3) Leave at least 100' of cement in the wellbore for each plug without mechanical isolation. 4) After cut and prior to cap, verify isolation by either a 15 minute bubble test or 15 minute optical gas imaging recording. If there is indication of flow contact ECMC Engineering. Provide a statement on the 6SRA which method was used and what was observed. Retain records of final isolation test for 5 years. 5) With the Form 6 SRA operator must provide written documentation which positively affirms each COA listed above has been addressed.
3 COAs	

**ATTACHMENT LIST**

<b>Att Doc Num</b>	<b>Name</b>
404318888	FORM 6 INTENT SUBMITTED
404324386	LOCATION PHOTO
404338711	SURFACE OWNER CONSENT
404340336	WELLBORE DIAGRAM

Total Attach: 4 Files

**General Comments**

<b>User Group</b>	<b>Comment</b>	<b>Comment Date</b>
Engineer	Operator shall implement measures to control venting, to protect health and safety, and to ensure that vapors and odors from well plugging operations do not constitute a nuisance or hazard to public welfare.	09/18/2025
OGLA	Location is in a CPW mapped Pronghorn Winter Concentration Area High Priority Habitat. Although plugging and abandonment operations with heavy equipment will be allowed, the operator is strongly encouraged to avoid them from January 1 through April 30.	09/17/2025
Permit	Passes Permitting • No completed intervals to verify; well never completed. • No production reporting to verify; well never produced.	09/12/2025
Engineer	Deepest Water Well within 1 Mile – 1410' SB5 Base of Fox Hills - 2068' SB5 Base of Lower Arapahoe - 1535' SB5 Base of Upper Arapahoe - 1344' SB5 Base of Denver - 953'  Denver / 4893 / 5667 / 266.7 / 953 / 179 / 72.54 / NNT Upper Arapahoe / 4502 / 4822 / 159.4 / 1344 / 1024 / 43.36 / NT Lower Arapahoe / 4311 / 4521 / 90.4 / 1535 / 1325 / 24.59 / E NT Laramie-Fox Hills / 3778 / 4006 / 138.6 / 2068 / 1840 / 33.26 / NT	09/05/2025

Total: 4 comment(s)