

| DEPTH (FT) | LITHOLOGY | SAMPLE | | | | OVM/OVA (PPM) | BLOW COUNT (per 0.5 FT) | DEPTH (FT) | WELL CONSTRUCTION DETAIL | COMMENTS |
|------------|---------------------------------------------------------------------------------------------------------------------------------------|-----------------|------|--------|------------|---------------|-------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|----------|
| | DESCRIPTION | USCS SOIL CLASS | TYPE | NUMBER | RECOVERY % | | | | | |
| 0 | (0-5') clayey SAND - brown, fine to medium-grained, moderately sorted with 25% medium stiff, low plasticity clay, dry to moist, NO/NS | SC | | 1 | 100 | 1.9 | N/A | <p>Concrete/Steel Casing Bentonite Chips 2" Dia. Sch. 40 PVC Riser 10/20 Silica Sand Pack 2" Dia. Sch. 40 Slotted PVC (0.010") 2" End Cap</p> | MW-06@7.5-10' @11' wet | |
| 5 | | | | 2 | 100 | 1.7 | | | | |
| 5 | | | | 3 | 100 | 1.7 | | | | |
| 5 | (7.5-17.5') SAND - tan, fine to medium-grained, moderately sorted, wet, NO/NS | HV | | 4 | 100 | 1.8 | | | | |
| 10 | | | | 5 | 100 | 1.2 | | | | |
| 15 | | | | SP | 6 | 100 | | | | 1.6 |
| 15 | | | | | 7 | 100 | | | | 1.6 |
| 17.5 | BoB @ 17.5' | | | | | | | | | |

HV - Hydrovac
BoB - Bottom of Boring
N/A - Not applicable
NO - No odor
NS - No staining
bgs - below ground surface

| | |
|-----------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| START/COMPLETION DATE: 08/07/25 | SAND PACK INTERVAL (FEET): 1-17.5 |
| PROJECT: McKinstry 28N 21N 7C 2N 0 SA | BENTONITE/GROUT INTERVAL (FEET): 0.5-1 |
| LOGGED BY: JS | WELL SCREEN INTERVAL (FEET): 2.5-17.5 |
| DRILLING COMPANY/EQUIPMENT: EAGLE/HAND AUGER LONE TREE SERVICES/HYDROVAC | WELL DIAMETER (INCHES): 2 BORE DIAMETER (INCHES): 6.25 |
| BORING DEPTH (FEET): 17.5 WELL DEPTH (FEET): 17.5 | <p>EAGLE ENVIRONMENTAL CONSULTING, LLC 8000 W 44th Ave., Wheat Ridge, CO 80033 Ph: 303-433-0479 • F: 303-325-5449</p> |
| PID INSTRUMENT: TIGER XLT | |
| TIME STARTED/COMPLETED: 1000/1055 | |
| SAMPLE COLLECTION DEPTH (FT.)/TIME: (7.5-10)/1040 | |

| DEPTH (FT) | LITHOLOGY | SAMPLE | | | | OVM/OVA (PPM) | BLOW COUNT (per 0.5 FT) | DEPTH (FT) | WELL CONSTRUCTION DETAIL | COMMENTS |
|------------|--------------------------------------------------------------------------------------------------------------------------------|-----------------|------|--------|------------|---------------|-------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------|----------|
| | DESCRIPTION | USCS SOIL CLASS | TYPE | NUMBER | RECOVERY % | | | | | |
| 0 | (0-7.5') sandy CLAY - brown, soft, moderate to high plasticity, well sorted with 10% fine-grained sand, dry, NO/NS | CL | | 1 | 100 | 0.1 | N/A | <p>Concrete/Steel Casing Bentonite Chips 2" Dia. Sch. 40 PVC Riser 10/20 Silica Sand Pack 2" Dia. Sch. 40 Slotted PVC (0.010") 2" End Cap</p> | MW-07@7.5-10' @11' wet @16' refusal with direct push | |
| 5 | | | | 2 | 100 | 0.5 | | | | |
| 7.5 | | | | 3 | 100 | 0.9 | | | | |
| 10 | (7.5-12.5') sandy CLAY - brown, soft, high plasticity, well sorted with 5% fine-grained sand, wet, NO/NS | CHSS | | 4 | 100 | 1.4 | | | | |
| 12.5 | | | | 5 | 60 | 1.9 | | | | |
| 15 | (12.5-16') sandy CLAY - brown, medium stiff, moderate plasticity, well sorted with 10% fine to medium-grained sand, wet, NO/NS | CL | | 6 | 100 | 1.0 | | | | |
| 16 | | | | 7 | N/A | NR | | | | |
| 20 | (16-20') No recovery | NR | | | | NR | | | | |
| 20 | BoB @ 20' | | | | | | | | | |

| | | | |
|-----------------------------------------------------------|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------|------------------------------|
| START/COMPLETION DATE: 08/07/25 | | SAND PACK INTERVAL (FEET): 2.5-20 | |
| PROJECT: McKinstry 28N 21N 7C 2N 0 SA | | BENTONITE/GROUT INTERVAL (FEET): 0.5-2.5 | |
| LOGGED BY: JS | | WELL SCREEN INTERVAL (FEET): 5-20 | |
| DRILLING COMPANY/EQUIPMENT: EAGLE/GEOPROBE/HA/POTHOLE RIG | | WELL DIAMETER (INCHES): 2 | BORE DIAMETER (INCHES): 4.25 |
| BORING DEPTH (FEET): 20 | WELL DEPTH (FEET): 20 | <p>EAGLE ENVIRONMENTAL CONSULTING, LLC 8000 W 44th Ave., Wheat Ridge, CO 80033 Ph: 303-433-0479 • F: 303-325-5449</p> | |
| PID INSTRUMENT: TIGER XLT | | | |
| TIME STARTED/COMPLETED: 1025/1410 | | | |
| SAMPLE COLLECTION DEPTH (FT.)/TIME: (7.5-10)/1400 | | | |

HA - Hand auger
 SS - Solid Stem
 BoB - Bottom of Boring
 N/A - Not applicable
 NO - No odor
 NS - No staining
 NR - No Recovery
 bgs - below ground surface

| DEPTH (FT) | LITHOLOGY | SAMPLE | | | | OVM/OVA (PPM) | BLOW COUNT (per 0.5 FT) | DEPTH (FT) | WELL CONSTRUCTION DETAIL | COMMENTS |
|------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|------|--------|------------|---------------|-------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------|----------|
| | DESCRIPTION | USCS SOIL CLASS | TYPE | NUMBER | RECOVERY % | | | | | |
| 0 | (0-2.5') sandy CLAY - brown, medium stiff, low plasticity, moderately sorted with 15% fine-grained sand, dry, NO/NS (2.5-10') sandy CLAY - tan/brown, soft, high plasticity, well sorted with 10% fine-grained sand, moist, NO/NS | CL | | 1 | 100 | 0.9 | N/A | <p>Concrete/Steel Casing Bentonite Chips 2" Dia. Sch. 40 PVC Riser 10/20 Silica Sand Pack 2" Dia. Sch. 40 Slotted PVC (0.010") 2" End Cap</p> | MW-08@7.5-10' @11' wet @15' refusal with direct push | |
| 5 | | | | 2 | 100 | 1.1 | | | | |
| 10 | | | | 3 | 100 | 1.3 | | | | |
| 15 | CH | SS | 4 | 100 | 0.6 | | | | | |
| 20 | | | 5 | 90 | 0.9 | | | | | |
| 25 | (15-20') No recovery | NR | | | | 0.2 | | | | |
| 30 | | | | 6 | N/A | NR | | | | |
| BoB @ 20' | | | | | | | | | | |

| | | |
|-----------------------------------------------------------|------------------------------------------|------------------------------|
| START/COMPLETION DATE: 08/07/25 | SAND PACK INTERVAL (FEET): 2.5-20 | |
| PROJECT: McKinstry 28N 21N 7C 2N 0 SA | BENTONITE/GROUT INTERVAL (FEET): 0.5-2.5 | |
| LOGGED BY: JS | WELL SCREEN INTERVAL (FEET): 5-20 | |
| DRILLING COMPANY/EQUIPMENT: EAGLE/GEOPROBE/HA/POTHOLE RIG | WELL DIAMETER (INCHES): 2 | BORE DIAMETER (INCHES): 4.25 |
| BORING DEPTH (FEET): 20 | WELL DEPTH (FEET): 20 | |
| PID INSTRUMENT: TIGER XLT | | |
| TIME STARTED/COMPLETED: 1040/1330 | | |
| SAMPLE COLLECTION DEPTH (FT.)/TIME: (7.5-10)/1320 | | |



EAGLE
 ENVIRONMENTAL
 CONSULTING, LLC
 8000 W 44th Ave., Wheat Ridge, CO 80033
 Ph: 303-433-0479 • F: 303-325-5449

HA - Hand Auger
 SS - Solid Stem
 BoB - Bottom of Boring
 N/A - Not applicable
 NO - No odor
 NS - No staining
 NR - No Recovery
 bgs - below ground surface

| DEPTH (FT) | LITHOLOGY | SAMPLE | | | | OVM/OVA (PPM) | BLOW COUNT (per 0.5 FT) | DEPTH (FT) | WELL CONSTRUCTION DETAIL | COMMENTS |
|------------|---------------------------------------------------------------------------------------------------------------------------|-----------------|------|--------|------------|---------------|-------------------------|------------|---------------------------------------------------|----------|
| | DESCRIPTION | USCS SOIL CLASS | TYPE | NUMBER | RECOVERY % | | | | | |
| 0 | (0-6') sandy CLAY - brown, medium stiff, moderate plasticity, well sorted with 20% fine grained sand, dry to moist, NO/NS | CL | SS | 1 | 90 | 0.2 | N/A | | BG-11@2.5-5' | |
| 5 | (6-7') sandy CLAY - tan, soft, moderate plasticity, well sorted with 15% fine grained sand, wet, NO/NS | | | 2 | 60 | 0.1 | | | BG-11@5-7.5' | |
| 10 | (7-15') sandy CLAY - tan, stiff, low plasticity, well sorted, 20% fine grained sand, wet, NO/NS | | | 3 | 100 | 0.4 | | | BG-11@7.5-10' | |
| 15 | (15-20') sandy CLAY - tan, soft, moderate plasticity, well sorted with 10% fine grained sand, wet, NO/NS | | | 4 | N/A | 0.2 | | | BG-11@10-12.5' | |
| 20 | BoB @ 20' | | | | | | | 2" End Cap | @12.5' refusal with direct push BG-11@12.5-15' | |
| 25 | | | | | | | | | BG-11@15-17.5' | |
| 30 | | | | | | | | | BG-11@17.5-20' | |

BoB - Bottom of Boring
 N/A - Not applicable
 NO - No odor
 NS - No staining
 SS - Soild Stem
 bgs - below ground surface

| | | | |
|----------------------------------------------------------|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------|
| START/COMPLETION DATE: 08/08/25 | | SAND PACK INTERVAL (FEET): 1-20 | |
| PROJECT: McKinstry 28N 21N 7C 2N 0 SA | | BENTONITE/GROUT INTERVAL (FEET): 0-1 | |
| LOGGED BY: SL/JS | | WELL SCREEN INTERVAL (FEET): 2-20 | |
| DRILLING COMPANY/EQUIPMENT: EAGLE/GEOPROBE | | WELL DIAMETER (INCHES): 2 | BORE DIAMETER (INCHES): 4.25 |
| BORING DEPTH (FEET): 20 | WELL DEPTH (FEET): 20 | <p>EAGLE ENVIRONMENTAL CONSULTING, LLC 8000 W 44th Ave., Wheat Ridge, CO 80033 Ph: 303-433-0479 • F: 303-325-5449</p> | |
| PID INSTRUMENT: TIGER XLT | | | |
| TIME STARTED/COMPLETED: 0900/0945 | | | |
| SAMPLE COLLECTION DEPTH (FT.)/TIME: (2.5-20)/(0910-0940) | | | |

| DEPTH (FT) | LITHOLOGY | SAMPLE | | | | OVM/OVA (PPM) | BLOW COUNT (per 0.5 FT) | DEPTH (FT) | WELL CONSTRUCTION DETAIL | COMMENTS |
|------------|-----------------------------------------------------------------------------------------------------------------|-----------------|------|--------|------------|---------------|-------------------------|--------------------------------------|---------------------------------------------------|----------|
| | DESCRIPTION | USCS SOIL CLASS | TYPE | NUMBER | RECOVERY % | | | | | |
| 0 | (0-7') sandy CLAY - brown, stiff, moderate plasticity, well sorted with 20% fine grained sand, dry, NO/NS | CL | SS | 1 | 85 | 0.1 | N/A | | BG-12@2.5-5' | |
| 5 | (7-9') sandy CLAY - tan, soft, moderate plasticity, well sorted with 15% fine grained sand, wet, NO/NS | | | 2 | 90 | 0.3 | | | BG-12@5-7.5' | |
| 10 | (9-15') sandy CLAY - tan, very stiff, low plasticity, well sorted, 15% fine grained sand, wet, NO/NS | | | 3 | 40 | 0.2 | | | BG-12@7.5-10' @8' wet | |
| 15 | (15-20') sandy CLAY - dark brown, soft, moderate plasticity, well sorted with 10% fine grained sand, wet, NO/NS | | | 4 | N/A | 0.3 | | | BG-12@10-12.5' | |
| 20 | BoB @ 20' | | | | 0.1 | | | 2" Dia. Sch. 40 Slotted PVC (0.010") | @12.5' refusal with direct push BG-12@12.5-15' | |
| 25 | | | | | 0.9 | | | | BG-12@15-17.5' | |
| 30 | | | | | 0.5 | | | 2" End Cap | BG-12@17.5-20' | |

BoB - Bottom of Boring
 N/A - Not applicable
 NO - No odor
 NS - No staining
 SS - Solid Stem
 bgs - below ground surface

| | | | |
|----------------------------------------------------------|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------|
| START/COMPLETION DATE: 08/08/25 | | SAND PACK INTERVAL (FEET): 1-20 | |
| PROJECT: McKinstry 28N 21N 7C 2N 0 SA | | BENTONITE/GROUT INTERVAL (FEET): 0-1 | |
| LOGGED BY: SL/JS | | WELL SCREEN INTERVAL (FEET): 2-20 | |
| DRILLING COMPANY/EQUIPMENT: EAGLE/GEOPROBE | | WELL DIAMETER (INCHES): 2 | BORE DIAMETER (INCHES): 4.25 |
| BORING DEPTH (FEET): 20 | WELL DEPTH (FEET): 20 | <p>EAGLE ENVIRONMENTAL CONSULTING, LLC</p> 8000 W 44th Ave., Wheat Ridge, CO 80033 Ph: 303-433-0479 • F: 303-325-5449 | |
| PID INSTRUMENT: TIGER XLT | | | |
| TIME STARTED/COMPLETED: 0955/1030 | | | |
| SAMPLE COLLECTION DEPTH (FT.)/TIME: (2.5-20)/(1000-1030) | | | |

| DEPTH (FT) | LITHOLOGY | SAMPLE | | | | OVM/OVA (PPM) | BLOW COUNT (per 0.5 FT) | DEPTH (FT) | WELL CONSTRUCTION DETAIL | COMMENTS |
|------------|---------------------------------------------------------------------------------------------------------|-----------------|------|--------|------------|---------------|-------------------------|------------|---------------------------------------------------|----------|
| | DESCRIPTION | USCS SOIL CLASS | TYPE | NUMBER | RECOVERY % | | | | | |
| 0-4' | sandy CLAY - brown, stiff, low plasticity, well sorted with 25% fine grained sand, dry, NO/NS | CL | SS | 1 | 90 | 0.1 | N/A | | BG-13@2.5-5' | |
| 4-9' | sandy CLAY - tan, soft, moderate plasticity, well sorted with 15% fine grained sand, wet, NO/NS | | | 2 | 95 | 0.7 | | | @5' wet BG-13@5-7.5' | |
| 9-16' | sandy CLAY - tan, very stiff, low plasticity, well sorted, 15% fine grained sand, wet, NO/NS | | | 3 | 50 | 0.2 | | | BG-13@7.5-10' | |
| 16-20' | sandy CLAY - dark brown, stiff, moderate plasticity, well sorted with 10% fine grained sand, wet, NO/NS | | | 4 | N/A | 0.4 | | | @12.5' refusal with direct push BG-13@12.5-15' | |
| 20' | BoB @ 20' | | | | | | | 2" End Cap | BG-13@15-17.5' | |
| 20-30' | | | | | | | | | BG-13@17.5-20' | |

| | | | |
|----------------------------------------------------------|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------|------------------------------|
| START/COMPLETION DATE: 08/08/25 | | SAND PACK INTERVAL (FEET): 1-20 | |
| PROJECT: McKinstry 28N 21N 7C 2N 0 SA | | BENTONITE/GROUT INTERVAL (FEET): 0-1 | |
| LOGGED BY: SL/JS | | WELL SCREEN INTERVAL (FEET): 2-20 | |
| DRILLING COMPANY/EQUIPMENT: EAGLE/GEOPROBE | | WELL DIAMETER (INCHES): 2 | BORE DIAMETER (INCHES): 4.25 |
| BORING DEPTH (FEET): 20 | WELL DEPTH (FEET): 20 | <p>EAGLE ENVIRONMENTAL CONSULTING, LLC 8000 W 44th Ave., Wheat Ridge, CO 80033 Ph: 303-433-0479 • F: 303-325-5449</p> | |
| PID INSTRUMENT: TIGER XLT | | | |
| TIME STARTED/COMPLETED: 1045/1120 | | | |
| SAMPLE COLLECTION DEPTH (FT.)/TIME: (2.5-20)/(1050-1120) | | | |

BoB - Bottom of Boring
 N/A - Not applicable
 NO - No odor
 NS - No staining
 SS - Solid Stem
 bgs - below ground surface