

Document Number:
404385853

Date Received:

WELL ABANDONMENT REPORT

This form is to be submitted as an Intent to Abandon whenever an abandonment is planned on a borehole. After the abandonment is complete, this form shall again be submitted as a Subsequent Report of the actual work completed. The approved intent shall be valid for six months after the approval date, after that period, a new intent will be required. Attachments required with the Intent to Abandon are wellbore diagrams of the current configuration and the proposed configuration with plugs set. A Subsequent Report of Abandonment shall indicate the actual work completed. Attachments required with a Subsequent Report are a wellbore diagram showing plugs that were set and casing remaining in the hole, the job summaries from all plugging contractors used, including wireline and cementing (third party verification) and any logs that may have been run during abandonment.

ECMC Operator Number: 8960 Contact Name: Adam Conry
 Name of Operator: BONANZA CREEK ENERGY OPERATING COMPANY Phone: (303) 883-3351
 Address: 555 17TH STREET SUITE 3700 Fax: _____
 City: DENVER State: CO Zip: 80202 Email: AConry@civiresources.com

For "Intent" 24 hour notice required, Name: _____ Tel: _____
 Email: _____

Type of Well Abandonment Report: Notice of Intent to Abandon Subsequent Report of Abandonment

API Number 05-123-33175-00
 Well Name: Antelope Well Number: 21-29
 Location: QtrQtr: SWNW Section: 29 Township: 5N Range: 62W Meridian: 6
 County: WELD Federal, Indian or State Lease Number: _____
 Field Name: WATTENBERG Field Number: 90750

Only Complete the Following Background Information for Intent to Abandon

Latitude: 40.373310 Longitude: -104.352710
 GPS Data: GPS Quality Value: 2.3 Type of GPS Quality Value: PDOP Date of Measurement: 07/21/2011

Reason for Abandonment: Dry Production Sub-economic Mechanical Problems
 Other _____

Casing to be pulled: Yes No Estimated Depth: _____

Fish in Hole: Yes No If yes, explain details below

Wellbore has Uncemented Casing leaks: Yes No If yes, explain details below

Details: _____

Current and Previously Abandoned Zones

Formation	Perf. Top	Perf. Btm	Abandoned Date	Method of Isolation	Plug Depth
CODELL	6744	6752	07/18/2019	B PLUG CEMENT TOP	6429
NIOBRARA	6494	6642	07/18/2019	B PLUG CEMENT TOP	6429

Total: 2 zone(s)

Casing History

Casing Type	Size of Hole	Size of Casing	Grade	Wt/Ft	Csg/Liner Top	Setting Depth	Sacks Cmt	Cmt Btm	Cmt Top	Status
SURF	13+1/2	8+5/8	N/A	0	0	447	430	447	0	VISU
1ST	7+7/8	4+1/2	N/A	0	0	6903	520	6903	2824	CBL

Plugging Procedure for Intent and Subsequent Report

CIBP #1: Depth 6429 with 2 sacks cmt on top. CIBP #2: Depth _____ with _____ sacks cmt on top.
CIBP #3: Depth _____ with _____ sacks cmt on top. CIBP #4: Depth _____ with _____ sacks cmt on top.
CIBP #5: Depth _____ with _____ sacks cmt on top.

NOTE: Two(2) sacks cement required on all CIBPs.

Set 100 sks cmt from 2800 ft. to 2450 ft. Plug Type: STUB PLUG Plug Tagged:
Set _____ sks cmt from _____ ft. to _____ ft. Plug Type: _____ Plug Tagged:
Set _____ sks cmt from _____ ft. to _____ ft. Plug Type: _____ Plug Tagged:
Set _____ sks cmt from _____ ft. to _____ ft. Plug Type: _____ Plug Tagged:
Set _____ sks cmt from _____ ft. to _____ ft. Plug Type: _____ Plug Tagged:

Perforate and squeeze at _____ ft. with _____ sacks. Leave at least 100 ft. in casing _____ CICR Depth
Perforate and squeeze at _____ ft. with _____ sacks. Leave at least 100 ft. in casing _____ CICR Depth
Perforate and squeeze at _____ ft. with _____ sacks. Leave at least 100 ft. in casing _____ CICR Depth
Perforate and squeeze at _____ ft. with _____ sacks. Leave at least 100 ft. in casing _____ CICR Depth
Perforate and squeeze at _____ ft. with _____ sacks. Leave at least 100 ft. in casing _____ CICR Depth
Perforate and squeeze at _____ ft. with _____ sacks. Leave at least 100 ft. in casing _____ CICR Depth
Perforate and squeeze at _____ ft. with _____ sacks. Leave at least 100 ft. in casing _____ CICR Depth
Perforate and squeeze at _____ ft. with _____ sacks. Leave at least 100 ft. in casing _____ CICR Depth

(Cast Iron Cement Retainer Depth)

Set 275 sacks half in. half out surface casing from 547 ft. to 0 ft. Plug Tagged:
Set 10 sacks at surface
Cut four feet below ground level, weld on plate Above Ground Dry-Hole Marker: Yes No
Set _____ sacks in rat hole Set _____ sacks in mouse hole

Additional Plugging Information for Subsequent Report Only

Casing Recovered: 2650 ft. of 4+1/2 inch casing
Surface Plug Setting Date: 08/21/2025 Cut and Cap Date: 09/29/2025 Number of Days from Setting Surface Plug to Capping or Sealing the Well: 39

*Wireline Contractor: Surefire *Cementing Contractor: Axis

Type of Cement and Additives Used: G Neat

Flowline/Pipeline has been abandoned per Rule 1105 Yes No

Technical Detail/Comments:

Change in plugging operations communicated with ECMC engineers - see attached correspondence.

Operator used secondary containment for all tanks and other liquid containment.

See Form 27 Doc# 404269701 (WH, FAC, OFF-LOC).
 This well's flowline(s) has not yet been abandoned per Rule 1105 at the time of this Form 6 subsequent report. It will be abandoned within 90 days of the last surface plug set date and reported on a Form 42 or 44 as per Rule 1105.f.

Form 42 was submitted prior to plugging operations, Form 42 Doc #404319625. Form 42 was submitted prior to MIRU for plugging operations, Form 42 Doc #404319627.
 Prior to placing the 547' plug, operator waited a sufficient amount of time to confirm static conditions. There was no pressure or fluid migration.
 No fluids or gas migration was present prior to surface casing shoe plug being set. The plug was cemented to surface with 275 sacks of cement from 547' - 0' with an additional 10 sks of cement at surface.
 At least 100' of cement was left in the wellbore for each plug.
 After cut prior to cap, Operator verified isolation by a 15 minute bubble test and no flow was observed.
 This form 6-SRA addresses all COA's from the Form 6-NOIA.

Venting health and safety precautions were taken to avoid nuisance and or hazards to the public.

A Bradenhead test was performed before plugging this well. Pressures were present, but there was no flow, so no sample could be taken. Form 17 submitted with results, Doc #404297590.

Attached to this form:
 1. Wireline tickets
 2. Cement tickets
 3. Operations summary
 4. Final P&A WBD
 5. CBL
 6. ECMC correspondence

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: _____ Print Name: Aubrey Noonan
 Title: Sr. Regulatory Analyst Date: _____ Email: regulatory@civiresources.com

Based on the information provided herein, this Well Abandonment Report (Form 6) complies with ECMC Rules and applicable orders and is hereby approved.

ECMC Approved: _____ Date: _____

CONDITIONS OF APPROVAL, IF ANY LIST

<u>COA Type</u>	<u>Description</u>
0 COA	

ATTACHMENT LIST

<u>Att Doc Num</u>	<u>Name</u>
404385903	CEMENT JOB SUMMARY
404385905	OPERATIONS SUMMARY
404385906	WIRELINE JOB SUMMARY
404385907	CEMENT BOND LOG
404402794	WELLBORE DIAGRAM
404403830	CORRESPONDENCE

Total Attach: 6 Files

General Comments

<u>User Group</u>	<u>Comment</u>	<u>Comment Date</u>
		Stamp Upon Approval

Total: 0 comment(s)