



00390979

RECEIVED

MAR 20 1978

COLO. OIL & GAS CONS. COMM.

A. T. SKAER
Christiansen No. 3
Section 22, T3S, R50W-SW/SW 600' FWL & 330' FSL
Washington County, Colo.
Allison Drilling Company Rig
Vince Eurich, Pusher

3-22-1976: Started running casing @ 8:00 P. M.
Ran 126 jts. of 5-1/2" 14# casing
Ran casing to bottom-picked up three
feet off bottom to cement to bring casing
collar above rotary table.
Plug back T.D. @ approximately 3909'.
Approximately 22' of rat hole below bottom of
pay zone.
Ran guide shoe on bottom jt. Ran 60' of Roto
Wall Cleaners from 3860' to 3920'--three
centralizers- one at 3910', 3876' and 3844 approx.
Ran casing to bottom-circulated until pump pressure
leveled off. Hole clean-no trouble getting to
T.D.--picked casing up three feet off bottom.
Cemented with 150sx 50/50 Pozmix 3% salt by volume
of water. Ran plug ahead and behind cement.
Bumped float with 1500 P.S.I. Let set 15 min. with
pressure on casing then released pressure-float held
O.K. Plug down @ 11:15 P. M.
Called Lambrecht Welding Service @ 1:00 A. M. 3/23/76
to cut off casing and weld on bell nipple.

Kenneth Lewis



CARL A. HOUY

~~610-PATTERSON-BUILDING~~

DENVER, COLORADO 80202
910 Metrobank Building
TELEPHONE 303 -~~695-6992~~ 534-0784


REC-11
MAR 20 1978

COLO. OIL & GAS CONS. COMM.

A. T. SKAER
CHRISTIANSEN NO. 3
Pod Field
SW/SW Section 22, T3S, R50W,
Washington County, Colorado

April 14, 1976

PBTD 3900'.
Swabbed casing to 3170'.
Perforated 3890.5-92.5' with 3 - 90 gram jets per foot (total
7 holes).
Swabbed hole down - oil on last pull.
30 minute fillup - 2 barrels - good show of oil.
Loaded hole with 10 barrels crude.
Perforated 3881-83' with 3 - 90 gram jets per foot (total 7
holes).
Ran swab - top of fluid 3000' below surface.
Swabbed 27 barrels in 35 minutes - did not lower fluid - good
oil cut.
Will swab test and sand pump April 14th and 15th.



Carl A. Houy