Radial CBL
VDL / CCL / GR

Company Civitas Resources
Well Antelope K-19
Field Wattenberg
County Weld
State CO

API #: 05-123-35127

Location:
SHL: 634' FNL & 1977' FWL NE/NW
BHL: 50' FNL & 2525' FWL NE/NW
SEC 7 TWP 2N RGE 67W

Other Services

Permanent Datum	GL	Elevation 4605'	Elevation
Log Measured From	KB		K.B. 4616'
Drilling Measured From	KB		D.F. 4615' G.L. 1605'

Date	July 9, 2025
Run Number	1
Depth Driller	6745'
Depth Logger	6260'
Bottom Logged Interval	6260'-0'
Top Log Interval	
Open Hole Size	
Type Fluid	WATER
Density / Viscosity	8.3
Max. Recorded Temp.	215° F
Estimated Cement Top	
Time Well Ready	
Time Logger on Bottom	
Equipment Number	505
Location	
Recorded By	Meisner
Witnessed By	Santiago

Borehole Record				Tubing Record			
Run Number	Bit	From	To	Size	Weight	From	To

Casing Record	Size	Wgt/Ft	Top	Bottom
Surface String	8-5/8"	24 Lbs.	0'	482'
Prot. String				
Production String	4-1/2"	11.6 Lbs.	0'	6745'
Liner				

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

Thank you for choosing Surefire Wireline

CBL Ran With 500 PSI Applied

Database File	cblantelopek19.db
Dataset Pathname	pass1
Presentation Format	civitas
Dataset Creation	Wed Jul 09 12:09:15 2025
Charted by	Depth in Feet scaled 1:240

5 CCL$1 -0.625	0 AMP (mV) 100	0 AMPS1 150	200 VDL (usec) 1200	1 RADIAL MAP 8
0 GR (GAPI) 150	650 TT (usec) 150	0 AMPS2 150		
GCT_TEMP (degF)	0 AMPx5 (mV) 20	0 AMPS3 150		
		0 AMPS4 150		
		0 AMPS5 150		
		0 AMPS6 150		
		0 AMPS7 150		
		0 AMPS8 150		

3750
3800
147.88
3850
3900
150.28
3950
4000
152.80
4050
4100
155.43
4150
4200
157.95
4250
4300
160.38
4350
4400
162.87
4450
4500
165.61
4550
4600
168.25
4650
4700
170.86
4750
4800
173.44
4850
4900
176.07
4950
5000
179.33
5050
5100
182.63
5150
5200
185.86
5250
5300
189.10
5350
5400
192.56
5450
5500
196.15
5550
5600
199.48
5650
5700
202.71
5750
5800
205.64
5850
5900
207.90
5950
6000
210.26
6050
6100
212.36
6150
6200
216.52
6250
5 CCLS1 -0.625
0 GR (GAPI) 150
GCT_TEMP
(degF)
0 AMP (mV) 100
650 TT (usec) 150
0 AMPx5 (mV) 20
0 AMPS1 150
0 AMPS2 150
0 AMPS3 150
0 AMPS4 150
0 AMPS5 150
0 AMPS6 150
0 AMPS7 150
0 AMPS8 150
200 VDL (usec) 1200
1 RADIAL MAP 8