



OFFICE OF STATE OIL INSPECTOR  
SUNDRY NOTICES AND REPORTS OF WELLS  
LOCATED ON PRIVATE LANDS

104-12

(Indicate nature of data by checking below)

- Notice of intention to drill X
- Notice of intention to change plans \_\_\_\_\_
- Notice of date for test of water shut-off \_\_\_\_\_
- Report on result of test of water shut-off \_\_\_\_\_
- Notice of intention to re-drill or repair well \_\_\_\_\_
- Notice of intention to clean out well \_\_\_\_\_
- Statement of shooting \_\_\_\_\_
- Statement of perforating \_\_\_\_\_
- Notice to pull or otherwise alter casing \_\_\_\_\_
- Notice of intention to abandon well \_\_\_\_\_
- Report of work done on well since previous report \_\_\_\_\_

Following is a (notice of intention to do work) Dec. 3 1951  
(~~report of work done~~) (On land) (patented) Described as follows:

<u>COLORADO</u> State	<u>LOGAN</u> County	<u>YENTER</u> Field
<u>4</u> (Well No.)	<u>Naggatz</u> (Lease)	<u>NW/4 Sec. 10</u> (Sec. and 1/4 Sec.)
		<u>8N</u> (Twp.)
		<u>54W</u> (Range)
		<u>(Meridian)</u>

The well is located 990 ft. (S) of North Line and 330 ft. (W) of East Line  
NW/4 Sec. 10

The elevation above sea level is 4365 ft. K.B. (Est.)

Details of Plan of Work: (State names of and expected depths to objective sands; Show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work.)

To drill and test subject well to the "J" Sand of the Graneros Sand Series.  
SURFACE CASING: 9-5/8" O.D. Armco Spiral Weld to be set at approximately 200' and cemented with 160 sax. Cement to be circulated to ground surface.  
PRODUCTION STRING CASING: 5 1/2" O.D., 15.5#, J-55 casing to be set through the oil producing section of the "J" Sand. Cement with 200 sax.  
TESTING: 1. No coring planned. 2. DST "D" Sand if above minus 715'. 3. No DST planned for "J" sand.  
LOGGING: One-run Schlumberger Electric Log from under surface casing point to T.D. Run Micro-log only in event that evaluation of the electric log indicates that it is necessary and desirable.  
DRIFT SURVEYS: At 50' intervals in surface hole and to a point 100' below surface casing, thereafter at 250' intervals.  
DRILLING TIME: Use Geolograph from 3500' to T.D.  
SAMPLES: 5' intervals from 5000' to T.D.  
DEPTH MEASUREMENTS: SLM of drill pipe at approx. 4000' and prior to DST And at T.D.  
COMPLETION PROGRAM: Drill "J" Sand to a minus T.D. of 880' or just into the water zone. Set and cement the oil string casing on bottom (thru the oil section) and perforate for production.  
EXPECTED FORMATION TOPS: Niobrara 4340' - Ft. Hays 4618' - Greenhorn 4841' - "D" Sand 5113' - "J" Sand 5212'

Approved: DEC 5 1951  
[Signature]  
DIRECTOR

Company The British American Oil Producing Co.  
Address P. O. Box 620, Casper, Wyoming  
By [Signature]  
Title Sup't., Northwestern District

Submit reports of proposed work, for approval, on this form in Duplicate.