02359450

Locate
Well
Correctly

Naggatz "B" #4

OFFICE OF STATE OIL INSPECTOR
Oil and Gas Conservation
Department

- - -

LOG OF OIL AND GAS WELL

Company The British-American Oil Prod. Co. Address P. O. Box 620 - Casper, Wyoming
State or Patented Patented Field Yenter Block State Colorado
Well No. 4 Sec. 10 (XXXX) T. 8N. R. 54W. (XXXX) Meridian County Logan
Location 990 Ft. (S) of N. Line and 330 Ft. (W) of E. line of NW/4 Elevation 4349' GL
(Derrick floor ralative to sea level)

The information given herewith is a complete and correct record of the well and all work done thereon so far as can be determined from all available records.

Signed [signature]
Date March 6, 1952 Title District Superintendent

The summary on this page is for the condition of the well as above date.
Commenced drilling 12-2, 1951 Finished Drilling 12-12 1951

OIL SANDS OR ZONES

No. 1, from 5126' to 5157' "D" No. 4, from to
No. 2, from 5228' to Not penetrated "J" No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

No. 1, from to No. 3, from to
No. 2, from to No. 4, from to

CASING RECORD

Size	Weight per ft.	Threads per inch	Make	Amount	Kind of Shoe	Cut & Pulled from	Perforated From	Perforated to	Purpose
9-5/8"	32#	8 Rd.	T&C	220'					

MUDDING AND CEMENTING RECORD

Size	Where Set	No. Sacks of Cement	Methods used	Mud Gravity	Amount of Mud Used
9-5/8"	219'KB	160	HOWCO		

PLUGS AND ADAPTERS

Heaving plug-Material Length Depth Set
Adapters-Material Size

SHOOTING RECORD

Size	Shell Used	Explosive Used	Quantity	Date	Depth Shot	Depth Cleaned Out

TOOLS USED

Rotary Tools used from 0 ft. to 5242 ft. and from ft. to ft.
Cable tools were used from ft. to ft. and from ft. to ft.

DATES

December 28 1951 Put to producing DRY 19
The production for the first 24 hours was barrels of fluid of which
% was oil, % emulsion; % sediment. Gravity Be,
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft.
of gas . Rock Pressure, lbs. per sq. in.

EMPLOYES

Sterling Drilling Company Driller , Driller
Driller , Driller

FORMATION RECORD

From	To	Total Feet	Formation
0	220	220	Clay & Shale
220	4470	4250	Shale & Shells
4470	5025	555	Shale & Lime
5025	5240	215	Sand & Shale