



00239086

OFFICE OF STATE OIL INSPECTOR
SUNDRY NOTICES AND REPORTS OF WELLS
LOCATED ON PRIVATE LANDS

2 approved copies
returned 8/20/51
JB

8/20/51

185-4

(Indicate nature of data by checking below)

- Notice of intention to drill
- Notice of intention to change plans
- Notice of date for test of water shut-off
- Report on result of test of water shut-off
- Notice of intention to re-drill or repair well
- Notice of intention to clean out well
- Statement of shooting
- Statement of perforating
- Notice to pull or otherwise alter casing
- Notice of intention to abandon well
- Report of work done on well since previous report

August 17 19 51

Following is a (notice of intention to do work) (On land)
(~~report of work done~~) (patented) described as follows:

| | | |
|-------------|------------|---------------------|
| Colorado | Logan | Yenter Pool |
| State | County | Field |
| Eleven (11) | Yenter "A" | Lot #1 NE/4, Sec. 3 |
| (Well No.) | (Lease) | (Sec. and 1/4 Sec.) |
| | | 8 N. |
| | | (Twp.) |
| | | 54 W. |
| | | (Range) (Meridian) |

The well is located 330 ft. ~~(N)~~ of North Line and 330 ft. ~~(E)~~ of East Line
(S) (W)

Lot #1 NE/4, Sec. 3

The elevation above sea level is 4325' ft. G.L. Estimated

Details of Plan of Work: (State names of and expected depths to objective sands; Show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work.)

To drill and test subject well to the "J" Sand of the Graneros Sand series.

SURFACE CASING: 9-5/8" O.D. Armco spiral weld to be set at approx. 200' and cemented with 150 sax. Cement to be circulated to ground surface.

PRODUCTION STRING CASING: 5 1/2" O.D., 15.5#, J-55, casing to be set thru the oil producing section of the "J" Sand. Cement with 200 sax.

TESTING: 1.- No coring planned. 2.-DST "D" Sand if as high as Yenter #2 (-713')
3.-No DST planned for "J" Sand.

LOGGING: One-run Schlumberger electric log from under Surface casing point to T.D. Run Micro log only in event that evaluation of the electric log indicates that it is necessary and desirable.

DRIFT SURVEYS: At 50' intervals in surface hole and to a point 100' below surface casing, thereafter at 250' intervals.

DRILLING TIME: Use Geolograph.

SAMPLES: 10' intervals from 4200' to 5050' - 5' intervals from 5050' to T.D.

DEPTH MEASUREMENTS: SIM of drill pipe at approximately 4000' and prior to DST and at total depth.

Approved: Aug 20 1951

John R. Brown
State Oil Inspector

Company The British-American Oil Producing Co.

Address *C. Wm. Evelyn, Jr.*

By C. Wm. Evelyn, Jr.

Title Superintendent - Northwestern Dist.

Submit reports of proposed work, for approval, on this form in Duplicate.

COMPLETION PROGRAM: Drill "J" Sand to a minus T.D. of 865' or just into the water zone. Set and cement the oil string casing on bottom (thru the oil section) and perforate for production.

ESTIMATED FORMATION TOPS: Niobrara 4270' - Ft. Hays 4550' - Greenhorn 4810'
"D" Sand 5062' - "J" Sand 5175'