



00751922

OFFICE OF STATE OIL INSPECTOR  
SUNDRY NOTICES AND REPORTS OF WELLS  
LOCATED ON PRIVATE LANDS

*2 approved copies  
returned 4-13-51  
JB 117-19*

R

(Indicate nature of data by checking below)

\* NOTE: It was necessary to move location 30' east of a normal location because of a 15' rock ledge.

- Notice of intention to drill
- Notice of intention to change plans.....
- Notice of date for test of water shut-off.....
- Report on result of test of water shut-off.....
- Notice of intention to re-drill or repair well.....
- Notice of intention to clean out well.....
- Statement of shooting.....
- Statement of perforating.....
- Notice to pull or otherwise alter casing.....
- Notice of intention to abandon well.....
- Report of work done on well since previous report.....

April 10 1951

Following is a (notice of intention to do work) (On land)  
(report of work done) (patented) described as follows:

| COLORADO   | LOGAN       | YENTER POOL         |                           |
|------------|-------------|---------------------|---------------------------|
| State      | County      | Field               |                           |
| ONE (1)    | ZIEGLER "B" | NE 1/4 Sec. 3       | 8N 54W                    |
| (Well No.) | (Lease)     | (Sec. and 1/4 Sec.) | (Twp.) (Range) (Meridian) |

\* The well is located 330 ft. (N) of North Line and 360 ft. (E) of West Line, Lot 10, NE 1/4 Sec. 3 (S) (W)

The elevation above sea level is 4370 ft. G.L. Estimated

Details of Plan of Work: (State names of and expected depths to objective sands: Show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work.)

To drill and test subject well to the "J" Sand of the Granerous Sand series.  
SURFACE CASING: 9-5/8" O.D. Armco Spiral Weld to be set at approx. 200' & cemented with 150 sax. Cement to be circulated to ground surface.  
PRODUCTION STRING CASING: 5 1/2" OD, 15.5#, J-55, Casing to be set thru the oil producing section of the "J" Sand. Cement with 200 sax.  
TESTING: 1. No coring planned. 2. DST "D" Sand if as high as Yenter #2 (-713') 3. No DST planned for "J" Sand.  
LOGGING: One-run Schlumberger electric log from under surface casing point to T.D. Run Micro-log on any indicated gas or oil zones.  
DRIFT SURVEYS: At 50' intervals in surface hole & to a point 100' below surface casing, thereafter at 250' intervals.  
DRILLING TIME: Use Geolograph. SAMPLES: 10' intervals from 4200' to 5050'  
5' intervals from 5050' to TD  
DEPTH MEASUREMENTS: SLM of drill pipe at approx. 4000' & prior to DST and at total depth.

COMPLETION PROGRAM: Drill "J" Sand to a minus T.D. of 865' or just into the water zone. Set and cement the oil string casing on bottom (thru the oil section) and perforate for production.

04/13/51

Title...Suppl...Northwestern District

Submit reports of proposed work, for approval, on this form in Duplicate.