



OFFICE OF STATE OIL INSPECTOR
SUNDRY NOTICES AND REPORTS OF WELLS
LOCATED ON PRIVATE LANDS

R

117-7

(Indicate nature of data by checking below)

- Notice of intention to drill
- Notice of intention to change plans.....
- Notice of date for test of water shut-off.....
- Report on result of test of water shut-off.....
- Notice of intention to re-drill or repair well.....
- Notice of intention to clean out well.....
- Statement of shooting.....
- Statement of perforating.....
- Notice to pull or otherwise alter casing.....
- Notice of intention to abandon well.....
- Report of work done on well since previous report.....

February 26 19 51

Following is a (notice on intention to do work) (On land)
(~~report of work done~~) (~~patented~~) described as follows:

Colorado	Logan	Yenter Pool		
State	County	Field		
5	Yenter	Sec. 3 - NE $\frac{1}{4}$	8N	54W 6th.
(Well No.)	(Lease)	(Sec. and $\frac{1}{4}$ Sec.)	(Twp.)	(Range) (Meridian)

The well is located 330' ft. (N) of So. Line and 990' ft. (E) of W. Line
Sec. 3 - NE $\frac{1}{4}$ lot 7 (S) (W)

The elevation above sea level is Est. 4370' ft.

Details of Plan of Work: (State names of and expected depths to objective sands: Show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work.)

To drill W/Rotary tools and test well to the "J" Sand of the Granerous sand series, expected at approximately 5250'.

SURFACE CASING: 8-5/8" OD, 32# to be set at approximately 200' and cement with 175 sacks.

PRODUCTION STRING CASING: 5 1/2" OD, 15.5#, J-55, casing to be set on top of or thru the producing zone. Casing to be cemented with 200 Sacks.

TESTING: No coring planned. DST "D" Sand if as high as Yenter #2 (-713'). No DST planned for "J" Sand.

LOGGING: One-run Schlumberger electric log from under surface casing point to T.D. Run Micro-log on any indicated gas or oil zones.

DRIFT SURVEYS: At 50' intervals in surface hole and to a point 100' below surface casing, thereafter at 250' intervals.

DRILLING TIME: Use Geolograph.

SAMPLES: 10' intervals from 4200' to 5050' and 5' intervals from 5050' to T.D.

DEPTH MEASUREMENTS: S. L. M. of drill pipe at approximately 4000' & prior to DST & at T.D.

COMPLETION PROGRAM: To be determined from DST and Geological evaluation.

Approved: Feb 28 19 51
John E. [Signature]
State Oil Inspector

Company British-American Oil Producing Co.

Address Casper, Wyoming

By C. Wm. Evelyn, Jr. [Signature]

Title District Superintendent

Submit reports of proposed work, for approval, on this form in Duplicate.