



99999999

GAS CONSERVATION COMMISSION THE STATE OF COLORADO

075-06125

RECEIVED

FEB 21 1968

Application for Patented and Federal lands. File in triplicate for State lands.

COLO. OIL & GAS CONS. COMM.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

Form fields 1-15 containing well details: 1. OIL WELL [X] GAS WELL [ ] OTHER [ ]; 2. NAME OF OPERATOR PAT'S POWER TONGS, INC.; 3. ADDRESS OF OPERATOR Box 702, Grand Junction, Colorado 81501; 4. LOCATION OF WELL 663' FNL, 654' FEL of NE/4; 5. ELEVATIONS 4386' D.F.; 7. UNIT AGREEMENT NAME Liberty "J" Sand; 8. FARM OR LEASE NAME MALLO; 9. WELL NO. 5; 10. FIELD AND POOL, OR WILDCAT Liberty; 11. SEC., T., R., M., OR BLEK. AND SURVEY OR AREA S.5, T.8N., R.54W.; 12. COUNTY OR PARISH Logan; 13. STATE Colo.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

Checkboxes for TEST WATER SHUT-OFF, FRACTURE TREAT, SHOOT OR ACIDIZE, REPAIR WELL, PULL OR ALTER CASING, MULTIPLE COMPLETE, ABANDON, CHANGE PLANS, WATER SHUT-OFF, FRACTURE TREATMENT, SHOOTING OR ACIDIZING, REPAIRING WELL, ALTERING CASING, ABANDONMENT. Includes note: (NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Date of work Compl. 2-8-68

LU-3

Dumped 3 bbls of sand and filled the 5 1/2" casing from 5360' to 5240' Set 15 sack cement plug from 5240' to 5110' depth.

Shot off 5 1/2" casing @ 3807' depth and pulled.

Filled hole with heavy mud from 5110' to 225' depth.

Set 10 sack cement plug over base of 9-5/8" from 225' to 195' depth.

Filled casing from 195' depth to approx. 15' from bottom of the cellar with heavy mud.

Set 5 sack cement plug in top of 9-5/8" casing from 15' depth approx. to bottom of cellar. Welded on steel plate at top of the surface casing. Filled cellar with rocks, dirt and topped off with top soil.

Plugged & Abandoned 2-8-68

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Agent/Pat's Power Tongs DATE 2-20-68

(This space for Federal or State office use)

APPROVED BY [Signature] TITLE Director DATE 2/21/68

CONDITIONS OF APPROVAL, IF ANY:

Handwritten table with initials: DVR, FJP, HHH, JAM, JJD. Includes handwritten note 'Ex G's Prod'.



075-06125 T



00786188