

Document Number:
 404500831
 Date Received:
 01/09/2026

WELL ABANDONMENT REPORT

This form is to be submitted as an Intent to Abandon whenever an abandonment is planned on a borehole. After the abandonment is complete, this form shall again be submitted as a Subsequent Report of the actual work completed. The approved intent shall be valid for six months after the approval date, after that period, a new intent will be required. Attachments required with the Intent to Abandon are wellbore diagrams of the current configuration and the proposed configuration with plugs set. A Subsequent Report of Abandonment shall indicate the actual work completed. Attachments required with a Subsequent Report are a wellbore diagram showing plugs that were set and casing remaining in the hole, the job summaries from all plugging contractors used, including wireline and cementing (third party verification) and any logs that may have been run during abandonment.

ECMC Operator Number: 10711 Contact Name: Deborah Abrams
 Name of Operator: PAINTED PEGASUS PETROLEUM LLC Phone: (303) 8942100
 Address: 16820 BARKER SPRINGS RD #521 Fax: _____
 City: HOUSTON State: TX Zip: 77084 Email: deborah.abrams@state.co.us

For "Intent" 24 hour notice required, Name: Medina, Justin Tel: (720) 471-0006
 ECMC contact: Email: justin.medina@state.co.us

Type of Well Abandonment Report: Notice of Intent to Abandon Subsequent Report of Abandonment

API Number 05-001-08195-00
 Well Name: UPPR-JULIE Well Number: 1 (OWP)
 Location: QtrQtr: NWNE Section: 17 Township: 1S Range: 64W Meridian: 6
 County: ADAMS Federal, Indian or State Lease Number: _____
 Field Name: BANNER LAKES Field Number: 5195

Only Complete the Following Background Information for Intent to Abandon

Latitude: 39.969444 Longitude: -104.572368
 GPS Data: GPS Quality Value: 2.1 Type of GPS Quality Value: _____ Date of Measurement: 10/20/2010
 Reason for Abandonment: Dry Production Sub-economic Mechanical Problems
 Other OWP
 Casing to be pulled: Yes No Estimated Depth: _____
 Fish in Hole: Yes No If yes, explain details below
 Wellbore has Uncemented Casing leaks: Yes No If yes, explain details below
 Details: _____

Current and Previously Abandoned Zones

Formation	Perf. Top	Perf. Btm	Abandoned Date	Method of Isolation	Plug Depth
D & J SAND	7676	7770			
J SAND	7776	7786			

Total: 2 zone(s)

Casing History

Casing Type	Size of Hole	Size of Casing	Grade	Wt/Ft	Csg/Liner Top	Setting Depth	Sacks Cmt	Cmt Btm	Cmt Top	Status
SURF	12+1/4	8+5/8	UNK	24	0	212	150	212	0	VISU
1ST	7+7/8	4+1/2	UNK	11.6	0	7848	275	7848	6650	CALC
S.C. 1.1						1410	100	1410	1000	CBL

Plugging Procedure for Intent and Subsequent Report

CIBP #1: Depth 7601 with 2 sacks cmt on top. CIBP #2: Depth 6783 with 2 sacks cmt on top.
 CIBP #3: Depth _____ with _____ sacks cmt on top. CIBP #4: Depth _____ with _____ sacks cmt on top.
 CIBP #5: Depth _____ with _____ sacks cmt on top.

NOTE: Two(2) sacks cement required on all CIBPs.

Set _____ sks cmt from _____ ft. to _____ ft. Plug Type: _____ Plug Tagged:
 Set _____ sks cmt from _____ ft. to _____ ft. Plug Type: _____ Plug Tagged:
 Set _____ sks cmt from _____ ft. to _____ ft. Plug Type: _____ Plug Tagged:
 Set _____ sks cmt from _____ ft. to _____ ft. Plug Type: _____ Plug Tagged:
 Set _____ sks cmt from _____ ft. to _____ ft. Plug Type: _____ Plug Tagged:

Perforate and squeeze at 2550 ft. with 50 sacks. Leave at least 100 ft. in casing 2500 CICR Depth
 Perforate and squeeze at 1352 ft. with 65 sacks. Leave at least 100 ft. in casing 1272 CICR Depth
 Perforate and squeeze at _____ ft. with _____ sacks. Leave at least 100 ft. in casing _____ CICR Depth
 Perforate and squeeze at _____ ft. with _____ sacks. Leave at least 100 ft. in casing _____ CICR Depth
 Perforate and squeeze at _____ ft. with _____ sacks. Leave at least 100 ft. in casing _____ CICR Depth
 Perforate and squeeze at _____ ft. with _____ sacks. Leave at least 100 ft. in casing _____ CICR Depth
 Perforate and squeeze at _____ ft. with _____ sacks. Leave at least 100 ft. in casing _____ CICR Depth
 Perforate and squeeze at _____ ft. with _____ sacks. Leave at least 100 ft. in casing _____ CICR Depth

(Cast Iron Cement Retainer Depth)

Set 150 sacks half in. half out surface casing from 475 ft. to 0 ft. Plug Tagged:
 Set _____ sacks at surface
 Cut four feet below ground level, weld on plate Above Ground Dry-Hole Marker: Yes No
 Set _____ sacks in rat hole Set _____ sacks in mouse hole

Additional Plugging Information for Subsequent Report Only

Casing Recovered: _____ ft. of _____ inch casing Number of Days from Setting Surface Plug to Capping or Sealing the Well: _____
 Surface Plug Setting Date: _____ Cut and Cap Date: _____
 *Wireline Contractor: _____ *Cementing Contractor: _____
 Type of Cement and Additives Used: _____
 Flowline/Pipeline has been abandoned per Rule 1105 Yes No

Technical Detail/Comments:

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.
 Signed: _____ Print Name: Deborah Abrams
 Title: OWP Date: 1/9/2026 Email: deborah.abrams@state.co.us

Based on the information provided herein, this Well Abandonment Report (Form 6) complies with ECMC Rules and applicable orders and is hereby approved.

Jacobson, Eric

ECMC Approved: _____

Date: 1/14/2026

CONDITIONS OF APPROVAL, IF ANY LIST

Expiration Date: 7/13/2026

COA Type	Description
	Operator shall implement measures to control venting, to protect health and safety, and to ensure that vapors and odors from well plugging operations do not constitute a nuisance or hazard to public welfare.
	This oil and gas location is located within a CPW-mapped 500 foot buffer of the Ordinary High Water Mark of Horse Creek for protection of Aquatic Native Species Conservation Water High Priority Habitat/Cutthroat Trout Designate Crucial Habitat/Sportfish Management Waters High Priority Habitat. At a minimum, Operator will review the stormwater program and implement stormwater BMPs and erosion control measures as needed to prevent fine-grained sediment and impacted stormwater runoff from entering surface water.
	Due to proximity to a wetland, surface water and expected shallow groundwater, operator will use secondary containment for all tanks and other liquid containers. Operator will implement stormwater BMPs and erosion control measures as needed to prevent sediment and stormwater runoff from entering the wetland and surface water.
	Notification will be given to any adjacent building unit occupants within 1,000 feet of the wellhead of planned P&A start date.
	CBL to be run prior to plugging to verify stage tool setting depth and existing coverage - submit to ECMC for verification of plugging orders prior to continuing plugging operations.
	<p>Prior to starting plugging operations a bradenhead test shall be performed if there has not been a reported bradenhead test within the 60 days immediately preceding the start of plugging operations.</p> <p>1) If, before opening the bradenhead valve, the beginning pressure is greater than 25 psi, sampling is required.</p> <p>2) If pressure remains at the conclusion of the test, or if any liquids were present during the test, sampling is required.</p> <p>The Form 17 shall be submitted within 10 days of the test. Sampling shall comply with Operator Guidance - Bradenhead Testing and Reporting Instructions. If samples are collected, copies of all final laboratory analytical results shall be provided to the ECMC within three (3) months of collecting the samples.</p> <p>If there is a need for sampling, contact ECMC engineering for verification of plugging procedure.</p>
	<p>Consistent with Rule 911.a, a Form 27 must be approved prior to cut and cap, conducting flowline abandonment, or removing production equipment. Allow 30 days for Director review of the Form 27; include the Form 27 document number on the Form 44 for offsite flowline abandonment (if applicable) and on the Form 6 Subsequent.</p> <p>Properly abandon flowlines per Rule 1105. If flowlines will be abandoned in place, include with the Form 27: pressure test results conducted in the prior 12 months as well as identification of any document numbers for a ECMC Spill/Release Report, Form 19, associated with the abandoned line.</p>
	<p>1) Provide electronic Form 42 Notice of MIRU 2 business days ahead of operations and electronic Form 42 Notice of Plugging Operations 48 hours prior to mobilizing for plugging operations. These are two separate notifications, required by Rules 405.e and 405.i.</p> <p>2) Pump surface casing shoe plug at 475' only after isolation has been verified. If surface casing cement is not circulated to surface, shut-in, WOC 4 hours then tag plug – must be at 52' or shallower and provide a minimum of 10 sx plug at the surface.</p> <p>3) Leave at least 100' of cement in the wellbore for each plug without mechanical isolation.</p> <p>4) After cut and prior to cap, verify isolation by either a 15 minute bubble test or 15 minute optical gas imaging recording. If there is indication of flow contact ECMC Engineering. Provide a statement on the 6SRA which method was used and what was observed. Retain records of final isolation test for 5 years.</p> <p>5) With the Form 6 SRA operator must provide written documentation which positively affirms each COA listed above has been addressed.</p>
8 COAs	

ATTACHMENT LIST

<u>Att Doc Num</u>	<u>Name</u>
404500831	FORM 6 INTENT SUBMITTED
404500883	WELLBORE DIAGRAM

Total Attach: 2 Files

General Comments

<u>User Group</u>	<u>Comment</u>	<u>Comment Date</u>
Permit	Confirmed as-drilled well location. Confirmed perf intervals docnum: 163222, 319483. Production reporting up-to-date. No other forms in process. Reviewed WBDs. Pass.	01/13/2026
OGLA	LAS review complete.	01/12/2026
OGLA	Location is in CPW mapped Mule Deer Winter Concentration Area and Mule Deer Severe Winter Range High Priority Habitats. Although plugging and abandonment operations with heavy equipment will be allowed, the Operator is strongly encouraged to avoid them between December 1 through April 30.	01/12/2026
Engineer	Deepest Water Well within 1 Mile – 1252' SB5 Base of Fox Hills - 1302' SB5 Base of Lower Arapahoe - 617' SB5 Base of Upper Arapahoe - 350' SB5 Base of Denver - 102' Denver / 5003 / 5077 / 27.9 / 102 / 28 / 7.59 / NNT Upper Arapahoe / 4755 / 4974 / 75.9 / 350 / 131 / 20.64 / NNT Lower Arapahoe / 4488 / 4680 / 80.8 / 617 / 425 / 21.98 / NT Laramie-Fox Hills / 3803 / 4045 / 143.2 / 1302 / 1060 / 34.37 / NT	01/12/2026

Total: 4 comment(s)