



99999999

UNITED STATES
THE INTERIOR
SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

Colorado - 60768

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back a well in a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL GAS WELL OTHER

2. NAME OF OPERATOR

3. ADDRESS OF OPERATOR

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface

750' ETL - 700' PTL - Sec. 4, T9N, R79W - 6th P.M.

UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

12. COUNTY OR PARISH 13. STATE

Jackson Colorado

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3200' Ord - 6111 RB (All rods, Ord)

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Moved in pulling unit 9-3-1964. PSTD - 6155' Ground.
Set 13 sack cement plug in 5 1/2" casing from 6155' to 6055' C.L.
Shot and pulled 1934.45' of 5 1/2" 21/2 J-5' casing.
Set 12 sack cement plug from 5004' to 5004' C.L.
Set 17 sack cement plug in and out of 8 5/8" casing from 370 to 320.
Set 2 sack cement plug in top of surface casing with 1" x 10' marker, cemented 6" in casing.
Hole between cement plugs filled with 9" mud, cement plugs were set with bailer.
Well site currently conditioned for final inspection.

BEST IMAGE
AVAILABLE

057-05116

p ya oil

DVR	
WRS	
HHM	
JAM	
FJP	<input checked="" type="checkbox"/>
JJD	
FILE	

18. I hereby certify that the foregoing is true and correct

SIGNED J. C. [Signature]

TITLE District Manager

DATE 9-22-1964

(This space for Federal or State office use)

APPROVED BY [Signature]
CONDITIONS OF APPROVAL, IF ANY:

TITLE Director
COLO. OIL & GAS COMM.

DATE OCT 9 1964

USRS(3), COCCC(2), [unclear]



00822805

*See Instructions on Reverse Side