



99999999

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE* (Other instructions on reverse side)

Form approved. Budget Bureau No. 42-R1424.

075-06780

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO. Colo - 037874

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

1. OIL WELL [] GAS WELL [] OTHER P & A

RECEIVED BR OF OIL & GAS OPERATIONS

2. NAME OF OPERATOR Continental Oil Company

FEB 24 1965

3. ADDRESS OF OPERATOR Box 680, Casper, Wyoming

U. S. GEOLOGICAL SURVEY DENVER, COLORADO

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.) See also space 17 below.) At surface

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME Canoco - Government

9. WELL NO. 24 No. 3

10. FIELD AND POOL, OR WILDCAT Red Lion - "D" Sand

11. SEC., T., R., M., OR BLK. AND SURVEY OR ARBA

SE - NE 1980' FNL - 660' FNL Sec. 24, T. 10 N., R. 48 W.

Sec. 24-T10N-R48W

14. PERMIT NO. 64 502

15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3941 RB - 3932 GR

12. COUNTY OR PARISH Logan 13. STATE Colorado

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF [] PULL OR ALTER CASING [] FRACTURE TREAT [] MULTIPLE COMPLETE [] SHOOT OR ACIDIZE [] ABANDON* [] REPAIR WELL [] CHANGE PLANS [] (Other) []

WATER SHUT-OFF [] REPAIRING WELL [] FRACTURE TREATMENT [] ALTERING CASING [] SHOOTING OR ACIDIZING [] ABANDONMENT* [X] (Other) []

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Well spudded 10 A.M. 2-10-65 and drilled to TD of 3905 RB with rotary tools. 8 5/8" - 2 1/4" J-55 Casing set at 410 RB with 260 sacks cement. Drilled 7 7/8" hole to TD. Ran Schlumberger Sonic, GR-IES, and Caliper logs. Well P & A 2-15-65. Rig released 1:30 A.M. 2-16-65.

Filled hole with heavy mud. Set 30 sacks cement plug 380 to 420 RB. Set 5 sacks cement plug in top of surface casing with regulation marker.



00789528

Table with names (DVR, WRS, HHM, JAM, FJP, JJD, FILE) and checkmarks.

18. I hereby certify that the foregoing is true and correct

SIGNED J. O. O'NEAL for. TITLE District Manager DATE 2-23-65

APPROVED BY [Signature] TITLE District Engineer DATE 2/12/65

*See Instructions on Reverse Side