



99999999

GAS CONSERVATION COMMISSION THE STATE OF COLORADO

RECEIVED

FEB 21 1968

075-06098

File in duplicate for Patented and Federal lands. File in triplicate for State lands.

COLO. OIL & GAS CONS. COMM.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

Form fields 1-15 containing well details: 1. OIL WELL [X] GAS WELL [] OTHER []; 2. NAME OF OPERATOR PAT'S POWER TONGS, INC.; 3. ADDRESS OF OPERATOR Box 702, Grand Junction, Colorado 81501; 4. LOCATION OF WELL 4016' FNL, 660' FWL (C-W/2 Lot 9, Sec. 5); 5. ELEVATIONS 4411 ft. D.F.; 7. UNIT AGREEMENT NAME Liberty "J" Sand; 8. FARM OR LEASE NAME L. A. Yenter; 9. WELL NO. 1; 10. FIELD AND POOL, OR WILDCAT Liberty; 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA S. 8, T. 8N., R. 54W.; 12. COUNTY OR PARISH Logan; 13. STATE Colo.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF [] FRACTURE TREAT [] SHOOT OR ACIDIZE [] REPAIR WELL [] (Other) []

PULL OR ALTER CASING [] MULTIPLE COMPLETE [] ABANDON [] CHANGE PLANS []

WATER SHUT-OFF [] FRACTURE TREATMENT [] SHOOTING OR ACIDIZING [] (Other) []

REPAIRING WELL [] ALTERING CASING [X] ABANDONMENT []

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Date of work Completed Dec. 5, 1967

LU-7

Dumped sand and filled 5 1/2" casing from 5361 to 5240 ft. depth. Set 15 sack cement plug on top of sand from 5240 to 5110 ft. depth.

Shot of 5 1/2" casing @ 4190' depth and pulled.

Filled hole with heavy mud from 5110' to 125' depth.

Set 10 sack plug over base of 8-5/8" surface casing from 95' to 125' depth.

Filled hole with heavy mud to 17 ft. from bottom of the cellar

Set 5 sack cement plug in top of 8-5/8" surface casing from 17 ft. depth to bottom of cellar. Welded steel plate to top of surface casing. Filled cellar with rocks and dirt and topped off with top soil.

Plugged and Abandoned 12-5-67

Table with columns for initials (DVR, FJP, HMM, JMM, JJD) and checkmarks. Includes handwritten note 'Ex Oil Prod.' and a red circle around the table.



00817140

18. I hereby certify that the foregoing is true and correct

SIGNED R.A. Higgins

TITLE Agent/Pat's Power Tong's DATE 2-19-68

(This space for Federal or State office use)

APPROVED BY D.V. Rogers

TITLE Director DATE 2/21/68

CONDITIONS OF APPROVAL, IF ANY: 7-10

T